

UNIPLUS⁺ SYSTEM V

Administrator's Manual

Copyright © 1983 UniSoft Corporation.

Portions of this material have been previously copyrighted by:

Bell Telephone Laboratories, Incorporated, 1980

Western Electric Company, Incorporated, 1983

Regents of the University of California

Holders of a UNIX and UniPlus⁺ software license are permitted to copy this document, or any portion of it, as necessary for licensed use of the software, provided this copyright notice and statement of permission are included.

UniSoft

UNIX is a Trademark of Bell Telephone Laboratories, Inc.

UniPlus⁺ is a Trademark of UniSoft Corporation of Berkeley.

INTRODUCTION

This manual is intended to supplement the information contained in the *UniPlus⁺ User's Manual* and to provide an easy reference volume for those who must administer the UniPlus⁺ system. Accordingly, only those commands and descriptions deemed appropriate for system administrators have been included here.

This manual is divided into three sections:

1. System Maintenance Commands and Application Programs
7. Special Files
8. System Maintenance Procedures

Throughout this volume, each reference of the form *name*(1M), *name*(7), or *name*(8), refers to entries in this manual, while all other references to entries of the form *name*(N), where *N* is a number possibly followed by a letter, refer to entry *name* in Section *N* of the *UniPlus⁺ User's Manual*.

Section 1 (*System Maintenance Commands and Application Programs*) contains system maintenance programs such as *fsck*, *mkfs*, etc., which generally reside in the directory */etc*; these entries carry a subsection designation of "M" for cross referencing reasons.

Section 7 (*Special Files*) discusses the characteristics of each system file that actually refers to an input/output device. The names in this section generally refer to device names for the hardware, rather than to the names of the special files themselves.

Section 8 (*System Maintenance Procedures*) discusses crash recovery and boot procedures.

Each section consists of a number of independent entries of a page or so each. The name of the entry appears in the upper corners of its pages. Entries within each section are alphabetized, with the exception of the introductory entry that precedes each section. The page numbers of each entry start at 1. The version date of the entry appears in the lower left corner of each page. Some entries may describe several routines, commands, etc. In such cases, the entry appears only once, alphabetized under its "major" name.

All entries are based on a common format, not all of whose parts always appear:

The **NAME** part gives the name(s) of the entry and briefly states its purpose.

The **SYNOPSIS** part summarizes the use of the program being described. A few conventions are used, particularly in Section 1 (*Commands*):

Boldface strings are literals and are to be typed just as they appear.

Italic strings usually represent substitutable argument prototypes and program names found elsewhere in the manual.

Square brackets [] around an argument prototype indicate that the argument is optional. When an argument prototype is given as "name" or "file", it always refers to a *file* name.

Ellipses ... are used to show that the previous argument prototype may be repeated.

A final convention is used by the commands themselves. An argument beginning with a minus -, plus +, or equal sign = is often taken to be some sort of flag argument, even if it appears in a position where a file name could appear. Therefore, it is unwise to have files whose names begin with -, +, or =.

The **DESCRIPTION** part discusses the subject at hand.

The **EXAMPLE** part gives example(s) of usage, where appropriate.

The **FILES** part gives the file names that are built into the program.

The **SEE ALSO** part gives pointers to related information.

The **DIAGNOSTICS** part discusses the diagnostic indications that may be produced. Messages that are intended to be self-explanatory are not listed.

The **WARNINGS** part points out potential pitfalls.

The **BUGS** part gives known bugs and sometimes deficiencies. Occasionally, the suggested fix is also described.

On most systems, all entries are available on-line via the *man(1)* command, q.v.

Permuted Index

At the front of each volume there is a table of contents and a permuted index. The permuted index is a computer-generated index that uses the information in the **NAME** part of each entry in the User's and Administrator's Manuals. The permuted index contains three columns. The center column is an alphabetic list of keywords as they appear in the **NAME** part of the entries. The last column is the entry that the keyword in the center column refers to. This entry is followed by the appropriate section number in parentheses. The first column contains the remaining information from the **NAME** part that either precedes or follows the keyword.

For example, to look for a text editor, scan the center column for the word "editor". There are several index lines containing an "editor" reference, i.e.:

```
ed, red: text  editor.          . . . . . ed(1)
files. ld: link  editor for common object . . . . . ld(1)
```

You can then turn to the entries listed in the last column, *ed(1)* and *ld(1)*, to find information on the editor.

TABLE OF CONTENTS

1. System Maintenance Commands and Application Programs

| | |
|--------------|--|
| intro | introduction to system maintenance commands and application programs |
| accept | allow/prevent LP requests |
| acct | overview of accounting and miscellaneous accounting commands |
| acctcms | command summary from per-process accounting records |
| acctcon | connect-time accounting |
| acctmerg | merge or add total accounting files |
| acctprc | process accounting |
| acctsh | shell procedures for accounting |
| badblk | program to set or update bad block information |
| bcopy | interactive block copy |
| brc | system initialization shell scripts |
| chroot | change root directory for a command |
| clri | clear i-node |
| cron | clock daemon |
| dcopy | copy file systems for optimal access time |
| devnm | device name |
| df | report number of free disk blocks |
| diskformat | format a disk |
| disktune | tune floppy disk settling time parameters |
| errdead | extract error records from dump |
| errdemon | error-logging daemon |
| errpt | process a report of logged errors |
| errstop | terminate the error-logging daemon |
| ff | list file names and statistics for a file system |
| filesave | daily/weekly UNIX file system backup |
| finc | fast incremental backup |
| frec | recover files from a backup tape |
| fsck | file system consistency check and interactive repair |
| fsdb | file system debugger |
| fuser | identify processes using a file or file structure |
| fwtmp | manipulate connect accounting records |
| getty | set terminal type, modes, speed, and line discipline |
| init | process control initialization |
| install | install commands |
| killall | kill all active processes |
| link | exercise link and unlink system calls |
| lpadmin | configure the LP spooling system |
| lpsched | start/stop the LP request scheduler and move requests |
| mkfs | construct a file system |
| mkfs512 | construct a file system |
| mklost+found | make a lost+found directory for fsck |
| mknod | build special file |
| mount | mount and dismount file system |
| mkdir | move a directory |
| ncheck | generate names from i-numbers |
| profiler | operating system profiler |
| pstat | print system facts |
| pwck | password/group file checkers |
| runacct | run daily accounting |
| sar | system activity report package |
| setmnt | establish mount table |
| shutdown | terminate all processing |
| updater | update files between two machines |

uuclean uucp spool directory clean-up
 uusub monitor uucp network
 vchk version checkup
 volcopy copy file systems with label checking
 wall write to all users
 whodo who is doing what

7. Special Files

intro introduction to special files
 aliases aliases file for delivermail
 err error-logging interface
 hosts host table for bnet
 mem core memory
 null the null file
 termio general terminal interface
 tty controlling terminal interface

8. System Maintenance Procedures

intro introduction to system maintenance procedures
 boot startup procedures
 crash what to do when the system crashes
 delivermail deliver mail to arbitrary people
 netmail the bnet network mail system
 netmailer deliver mail to bnet

PERMUTED INDEX

/functions of HP 2640 and 2621-series terminals. hp.1
 handle special functions of HP 2640 and 2621-series/ hp: hp.1
 archiver. hpio: HP 2645A terminal tape file hpio.1
 functions of DASI 300 and/ 300, 300s: handle special 300.1
 /special functions of DASI 300 and 300s terminals. 300.1
 of DASI 300 and 300s/ 300, 300s: handle special functions 300.1
 functions of DASI 300 and 300s terminals. /special 300.1
 l3tol, l3tol3: convert between 3-byte integers and long/ l3tol.3c
 comparison. diff3: 3-way differential file diff3.1
 Tektronix 4014 terminal. 4014: paginator for the 4014.1
 paginator for the Tektronix 4014 terminal. 4014: 4014.1
 of the DASI 450 terminal. 450: handle special functions 450.1
 special functions of the DASI 450 terminal. 450: handle 450.1
 long integer and base-64/ a64l, l64a: convert between a64l.3c
 value. abort: generate an IOT fault. abort.3c
 abs: return integer absolute abs: return integer absolute abs.3c
 /floor, ceiling, remainder, absolute value functions. floor.3m
 socket. accept: accept a connection on a accept.2
 a socket. accept: accept a connection on accept.2
 LP requests. accept, reject: allow/prevent accept.1m
 utime: set file access and modification times. utime.2
 of a file. touch: update access and modification times touch.1
 accessibility of a file. access: determine access.2
 machine/ sputl, sgetl: access long numeric data in a sputl.3x
 phys: allow a process to access physical addresses. phys.2
 sadp: disk access profiler. sadp.1
 copy file systems for optimal access time. dcopy: dcopy.1m
 /setutent, endutent, utmpname: access utmp file entry. getut.3c
 access: determine accessibility of a file. access.2
 enable or disable process accounting. acct: acct.2
 acctcon2: connect-time accounting. acctcon1, acctcon.1m
 acctprc1, acctprc2: process accounting. acctprc.1m
 turnacct: shell procedures for accounting. /startup, acctsh.1m
 runacct: run daily accounting. runacct.1m
 /accton, acctwtmp: overview of accounting and miscellaneous/ acct.1m
 accounting and miscellaneous accounting commands. /of acct.1m
 acct: per-process accounting file format. acct.4
 search and print process accounting file(s). acctcom: acctcom.1
 acctmerg: merge or add total accounting files. acctmerg.1m
 summary from per-process accounting records. /command acctcms.1m
 wtmpfix: manipulate connect accounting records. fwtmp, fwtmp.1m
 process accounting. acct: enable or disable acct.2
 file format. acct: per-process accounting acct.4
 per-process accounting/ acctcms: command summary from acctcms.1m
 process accounting file(s). acctcom: search and print acctcom.1
 connect-time accounting. acctcon1, acctcon2: acctcon.1m
 accounting. acctcon1, acctcon2: connect-time acctcon.1m
 acctwtmp: overview of/ acctdisk, acctdusg, accton, acct.1m
 overview of/ acctdisk, acctdusg, accton, acctwtmp: acct.1m
 accounting files. acctmerg: merge or add total acctmerg.1m
 acctdisk, acctdusg, accton, acctwtmp: overview of/ acct.1m
 accounting. acctprc1, acctprc2: process acctprc.1m
 acctprc2: process accounting. acctprc.1m
 acctwtmp: overview of/ acctwtmp: acct.1m
 sin, cos, tan, asin, acos, atan, atan2:/ trig.3m
 killall: kill all active processes. killall.1m
 current SCCS file editing activity. sact: print sact.1
 report process data and system activity. /time a command; timex.1
 sag: system activity graph. sag.1g
 sa1, sa2, sadc: system activity report package. sar.1m

sar: system
 random, hopefully interesting,
 formatting/ mosd: the OSDD
 acctmrg: merge or
 up internet hosts by name or
 socket. socketaddr: return
 a process to access physical
 SCCS files.
 admin: create and
 administer SCCS files.
 game.
 alarm: set a process's
 clock.
 delivermail.
 aliases:
 aliases:
 earth. aliens: The
 attack the earth.
 change data segment space
 realloc, calloc: main memory
 physical addresses. phys:
 accept, reject:
 information for bad block/
 for bad block/ altblk:
 sort: sort
 terminal. worms:
 rain:
 bcd: convert to
 editor output.
 introduction to commands and
 maintenance commands and
 maintainer.
 format.
 number: convert
 delivermail: deliver mail to
 language. bc:
 cpio: format of cpio
 tp: manipulate tape
 maintainer. ar:
 ar:
 HP 2645A terminal tape file
 tar: tape file
 cpio: copy file
 command. xargs: construct
 getopt: get option letter from
 echo: echo
 expr: evaluate
 bc: arbitrary-precision
 number facts.
 expr: evaluate arguments
 characters. asa: interpret
 control characters.
 ascii: map of
 /translates object files into
 set.
 long integer and base-64
 number. atof: convert
 and/ ctime, localtime, gmtime,
 trigonometric/ sin, cos, tan,
 help:
 as:
 output. a.out:
 assertion.
 assert: verify program
 activity reporter. sar.1
 adage. fortune: print a fortune.6
 adapter macro package for mosd.5
 adb: debugger. adb.1
 add total accounting files. acctmrg.1m
 address. rhost, raddr: look rhost.3
 address associated with a socketaddr.2
 addresses. phys: allow phys.2
 admin: create and administer admin.1
 administer SCCS files. admin.1
 adventure: an exploration adventure.6
 alarm clock. alarm.2
 alarm: set a process's alarm alarm.2
 aliases: aliases file for aliases.7
 aliases file for delivermail. aliases.7
 alien invaders attack the aliens.6
 aliens: The alien invaders aliens.6
 allocation. brk, sbrk: brk.2
 allocator. malloc, free, malloc.3c
 allow a process to access phys.2
 allow/prevent LP requests. accept.1m
 altblk: alternate block altblk.4
 alternate block information altblk.4
 and/or merge files. sort.1
 animate worms on a display worms.6
 animated raindrops display. rain.6
 antique media. bcd.6
 a.out: assembler and link a.out.4
 application programs. intro: intro.1
 application programs. /system intro.1m
 ar: archive and library ar.1
 ar: archive (library) file ar.4
 Arabic numerals to English. number.6
 arbitrary people. delivermail.8
 arbitrary-precision arithmetic bc.1
 archive. cpio.4
 archive. tp.1
 archive and library ar.1
 archive (library) file format. ar.4
 archiver. hpio: hpio.1
 archiver. tar.1
 archives in and out. cpio.1
 argument list(s) and execute xargs.1
 argument vector. getopt.3c
 arguments. echo.1
 arguments as an expression. expr.1
 arithmetic language. bc.1
 arithmetic: provide drill in arithmetic.6
 as an expression. expr.1
 as: assembler. as.1
 ASA carriage control asa.1
 asa: interpret ASA carriage asa.1
 ASCII character set. ascii.5
 ASCII formats suitable for/ hex.1
 ascii: map of ASCII character ascii.5
 ASCII string. /convert between a64l.3c
 ASCII string to floating-point atof.3c
 asctime, tzset: convert date ctime.3c
 asin, acos, atan, atan2: trig.3m
 ask for help. help.1
 assembler. as.1
 assembler and link editor a.out.4
 assert: verify program assert.3x
 assertion. assert.3x

setbuf: assign buffering to a stream. setbuf.3s
 associated with a socket. socketaddr.2
 atan, atan2: trigonometric/ trig.3m
 atan2: trigonometric/ sin, trig.3m
 floating-point number. atof.3c
 atoi: convert string to strtol.3c
 atoi: convert string to strtol.3c
 aliens: The alien invaders aliens.6
 autorobots: Escape from the autorobots.6
 automatic robots. autorobots.6
 wait:
 processing language. awk.1
 ungetc: push character ungetc.3s
 back: the game of backgammon. back.6
 backgammon. back.6
 backup. filesave, tapesave: filesave.1m
 backup. fnc.1m
 backup tape. freq.1m
 bad block handling. /alternate altblk.4
 bad block information. badblk.1m
 badblk: program to set or badblk.1m
 banner: make posters. banner.1
 banner on printer. banner7.1
 banner7: print large banner on banner7.1
 base. termcap: termcap.5
 port. ttytype: data ttytype.4
 between long integer and
 (visual) display editor a64l.3c
 portions of path names. vi.1
 arithmetic language. basename.1
 bc: arbitrary-precision bc.1
 bcd: convert to antique media. bcd.6
 bcheckrc, rc, powerfail: brc.1m
 bcopy: interactive block copy. bcopy.1m
 bdiff: big diff. bdiff.1
 beautifier. cb.1
 cb: C program ls7.1
 list contents of directory ls7.1
 j0, j1, jn, y0, y1, yn:
 Bessel functions. bessel.3m
 bfs: big file scanner. bfs.1
 strings in an object, or other
 fread, fwrite: strings.1
 bsearch: fread.3s
 binary input/output. bsearch.3c
 binary search. tsearch.3c
 binary search trees. tsearch, strip.1
 remove symbols and relocation reset.1
 reset: reset the teletype bj.6
 bj: the game of black jack. bj.6
 black jack. sync.1
 block. bcopy.1m
 block copy. sum.1
 sum: print checksum and bad
 block information for bad
 program to set or update bad
 block/ altblk: alternate altblk.4
 altblk: alternate altblk.4
 block transfer data. df.1m
 blocks. sum7.1
 blocks in a file. blt.3
 blt, blt512: block transfer blt.3
 blt512: block transfer data. hosts.7
 bnet. netmail.8
 bnet network mail system. boot.8
 boot: startup procedures. brc.1m
 brc, bcheckrc, rc, powerfail: brk.2
 brk, sbrk: change data segment bs.1
 bs: a compiler/interpreter for bsearch.3c
 bsearch: binary search. bsearch.3c

stdio: standard buffered input/output package. stdio.3s
 setbuf: assign buffering to a stream. setbuf.3s
 mknod: build special file. mknod.1m
 swab: swap bytes. swab.3c
 cc: C compiler. cc.1
 cflow: generate C flow graph. cflow.1
 cpp: the C language preprocessor. cpp.1
 maintain a tags file for a C program. ctags: ctags.1
 cb: C program beautifier. cb.1
 lint: a C program checker. lint.1
 cxref: generate C program cross reference. cxref.1
 message file by massaging C source. /create an error mkstr.1
 cal: print calendar. cal.1
 dc: desk calculator. dc.1
 cal: print calendar. cal.1
 calendar: reminder service. calendar.1
 call. stat: stat.5
 data returned by stat system call another UNIX System. cu.1c
 cu: malloc, free, realloc, calloc: main memory allocator. malloc.3c
 link and unlink system calls. link, unlink: exercise link.1m
 intro: introduction to system calls and error numbers. intro.2
 to an LP line printer. lp, cancel: send/cancel requests lp.1
 termcap: terminal capability data base. termcap.5
 cribbage: the card game cribbage. cribbage.6
 pnch: file format for card images. pnch.4
 asa: interpret ASA carriage control characters. asa.1
 files. cat: concatenate and print cat.1
 cb: C program beautifier. cb.1
 cc: C compiler. cc.1
 od: change working directory. cd.1
 commentary of an SCCS delta. cdc: change the delta cdc.1
 ceiling, remainder,/ floor, ceil, fmod, fabs: floor, floor.3m
 /ceil, fmod, fabs: floor, ceiling, remainder, absolute/ floor.3m
 cflow: generate C flow graph. cflow.1
 (change) to an SCCS file. delta.1
 pipe: create an interprocess channel. pipe.2
 stream. ungetc: push character back into input ungetc.3s
 and neqn. eqnchar: special character definitions for eqn eqnchar.5
 file. freq: report on character frequencies in a freq.1
 user. cuserid: get character login name of the cuserid.3s
 /getchar, fgetc, getw: get character or word from stream. getc.3s
 /putchar, fputc, putw: put character or word on a stream. putc.3s
 ascii: map of ASCII character set. ascii.5
 interpret ASA carriage control characters. asa: asa.1
 _tolower, toascii: translate characters. /_toupper, conv.3c
 iscntrl, isascii: classify characters. /isprint, isgraph, ctype.3c
 tr: translate characters. tr.1
 given/ sumdir: sum and count characters in the files in the sumdir.1
 lastlogin, monacct, nulladm,/ chargefee, ckpacct, dodisk, acctsh.1m
 killer robots. chase: Try to escape the chase.6
 directory. chdir: change working chdir.2
 /dfsk: file system consistency check and interactive repair. fsck.1m
 constant-width text for/ cw, checkcw: prepare cw.1
 text for nroff or/ eqn, neqn, checkedq: format mathematical eqn.1
 lint: a C program checker. lint.1
 grpk: password/group file checkers. pwck, pwck.1m
 copy file systems with label checking. volcopy, labelit: volcopy.1m
 systems processed by fsck. checklist: list of file checklist.4
 formatted with the/ mm, osdd, checkmm: print/check documents mm.1
 file. sum: print checksum and block count of a sum.1
 vchk: version checkup. vchk.1m
 chown, chgrp: change owner or group. chown.1
 times: get process and child process times. times.2
 terminate. wait: wait for child process to stop or wait.2

chmod: change mode. chmod.1
 chmod: change mode of file. chmod.2
 chown: change owner and group chown.2
 of a file. chown, chgrp: change owner or chown.1
 group. chroot: change root directory. chroot.2
 for a command. chroot: change root directory chroot.1m
 monacct, nulladm,/ chargefee, ckpacct, dodisk, lastlogin, acctsh.1m
 isgraph, iscntrl, isascii: classify characters. /isprint, ctype.3c
 uuclean: uucp spool directory clean-up. uuclean.1m
 clear: clear terminal screen. clear.1
 cli: clear i-node. cli.1m
 clear: clear terminal screen. clear.1
 status/ ferror, feof, clearerr, fileno: stream ferror.3s
 (command interpreter) with C-like syntax. csh: a shell csh.1
 alarm: set a process's alarm clock. alarm.2
 cron: clock daemon. cron.1m
 clock: report CPU time used. clock.3c
 close: close a file descriptor. close.2
 descriptor. close: close a file close.2
 fclose, fflush: close or flush a stream. fclose.3s
 cli: clear i-node. cli.1m
 cmp: compare two files. cmp.1
 line-feeds. col: filter reverse col.1
 comb: combine SCCS deltas. comb.1
 combine SCCS deltas. comb.1
 common to two sorted files. comm: select or reject lines comm.1
 change root directory for a command. chroot: chroot.1m
 system: issue a shell command. system.3s
 test: condition evaluation command. test.1
 time: time a command. time.1
 argument list(s) and execute command. xargs: construct xargs.1
 nice: run a command at low priority. nice.1
 env: set environment for command execution. env.1
 uux: unix to unix command execution. uux.1c
 (sh/ nohup: run a command immune to hangups nohup.1
 C-like syntax. csh: a shell (command interpreter) with csh.1
 getopt: parse command options. getopt.1
 /shell, the standard/restricted command programming language. sh.1
 and system/ time: time a command; report process data timex.1
 per-process/ acctcms: command summary from acctcms.1m
 and miscellaneous accounting commands. /of accounting acct.1m
 install: install commands. install.1m
 intro: introduction to commands and application/ intro.1
 /to system maintenance commands and application/ intro.1m
 at: execute commands at a later time. at.1
 cdc: change the delta. cdc.1
 comm: select or reject lines. comm.1
 socket: create an endpoint for communication. socket.2
 ipcs: report inter-process communication facilities/ ipcs.1
 stdipc: standard interprocess communication package. stdipc.3c
 diff: differential file comparator. diff.1
 cmp: compare two files. cmp.1
 SCCS file. scsdiff: compare two versions of an scsdiff.1
 diff3: 3-way differential file comparison. diff3.1
 dircmp: directory comparison. dircmp.1
 regcmp: regular expression compile. regcmp.1
 expression. regcmp, regex: compile and execute regular regcmp.3x
 regex: regular expression compile and match routines. regex.5
 cc: C compiler. cc.1
 fortran: FORTRAN compiler. fortran.1
 yacc: yet another compiler/compiler. yacc.1
 modest-sized programs. bs: a compiler/interpreter for bs.1
 erf, erfc: error function and complementary error function. erf.3m
 wait: await completion of process. wait.1

pack, pcat, unpack: compress and expand files. pack.1
 cat: concatenate and print files. cat.1
 test: condition evaluation command. test.1
 uvar: returns system-specific configuration information. uvar.2
 system. lpadmin: configure the LP spooling lpadmin.1m
 fwtmp, wtmpfix: manipulate connect accounting records. fwtmp.1m
 on a socket. connect: initiate a connection connect.2
 an out-going terminal line connection. dial: establish dial.3c
 accept: accept a connection on a socket. accept.2
 connect: initiate a connection on a socket. connect.2
 acctcon1, acctcon2: connect-time accounting. acctcon.1m
 fsck, dfsc: file system consistency check and/ fsck.1m
 cw, checkcw: prepare constant-width text for troff. cw.1
 mkfs: construct a file system. mkfs.1m
 mkfs512: construct a file system. mkfs512.1m
 execute command. xargs: construct argument list(s) and xargs.1
 nroff/troff, tbl, and eqn constructs. deroff: remove deroff.1
 ls: list contents of directories. ls.1
 (Berkeley version). ls7: list contents of directory ls7.1
 csplit: context split. csplit.1
 fcntl: file control. fcntl.2
 uucp status inquiry and job control. uustat: uustat.1c
 vc: version control. vc.1
 asa: interpret ASA carriage control characters. asa.1
 ioctl: control device. ioctl.2
 init, telinit: process control initialization. init.1m
 msgctl: message control operations. msgctl.2
 semctl: semaphore control operations. semctl.2
 shmctl: shared memory control operations. shmctl.2
 fcntl: file control options. fcntl.5
 tcp: Internet Transmission Control Protocol. tcp.5
 interface. tty: controlling terminal tty.7
 terminals. term: conventional names for term.5
 units: conversion program. units.1
 dd: convert and copy a file. dd.1
 English. number: convert Arabic numerals to number.6
 floating-point number. atof: convert ASCII string to atof.3c
 integers and/ l3tol, ltol3: convert between 3-byte l3tol.3c
 and base-64 ASCII/ a64l, l64a: convert between long integer a64l.3c
 /gmtime, asctime, tzset: convert date and time to/ ctime.3c
 to string. ecvt, fcvt, gcvt: convert floating-point number ecvt.3c
 scanf, fscanf, sscanf: convert formatted input. scanf.3s
 strtol, atol, atoi: convert string to integer. strtol.3c
 bcd: convert to antique media. bcd.6
 bcopy: interactive block copy. bcopy.1m
 rcp: remote file copy rcp.1
 uulog, uname: unix to unix copy. uucp, uucp.1c
 System-to-UNIX System file copy. /uupick: public UNIX uuto.1c
 dd: convert and copy a file. dd.1
 cpio: copy file archives in and out. cpio.1
 access time. dcopy: copy file systems for optimal dcopy.1m
 checking. volcopy, labelit: copy file systems with label volcopy.1m
 cp, ln, mv: copy, link or move files. cp.1
 file. core: format of core image core.4
 core: format of core image file. core.4
 mem, kmem: core memory. mem.7
 atan2: trigonometric/ sin, cos, tan, asin, acos, atan, trig.3m
 functions. sinh, cosh, tanh: hyperbolic sinh.3m
 wc: word count. wc.1
 sum7: sum and count blocks in a file. sum7.1
 in the given/ sumdir: sum and count characters in the files sumdir.1
 sum: print checksum and block count of a file. sum.1
 files. cp, ln, mv: copy, link or move cp.1
 cpio: format of cpio archive. cpio.4

and out. cpio: copy file archives in cpio.1
 cpio: format of cpio archive. cpio.4
 cpp: the C language cpp.1
 sethostname: set name of host sethostname.2
 clock: report CPU time used. clock.3c
 craps: the game of craps. craps.6
 system crashes. crash: what to do when the crash.8
 what to do when the system crashes. crash: crash.8
 rewrite an existing one. creat: create a new file or creat.2
 file. tmpnam, tempnam: create a name for a temporary tmpnam.3s
 an existing one. creat: create a new file or rewrite creat.2
 fork: create a new process. fork.2
 tmpfile: create a temporary file. tmpfile.3s
 communication. socket: create an endpoint for socket.2
 by messaging C source. mkstr: create an error message file mkstr.1
 channel. pipe: create an interprocess pipe.2
 files. admin: create and administer SCCS admin.1
 umask: set and get file creation mask. umask.2
 cribbage: the card game cribbage. cribbage.6
 cribbage: the card game cribbage.6
 cron: clock daemon. cron.1m
 cross reference. cxref: generate C program cxref.1
 more: file perusal filter for crt viewing. more.1
 generate DES encryption. crypt: encode/decode. crypt.1
 interpreter) with C-like/ crypt, setkey, encrypt: crypt.3c
 csh: a shell (command csh.1
 csplit: context split. csplit.1
 terminal. ct: spawn getty to a remote ct.1c
 for a C program. ctags: maintain a tags file ctags.1
 for terminal. ctermid: generate file name ctermid.3s
 asctime, tzset: convert date/ ctime, localtime, gmtime, ctime.3c
 cu: call another UNIX System. cu.1c
 ttt, cubic: tic-tac-toe. ttt.6
 gethostname: get name of current host. gethostname.2
 hostname: set or print name of current host system hostname.1
 activity. sact: print current SCCS file editing sact.1
 uname: print name of current UNIX System. uname.1
 name: get name of current UNIX system. uname.2
 slot in the utmp file of the current user. /find the ttyslot.3c
 getcwd: get pathname of current working directory. getcwd.3c
 spline: interpolate smooth curve. spline.1g
 name of the user. cuserid: get character login cuserid.3s
 of each line of a file. cut: cut out selected fields cut.1
 each line of a file. cut: cut out selected fields of cut.1
 constant-width text for/ cw, checkcw: prepare cw.1
 cross reference. cxref: generate C program cxref.1
 cron: clock daemon. cron.1m
 errdemon: error-logging daemon. errdemon.1m
 terminate the error-logging daemon. errstop: errstop.1m
 runacct: run daily accounting. runacct.1m
 backup. filesave, tapesave: daily/weekly UNIX file system filesave.1m
 /handle special functions of DASI 300 and 300s terminals. 300.1
 special functions of the DASI 450 terminal. /handle 450.1
 blt, blt512: block transfer data. blt.3
 prof: display profile data. prof.1
 /time a command: report process data and system activity. timex.1
 termcap: terminal capability data base. termcap.5
 port. ttytype: data base of terminal types by ttytype.4
 /sgctl: access long numeric data in a machine independent/ sputl.3x
 plock: lock process, text, or data in memory. plock.2
 call. stat: data returned by stat system stat.5
 brk, sbrk: change data segment space allocation. brk.2
 types: primitive system data types. types.5

join: relational database operator. join.1
 udp: Internet User Datagram Protocol. udp.5
 date: print and set the date. date.1
 /asctime, tzset: convert date and time to string. ctime.3c
 date: print and set the date. date.1
 dc: desk calculator. dc.1
 optimal access time. dcopy: copy file systems for dcopy.1m
 dd: convert and copy a file. dd.1
 adb: debugger. adb.1
 fsdb: file system debugger. fsdb.1m
 eqnchar: special character definitions for eqn and neqn. eqnchar.5
 netmailer: deliver mail to. netmailer.8
 people. delivermail: deliver mail to arbitrary delivermail.8
 names. basename, dirname: deliver portions of path basename.1
 file. tail: deliver the last part of a tail.1
 aliases: aliases file for delivermail. aliases.7
 arbitrary people. delivermail: deliver mail to delivermail.8
 delta commentary of an SCCS delta. cdc: change the cdc.1
 file. delta: make a delta (change) to an SCCS delta.1
 delta. cdc: change the delta commentary of an SCCS cdc.1
 rmdel: remove a delta from an SCCS file. rmdel.1
 to an SCCS file. delta: make a delta (change) delta.1
 comb: combine SCCS deltas. comb.1
 msg: permit or deny messages. msg.1
 tbl, and eqn constructs. deroff: remove nroff/troff, deroff.1
 setkey, encrypt: generate DES encryption. crypt, crypt.3c
 close: close a file descriptor. close.2
 dup: duplicate an open file descriptor. dup.2
 dc: desk calculator. dc.1
 file. access: determine accessibility of a access.2
 file. determine file type. file.1
 errors in the specified device. /on/off the extended exterr.1
 ioctl: control device. ioctl.2
 master: master device information table. master.4
 devnm: device name. devnm.1m
 devnm: device name. devnm.1m
 df: report number of free disk df.1m
 check and interactive/ fsck: file system consistency fsck.1m
 terminal line connection. dial: establish an out-going dial.3c
 bdiff: big diff. bdiff.1
 comparator. diff: differential file diff.1
 comparison. diff3: 3-way differential file diff3.1
 sdiff: side-by-side difference program. sdiff.1
 diffmk: mark differences between files. diffmk.1
 diff: differential file comparator. diff.1
 diff3: 3-way differential file comparison. diff3.1
 between files. diffmk: mark differences diffmk.1
 dir: format of directories. dir.4
 dircmp: directory comparison. dircmp.1
 directories. dir.4
 ls: list contents of directories. ls.1
 rm, rmdir: remove files or directories. rm.1
 in the files in the given directories. /count characters sumdir.1
 cd: change working directory. cd.1
 chdir: change working directory. chdir.2
 chroot: change root directory. chroot.2
 pathname of current working directory. getcwd: get getcwd.3c
 mkdir: make a directory. mkdir.1
 mvdir: move a directory. mvdir.1m
 ls7: list contents of directory (Berkeley version). ls7.1
 uclean: uucp pool directory clean-up. uclean.1m
 dircmp: directory comparison. dircmp.1
 unlink: remove directory entry. unlink.2
 chroot: change root directory for a command. chroot.1m

/make a lost+found directory for fsck. mklost+found.1m
 pwd: working directory name. pwd.1
 ordinary file. mknod: make a directory, or a special or mknod.2
 path names. basename, dirname: deliver portions of basename.1
 printers. enable, disable: enable/disable LP enable.1
 acct: enable or disable process accounting. acct.2
 type, modes, speed, and line discipline. /set terminal getty.1m
 diskformat - format a disk. diskformat.1m
 sadp: disk access profiler. sadp.1
 df: report number of free disk blocks. df.1m
 disk tune - tune floppy disk settling time parameters. disk tune.1m
 du: summarize disk usage. du.1
 diskformat - format a disk. diskformat.1m
 disk tune - tune floppy disk settling time parameters. disk tune.1m
 mount, umount: mount and dismount file system. mount.1m
 rain: animated raindrops display. rain.6
 /view: screen oriented (visual) display editor based on ex. vi.1
 prof: display profile data. prof.1
 worms: animate worms on a display terminal. worms.6
 hypot: Euclidean distance function. hypot.3m
 /lcong48: generate uniformly distributed pseudo-random/ documents. mm: the MM mm.5
 macro package for formatting documents. /the OSDDD adapter mosd.5
 macro package for formatting documents formatted with the/ mm.1
 mm, osdd, checkmm: print/check documents, view graphs, and mmt.1
 slides. mmt, mv: typeset nulladm,/ chargefee, ckpacct, dodisk, lastlogin, monacct, acctsh.1m
 who: who is doing what. whodo.1m
 suitable for Motorola S-record downloading. /ASCII formats hex.1
 /Motorola S-records from downloading into a file. rcvhex.1
 nrand48, mrand48, jrand48, drand48, erand48, lrand48, drand48.3c
 arithmetic: provide drill in number facts. arithmetic.6
 du: summarize disk usage. du.1
 extract error records from dump. errdead: errdead.1m
 od: octal dump. od.1
 an object file. dump: dump selected parts of dump.1
 object file. dump: dump selected parts of an dump.1
 descriptor. dup: duplicate an open file dup.2
 descriptor. dup: duplicate an open file dup.2
 The alien invaders attack the earth. aliens: aliens.6
 echo: echo arguments. echo.1
 echo: echo arguments. echo.1
 floating-point number to/ ecvt, fcvt, gcvt: convert ecvt.3c
 ed, red: text editor. ed.1
 program. end, etext, edata: last locations in end.3c
 ex, edit: text editor ex.1
 sact: print current SCCS file editing activity. sact.1
 ed, red: text editor. ed.1
 ex, edit: text editor ex.1
 ld: link editor. ld.1
 sed: stream editor. sed.1
 oriented (visual) display editor based on ex. /screen vi.1
 se: screen editor for video terminals. se.1
 a.out: assembler and link editor output. a.out.4
 /user, real group, and effective group IDs. getuid.2
 and/ /getgid: get real user, effective user, real group, getuid.2
 Language. efl: Extended Fortran efl.1
 split fortran, ratfor, or efl files. fsplit: fsplit.1
 for a pattern. grep, egrep, fgrep: search a file grep.1
 enable/disable LP printers. enable, disable: enable.1
 accounting. acct: enable or disable process acct.2
 enable, disable: enable/disable LP printers. enable.1
 crypt: encode/decode. crypt.1
 encryption. crypt, setkey, encrypt: generate DES crypt.3c
 setkey, encrypt: generate DES encryption. crypt, crypt.3c

| | | | | |
|---|--|--------------|---|-------------|
| makekey: generate locations in program. | encryption key. | makekey.1 | ex, edit: text editor | ex.1 |
| /getgrgid, getgrnam, setgrent, | end, etext, edata: last | end.3c | exclusive file regions for | lockf.2 |
| socket: create an | endgrent: get group file/ | getgrent.3c | execd, execv, execle, execve, | exec.2 |
| /getpwuid, getpwnam, setpwent, | endpoint for communication. | socket.2 | execle, execve, execlp, | exec.2 |
| utmp/ /pututline, setutent, | endpwent: get password file/ | getpwent.3c | execlp, execvp: execute a/ | exec.2 |
| convert Arabic numerals to | endutent, utmpname: access | getut.3c | execute a file. /execle, | exec.2 |
| nlist: get | English. number: | number.6 | execute command. xargs: | xargs.1 |
| man, manprog: print | entries from name list. | nlist.3c | execute commands at a later | at.1 |
| man: macros for formatting | entries in this manual. | man.1 | execute regular expression. | regcmp.3x |
| endgrent: get group file | entries in this manual. | man.5 | execution. env: | env.1 |
| endpwent: get password file | entry. /getgrnam, setgrent, | getgrent.3c | execution. | uux.1c |
| utmpname: access utmp file | entry. /getpwnam, setpwent, | getpwent.3c | execution for an interval. | sleep.1 |
| putpwent: write password file | entry. /setutent, endutent, | getut.3c | execution for interval. | sleep.3c |
| unlink: remove directory | entry. | putpwent.3c | execution profile. | monitor.3c |
| utmp, wtmp: utmp and wtmp | entry. | unlink.2 | execution time profile. | profil.2 |
| command execution. | entry formats. | utmp.4 | execv, execle, execve, execlp, | exec.2 |
| | env: set environment for | env.1 | execve, execlp, execvp: | exec.2 |
| | environ: user environment. | environ.4 | /execv, execle, execve, execlp, | exec.2 |
| environ: user | environ: user environment. | environ.5 | system calls. link, unlink: | link.1m |
| environ: user | environment. | environ.4 | a new file or rewrite an | creat.2 |
| printenv: print out the | environment. | environ.5 | process. | exit.2 |
| profile: setting up an | environment at login time. | profile.1 | exit, _exit: terminate process. | exit.2 |
| execution. env: set | environment for command | env.1 | exp, log, log10, pow, sqrt: | exp.3m |
| getenv: return value for | environment name. | getenv.3c | expand files. pack, | pack.1 |
| character definitions for | eqn and neqn. /special | eqnchar.5 | exploration game. | adventure.6 |
| remove nroff/troff, tbl, and | eqn constructs. deroff: | deroff.1 | exponential, logarithm, power,/ | exp.3m |
| mathematical text for nroff/ | eqn, neqn, checkeq: format | eqn.1 | expr: evaluate arguments as an | expr.1 |
| definitions for eqn and neqn. | eqnchar: special character | eqnchar.5 | expression. | expr.1 |
| mrnd48, jrnd48, / drand48, | erand48, lrand48, nrand48, | drand48.3c | expression. regcmp, regex: | regcmp.3x |
| complementary error function. | erf, erfc: error function and | erf.3m | expression compile. | regcmp.1 |
| complementary error/ erf, | erfc: error function and | erf.3m | expression compile and match | regexp.5 |
| | err: error-logging interface. | err.7 | extended errors in the/ | exterr.1 |
| | errdead: extract error records | errdead.1m | Extended Fortran Language. | efl.1 |
| from dump. | errdemon: error-logging | errdemon.1m | extended TTY-37 type-box. | greek.5 |
| daemon. | errfile: error-log file | errfile.4 | exterr - turn on/off the | exterr.1 |
| format. | errno, sys_errlist, sys_nerr: | perror.3c | extract error records from | errdead.1m |
| system error/ perror, | error function. /erfc: error | erf.3m | fabs: floor, ceiling, | floor.3m |
| function and complementary | error function and | erf.3m | factor a number. | factor.1 |
| complementary/ erf, erfc: | error message file by | mkstr.1 | factor: factor a number. | factor.1 |
| massaging C/ mkstr: create an | error messages. /errno, | perror.3c | false: provide truth values. | true.1 |
| sys_errlist, sys_nerr: system | error numbers. /introduction | intro.2 | fashion.. /access long numeric | sputl.3x |
| to system calls and | error records from dump. | errdead.1m | fast incremental backup. | finc.1m |
| errdead: extract | error-handling function. | matherr.3m | fault. | abort.3c |
| matherr: | error-log file format. | errfile.4 | fclose, fflush: close or flush | fclose.3s |
| errfile: | error-logging daemon. | errdemon.1m | fcntl: file control. | fcntl.2 |
| errdemon: | error-logging daemon. | errstop.1m | fcntl: file control options. | fcntl.5 |
| errstop: terminate the | error-logging interface. | err.7 | fcvt, gcvt: convert | ecvt.3c |
| err: | errors. errpt: | errpt.1m | fdopen: open a stream. | fopen.3s |
| process a report of logged | errors. /hashmake, spellin, | spell.1 | feof, clearerr, fileno: stream | ferror.3s |
| hashcheck: find spelling | errors in the specified/ | exterr.1 | ferror, feof, clearerr, | ferror.3s |
| /- turn on/off the extended | errpt: process a report of | errpt.1m | ff: list file names and | ff.1m |
| logged errors. | errstop: terminate the | errstop.1m | flush: close or flush a | fclose.3s |
| error-logging daemon. | Escape from the automatic | autorobots.6 | fgetc, getw: get character or | getc.3s |
| robots. autorobots: | Escape from the robots. | robots.6 | fgets: get a string from a | gets.3s |
| robots: | escape the killer robots. | chase.6 | fgrep: search a file for a | grep.1 |
| chase: Try to | establish an out-going | dial.3c | file. access: | access.2 |
| terminal line/ dial: | establish mount table. | setmnt.1m | file. | chmod.2 |
| setmnt: | /etc/hosts: host table for | hosts.7 | file. chown: | chown.2 |
| bnet. | etext, edata: last locations | end.3c | file. | core.4 |
| in program. end, | Euclidean distance function. | hypot.3m | file. cut: cut out selected | cut.1 |
| hypot: | evaluate arguments as an | expr.1 | file. | dd.1 |
| expression. expr: | evaluation command. | test.1 | file. delta: make | delta.1 |
| test: condition | ex. /screen oriented (visual) | vi.1 | file. dump: dump | dump.1 |
| display editor based on | | | file. /execv, execle, execve, | exec.2 |
| | | | reading or/ lockf: provide | |
| | | | execlp, execvp: execute a/ | |
| | | | execvp: execute/ execl, execv, | |
| | | | execl, execv, execle, execve, | |
| | | | execve, execlp, execvp: | |
| | | | construct argument list(s) and | |
| | | | time. at: | |
| | | | regcmp, regex: compile and | |
| | | | set environment for command | |
| | | | uux: unix to unix command | |
| | | | sleep: suspend | |
| | | | sleep: suspend | |
| | | | monitor: prepare | |
| | | | profil: | |
| | | | execvp: execute a/ execl, | |
| | | | execute/ execl, execv, execle, | |
| | | | /execv, execle, execve, execlp, | |
| | | | system calls. link, unlink: | |
| | | | a new file or rewrite an | |
| | | | process. | |
| | | | exit, _exit: terminate process. | |
| | | | exponential, logarithm,/ | |
| | | | pcat, unpack: compress and | |
| | | | adventure: an | |
| | | | exp, log, log10, pow, sqrt: | |
| | | | expression. | |
| | | | expr: evaluate arguments as an | |
| | | | compile and execute regular | |
| | | | regcmp: regular | |
| | | | routines. regex: regular | |
| | | | exterr - turn on/off the | |
| | | | efl: | |
| | | | greek: graphics for the | |
| | | | extended errors in the/ | |
| | | | dump. errdead: | |
| | | | remainder,/ floor, ceil, fmod, | |
| | | | factor: | |
| | | | true, | |
| | | | false: provide truth values. | |
| | | | data in a machine independent | |
| | | | finc: | |
| | | | abort: generate an IOT | |
| | | | a stream. | |
| | | | floating-point number/ ecvt, | |
| | | | fopen, freopen, | |
| | | | status inquiries. ferror, | |
| | | | fileno: stream status/ | |
| | | | statistics for a file system. | |
| | | | stream. fclose, | |
| | | | word from/ getc, getchar, | |
| | | | stream. gets, | |
| | | | pattern. grep, egrep, | |
| | | | determine accessibility of a | |
| | | | chmod: change mode of | |
| | | | change owner and group of a | |
| | | | core: format of core image | |
| | | | fields of each line of a | |
| | | | dd: convert and copy a | |
| | | | a delta (change) to an SCCS | |
| | | | selected parts of an object | |
| | | | execlp, execvp: execute a | |

on character frequencies in a file. freq: report freq.1
 get: get a version of an SCCS file. get.1
 group: group file. group.4
 issue: issue identification file. issue.4
 link: link to a file. link.2
 mknod: build special file. mknod.1m
 or a special or ordinary file. /make a directory, mknod.2
 change the format of a text file. newform: newform.1
 null: the null file. null.7
 passwd: password file. passwd.4
 or subsequent lines of one file. /lines of several files paste.1
 prs: print an SCCS file. prs.1
 from downloading into a file. /Motorola S-records rcvhex.1
 read: read from file. read.2
 remove a delta from an SCCS file. rmdel: rmdel.1
 two versions of an SCCS file. sccsdif: compare sccsdif.1
 sccsfile: format of SCCS file. sccsfile.4
 size: size of an object file. size.1
 in an object, or other binary file. /the printable strings strings.1
 checksum and block count of a file. sum: print sum.1
 sum and count blocks in a file. sum7: sum7.1
 deliver the last part of a file. tail: tail.1
 tmpfile: create a temporary file. tmpfile.3s
 create a name for a temporary file. tmpnam, tmpnam: tmpnam.3s
 and modification times of a file. touch: update access touch.1
 undo a previous get of an SCCS file. unget: unget.1
 report repeated lines in a file. uniq: uniq.1
 val: validate SCCS file. val.1
 write: write on a file. write.2
 times. utime: set file access and modification utime.2
 hpio: HP 2645A terminal tape file archiver. hpio.1
 tar: tape file archiver. tar.1
 cpio: copy file archives in and out. cpio.1
 mkstr: create an error message file by massaging C source. mkstr.1
 pwck, grpck: password/group file checkers. pwck.1m
 diff: differential file comparator. diff.1
 diff3: 3-way differential file comparison. diff3.1
 fcntl: file control. fcntl.2
 fcntl: file control options. fcntl.5
 rcp: remote file copy rcp.1
 UNIX System-to-UNIX System file copy. /uupick: public uuto.1c
 umask: set and get file creation mask. umask.2
 close: close a file descriptor. close.2
 dup: duplicate an open file descriptor. dup.2
 file: determine file type. file.1
 sact: print current SCCS file editing activity. sact.1
 setgrent, endgrent: get group file entry. /getgrnam, getgrent.3c
 endpwent: get password file entry. /setpwent, getpwent.3c
 utmpname: access utmp file entry. /endutent, getut.3c
 putpwent: write password file entry. putpwent.3c
 ctags: maintain a tags file for a C program. ctags.1
 grep, egrep, fgrep: search a file for a pattern. grep.1
 aliases: aliases file for delivermail. aliases.7
 acct: per-process accounting file format. acct.4
 ar: archive (library) file format. ar.4
 errfile: error-log file format. errfile.4
 pnch: file format for card images. pnch.4
 intro: introduction to file formats. intro.4
 take: takes a file from a remote machine. take.1c
 take7: takes a file from a remote machine.. . . . take7.1c
 see: see what a file has in it. see.1
 split: split a file into pieces. split.1
 mktemp: make a unique file name. mktemp.3c
 ctermid: generate file name for terminal. ctermid.3s

a file system. ff: list file names and statistics for ff.1m
 /find the slot in the utmp file of the current user. ttyslot.3c
 put: puts a file onto a remote machine.. . . . put.1c
 put7: puts a file onto a remote machine.. . . . put7.1c
 /identify processes using a file or file structure. fuser.1m
 one. creat: create a new file or rewrite an existing creat.2
 viewing. more: file perusal filter for crt more.1
 lseek: move read/write file pointer. lseek.2
 /rewind, ftell: reposition a file pointer in a stream. fseek.3s
 lockf: provide exclusive file regions for reading or/ lockf.2
 bfs: big file scanner. bfs.1
 stat, fstat: get file status. stat.2
 processes using a file or file structure. /identify fuser.1m
 names and statistics for a file system. ff: list file ff.1m
 mkfs: construct a file system. mkfs.1m
 mkfs512: construct a file system. mkfs512.1m
 ount: mount and dismount file system. mount, mount.1m
 mount: mount a file system. mount.2
 umount: unmount a file system. umount.2
 tapesave: daily/weekly UNIX file system backup. filesave, filesave.1m
 and interactive/ fscck, dfscck: file system consistency check fscck.1m
 fsdb: file system debugger. fsdb.1m
 volume. file system: format of system fs.4
 ustat: get file system statistics. ustat.2
 mnttab: mounted file system table. mnttab.4
 access time. dcopy: copy file systems for optimal dcopy.1m
 fscck. checklist: list of file systems processed by checklist.4
 volcopy, labelit: copy file systems with label/ volcopy.1m
 ftw: walk a file tree. ftw.3c
 file: determine file type. file.1
 umask: set file-creation mode mask. umask.1
 ferror, feof, clearerr, fileno: stream status/ ferror.3s
 and print process accounting file(s). acctcom: search acctcom.1
 merge or add total accounting files. acctmerg: acctmerg.1m
 create and administer SCCS files. admin: admin.1
 cat: concatenate and print files. cat.1
 cmp: compare two files. cmp.1
 lines common to two sorted files. comm: select or reject comm.1
 cp, ln, mv: copy, link or move files. cp.1
 mark differences between files. diffmk: diffmk.1
 find: find files. find.1
 format specification in text files. fspec: fspec.4
 fortran, ratfor, or efl files. fsplit: split fsplit.1
 string, format of graphical files. /graphical primitive gps.4
 intro: introduction to special files. intro.7
 unpack: compress and expand files. pack, pcat, pack.1
 pr: print files. pr.1
 sort: sort and/or merge files. sort.1
 reports version number of files. version: version.1
 what: identify SCCS files. what.1
 updater: update files between two machines. updater.1
 updater: update files between two machines. updater.1m
 frec: recover files from a backup tape. frec.1m
 and count characters in the files in the given/ /sum sumdir.1
 hex: translates object files into ASCII formats/ hex.1
 rm, rmdir: remove files or directories. rm.1
 /merge same lines of several files or subsequent lines of/ paste.1
 daily/weekly UNIX file system/ filesave, tapesave: filesave.1m
 greek: select terminal filter. greek.1
 nl: line numbering filter. nl.1
 more: file perusal filter for crt viewing. more.1
 col: filter reverse line-feeds. col.1
 tplot: graphics filters. tplot.1g
 finc: fast incremental backup. finc.1m

find: find files. find.1
 find: find files. find.1
 hyphen: find hyphenated words. hyphen.1
 ttyname, isatty: find name of a terminal. ttyname.3c
 object library. lorder: find ordering relation for an lorder.1
 hashmake, spellin, hashcheck: find spelling errors. spell.1
 an object, or other/ strings: find the printable strings in strings.1
 of the current user. ttyslot: find the slot in the utmp file ttyslot.3c
 fish: play "Go Fish". fish.6
 fish: play "Go Fish". fish.6
 (sh only). nohup: run nohup.1
 fitting. tee.1
 floating-point number. atof.3c
 floating-point number to/ ecvt.3c
 /modf: manipulate parts of frexp.3c
 floor, ceiling, remainder,/ floor.3m
 floor, ceil, fmod, fabs: floor.3m
 parameters. disktime - tune disktime.1m
 cflow: generate C cflow.1
 fclose, fflush: close or fclose.3s
 remainder,/ floor, ceil, floor.3m
 stream. fopen.3s
 fopen, freopen, fdopen: open a fopen.3s
 fork: create a new process. fork.2
 format. acct: acct.4
 format. ar.4
 format. errfile.4
 format. tp.4
 format a disk. diskformat.1m
 format for card images. pnch.4
 format mathematical text for eqn.1
 format of a text file. newform.1
 format of an inode. inode.4
 core: format of core image file. core.4
 cpio: format of cpio archive. cpio.4
 dir: format of directories. dir.4
 /graphical primitive string, gps.4
 sccsfile: format of SCCS file. sccsfile.4
 file system: format of system volume. fs.4
 files. fspec: format specification in text fspec.4
 troff. tbl: format tables for nroff or tbl.1
 nroff: format text. nroff.1
 formats. intro.4
 formats. utmp, utmp.4
 formats suitable for Motorola/ hex.1
 formatted input. scanf.3s
 formatted output. printf, printf.3s
 formatted with the MM macros. mm.1
 formatting a permuted index. mptx.5
 nroff7: text nroff7.1
 troff7: text troff7.1
 formatting documents. mm.5
 formatting documents. /the mosd.5
 formatting entries in this man.5
 FORTRAN compiler. fortran.1
 fortran: FORTRAN compiler. fortran.1
 Fortran Language. efl.1
 fortran, ratfor, or efl fsplit.1
 fortune: print a random, fortune.6
 fprintf, sprintf: print printf.3s
 fputc, putw: put character or putc.3s
 fputs: put a string on a puts.3s
 fread, fwrite: binary fread.3s
 frec: recover files from a frec.1m
 df: report number of df.1m

memory allocator. malloc, free, realloc, calloc: main malloc.3c
 stream. fopen, freopen, fdopen: open a fopen.3s
 frequencies in a file. freq.1
 freq: report on character freq.1
 frequencies in a file. freq.1
 parts of floating-point/ frexp.3c
 frec: recover files frec.1m
 take: takes a file take.1c
 take7: takes a file take7.1c
 receive: receive message receive.2
 send: send message send.2
 gets, fgets: get a string gets.3s
 rmdel: remove a delta rmdel.1
 getopt: get option letter getopt.3c
 /translates Motorola S-records rcvhex.1
 errdead: extract error records errdead.1m
 read: read read.2
 ncheck: generate names ncheck.4m
 nlist: get entries nlist.3c
 acctcms: command summary acctcms.1m
 getw: get character or word getc.3s
 autorobots: Escape autorobots.6
 robots: Escape robots.6
 getpw: get name getpw.3c
 formatted input. scanf, scanf.3s
 of file systems processed by checklist.4
 a lost+found directory for mklost+found.1m
 consistency check and/ fsck.1m
 fsck, dfsck: file system fsck.1m
 fsdb: file system debugger. fsdb.1m
 reposition a file pointer in/ fseek.3s
 text files. fspec.4
 or efl files. fsplit.1
 stat. stat.2
 ftell: reposition a file ftell.3s
 ftw: walk a file tree. ftw.3c
 function. /error function erf.3m
 gamma: log gamma gamma.3m
 hypot: Euclidean distance hypot.3m
 matherr: error-handling matherr.3m
 error/ erf, erfc: error erf.3m
 j0, j1, jn, y0, y1, yn: Bessel bessell.3m
 logarithm, power, square root exp.3m
 remainder, absolute value floor.3m
 sinh, cosh, tanh: hyperbolic sinh.3m
 atan, atan2: trigonometric trig.3m
 300, 300s: handle special 300.1
 hp: handle special hp.1
 terminal. 450: handle special 450.1
 using a file or file/ fuser.1m
 fread, fread.3s
 connect accounting records. fwtm.1m
 adventure: an exploration adventure.6
 moo: guessing moo.6
 trek: trekkie trek.6
 worm: Play the growing worm worm.6
 cribbage: the card cribbage.6
 back: the back.6
 bj: the bj.6
 craps: the craps.6
 wump: the wump.6
 life: play the life.6
 intro: introduction to intro.6
 gamma: log gamma.3m
 gamma: log gamma function. gamma.3m
 gcvt: convert floating-point gcvt.3c

maze: generate a maze. maze.6
 abort: generate an IOT fault. abort.3c
 cflow: generate C flow graph. cflow.1
 reference. cxref: generate C program cross cxref.1
 crypt, setkey, encrpt: generate DES encryption. crypt.3c
 makekey: generate encryption key. makekey.1
 terminal. ctermid: generate file name for ctermid.3s
 ncheck: generate names from i-numbers. ncheck.1m
 lexical tasks. lex: generate programs for simple lex.1
 /srand48, seed48, lcong48: generate uniformly distributed/ drand48.3c
 srand: simple random-number generator. rand, rand.3c
 gets, fgets: get a string from a stream. gets.3s
 get: get a version of an SCCS file. get.1
 ulimit: get and set user limits. ulimit.2
 the user. cuserid: get character login name of cuserid.3s
 getc, getchar, fgetc, getw: get character or word from/ getc.3s
 nlist: get entries from name list. nlist.3c
 umask: set and get file creation mask. umask.2
 stat, fstat: get file status. stat.2
 ustat: get file system statistics. ustat.2
 file. get: get a version of an SCCS get.1
 /getgrnam, setgrent, endgrent: get group file entry. getgrent.3c
 getlogin: get login name. getlogin.3c
 logname: get login name. logname.1
 msgget: get message queue. msgget.2
 getpw: get name from UID. getpw.3c
 gethostname: get name of current host. gethostname.2
 system. uname: get name of current UNIX uname.2
 unget: undo a previous get of an SCCS file. unget.1
 argument vector. getopt: get option letter from getopt.3c
 /getpwnam, setpwnent, endpwnent: get password file entry. getpwnent.3c
 working directory. getcwd: get pathname of current getcwd.3c
 times. times: get process and child process times.2
 and/ getpid, getpgid, getppid: get process, process group, getpid.2
 /geteuid, getgid, getegid: get real user, effective user,/ getuid.2
 semget: get set of semaphores. semget.2
 shmget: get shared memory segment. shmget.2
 tty: get the terminal's name. tty.1
 time: get time. time.2
 get character or word from/ getc, getchar, fgetc, getw: getc.3s
 character or word from/ getc, getchar, fgetc, getw: get getc.3s
 current working directory. getcwd: get pathname of getcwd.3c
 getuid, geteuid, getgid, getegid: get real user,/ getuid.2
 getenv: return value for getenv.3c
 geteuid, getgid, getegid: get getuid.2
 getgid, getegid: get real getuid.2
 setgrent, endgrent: get group/ getgrent, getgrgid, getgrnam, getgrent.3c
 endgrent: get group/ getgrent, getgrgid, getgrnam, setgrent, getgrent.3c
 get group/ getgrent, getgrgid, getgrnam, setgrent, endgrent: getgrent.3c
 gethostname: get name of gethostname.2
 getlogin: get login name. getlogin.3c
 argument vector. getopt: get option letter from getopt.3c
 getopt: parse command options. getopt.1
 getpass: read a password. getpass.3c
 process group, and/ getpid, getpgid, getppid: get process, getpid.2
 process, process group, and/ getpid, getpgid, getppid: get getpid.2
 group, and/ getpid, getpgid, getpw: get name from UID. getpw.3c
 setpwnent, endpwnent: get/ getpwnam, setpwnent, endpwnent: getpwnent.3c
 get/ getpwnent, getpwnam, setpwnent, endpwnent: getpwnent.3c
 a stream. gets, fgets: get a string from gets.3s
 and terminal settings used by getty. gettydefs: speed gettydefs.4
 modes, speed, and line/ getty: set terminal type, getty.1m

ct: spawn getty to a remote terminal. ct.1c
 settings used by getty. gettydefs: speed and terminal gettydefs.4
 getegid: get real user,/ pututline, setutent,/ getuid.2
 setutent, endutent,/ getutent, setutent,/ getutent, getutid, getut.3c
 from/ getc, getchar, fgetc, convert/ ctime, localtime, getut.3c
 fish: play fish: play ctime.3c
 setjmp, longjmp: non-local goto. setjmp.3c
 string, format of graphical/ gps: graphical primitive gps.4
 cflow: generate C flow graph. cflow.1
 sag: system activity sag. sag.1g
 primitive string, format of graphical files. /graphical gps.4
 format of graphical/ gps: graphical primitive string, gps.4
 tplot: graphics filters. tplot.1g
 TTY-37 type-box. greek: graphics for the extended greek.5
 plot: graphics interface. plot.4
 subroutines. plot: graphics interface plot.3x
 mvt: typeset documents, view graphs, and slides. mmt, mmt.1
 package for typesetting view graphs and slides. /macro mv.5
 extended TTY-37 type-box. greek: graphics for the greek.5
 greek: select terminal filter. greek.1
 file for a pattern. grep, egrep, fgrep: search a grep.1
 chown, chgrp: change owner or group. chown.1
 newgrp: log in to a new group. newgrp.1
 /user, effective user, real group, and effective group/ getuid.2
 /getppid: get process, process group file. getpid.2
 group: group file. group.4
 setgrent, endgrent: get group file entry. /getgrnam, getgrent.3c
 group: group file. group.4
 setpgrp: set process group ID. setpgrp.2
 real group, and effective group IDs. /effective user, getuid.2
 setuid, setgid: set user and group IDs. setuid.2
 id: print user and group IDs and names. id.1
 chown: change owner and group of a file. chown.2
 a signal to a process or a group of processes. /send kill.2
 update, and regenerate groups of programs. /maintain, make.1
 worm: Play the growing worm game. worm.6
 checkers. pwck, grpck: password/group file pwck.1m
 ssignal, gsignal: software signals. ssignal.3c
 hangman: guess the word. hangman.6
 moo: guessing game. moo.6
 DASI 300 and 300s/ 300, 300s: handle special functions of 300.1
 2640 and 2621-series/ hp: handle special functions of HP hp.1
 the DASI 450 terminal. 450: handle special functions of 450.1
 information for bad block handling. /alternate block altblk.4
 hangman: guess the word. hangman.6
 nohup: run a command immune to hangups (sh only). nohup.1
 hcreate, hdestroy: manage hash search tables. hsearch, hsearch.3c
 spell, hashmake, spellin, hashcheck: find spelling/ spell.1
 find spelling errors. spell, hashmake, spellin, hashcheck: spell.1
 search tables. hsearch, hcreate, hdestroy: manage hash hsearch.3c
 tables. hsearch, hcreate, hdestroy: manage hash search hsearch.3c
 help: ask for help. help.1
 help: ask for help. help.1
 into ASCII formats suitable/ hex: translates object files hex.1
 fortune: print a random, hopefully interesting, adage. fortune.6
 get name of current host. gethostname: gethostname.2
 sethostname: set name of host cpu. sethostname.2
 runtime: show host status of local machines runtime.1
 set or print name of current host system hostname: hostname.1
 /etc/hosts: host table for bnet. hosts.7
 current host system hostname: set or print name of hostname.1

rhost, raddr: look up internet
 handle special functions of
 archiver. hpio:
 of HP 2640 and 2621-series/
 file archiver.
 manage hash search tables.
 wump: the game of
 sinh, cosh, tanh:

 hyphen: find
 function.
 semaphore set or shared memory
 setpgrp: set process group
 and names.
 issue: issue
 file or file/ fuser:
 what:
 group, and parent process
 group, and effective group
 setgid: set user and group
 id: print user and group
 core: format of core
 pnch: file format for card
 only). nohup: run a command
 finc: fast
 long numeric data in a machine
 /tgoto, tputs: terminal
 for formatting a permuted
 ptx: permuted
 and teletypes. last:
 family.
 inittab: script for the
 initialization.
 init, telinit: process control
 initialization.
 /rc, powerfail: system
 socket. connect:
 process. popen, pclose:
 process.
 clri: clear
 inode: format of an

 sscanf: convert formatted
 push character back into
 fread, fwrite: binary
 stdio: standard buffered
 fileno: stream status
 uustat: uucp status
 install:

 atol, atoi: convert string to
 abs: return
 /l64a: convert between long
 3-byte integers and long
 /l64l3: convert between 3-byte
 bcopy:
 system consistency check and
 print a random, hopefully
 err: error-logging
 loop: software loopback
 plot: graphics
 termio: general terminal
 tty: controlling terminal
 plot: graphics
 rhost, raddr: look up

hosts by name or address. rhost.3
 HP 2640 and 2621-series/ hp: hp.1
 HP 2645A terminal tape file hpio.1
 hp: handle special functions hp.1
 hpio: HP 2645A terminal tape hpio.1
 hsearch, hcreate, hdestroy: hsearch.3c
 hunt-the-wumpus. wump.6
 hyperbolic functions. sinh.3m
 hyphen: find hyphenated words. hyphen.1
 hyphenated words. hyphen.1
 hypot: Euclidean distance hypot.3m
 id. /remove a message queue, ipcrm.1
 ID. setpgrp.2
 id: print user and group IDs id.1
 identification file. issue.4
 identify processes using a fuser.1m
 identify SCCS files. what.1
 IDs. /get process, process getpid.2
 IDs. /effective user, real getuid.2
 IDs. setuid, setuid.2
 IDs and names. id.1
 image file. core.4
 images. pnch.4
 immune to hangups (sh nohup.1
 incremental backup. finc.1m
 independent fashion.. /access sputl.3x
 independent operation/ termcap.3
 index. /the macro package mptx.5
 index. ptx.1
 indicate last logins of users last.1
 inet: Internet protocol inet.5
 init process. inittab.4
 init, telinit: process control init.1m
 initialization. init.1m
 initialization shell scripts. brc.1m
 initiate a connection on a connect.2
 initiate pipe to/from a popen.3s
 inittab: script for the init inittab.4
 i-node. clri.1m
 inode. inode.4
 inode: format of an inode. inode.4
 input. scanf, fscanf, scanf.3s
 input stream. ungetc: ungetc.3s
 input/output. fread.3s
 input/output package. stdio.3s
 inquiries. /feof, clearerr, ferror.3s
 inquiry and job control. uustat.1c
 install commands. install.1m
 install: install commands. install.1m
 integer. strtol, strtol.3c
 integer absolute value. abs.3c
 integer and base-64 ASCII/ a64l.3c
 integers. /convert between l3tol.3c
 integers and long integers. l3tol.3c
 interactive block copy. bcopy.1m
 interactive repair. /file fsck.1m
 interesting, adage. fortune: fortune.6
 interface. err.7
 interface. lo.5
 interface. plot.4
 interface. termio.7
 interface. tty.7
 interface subroutines. plot.3x
 internet hosts by name or/ rhost.3

ip: Internet Protocol. ip.5
 inet: Internet protocol family. inet.5
 Protocol. tcp: Internet Transmission Control tcp.5
 Protocol. udp: Internet User Datagram udp.5
 spline: interpolate smooth curve. spline.1g
 characters. asa: interpret ASA carriage control asa.1
 sno: SNOBOL interpreter. sno.1
 syntax. csh: a shell (command interpreter) with C-like csh.1
 pipe: create an inter-process communication pipe.2
 facilities/ ipc: report inter-process communication ipc.1
 package. stdipc: standard interprocess communication stdipc.3c
 suspend execution for an interval. sleep: sleep.1
 sleep: suspend execution for an interval. sleep.3c
 commands and application/ intro: introduction to intro.1
 formats. intro: introduction to file intro.4
 intro: introduction to games. intro.6
 intro: introduction to intro.5
 intro: introduction to special intro.7
 files. intro: introduction to intro.3
 subroutines and libraries. intro: introduction to system intro.2
 calls and error numbers. intro: introduction to system intro.1m
 maintenance commands and/ intro: introduction to system intro.8
 maintenance procedures. intro: introduction to commands and intro.1
 application programs. intro: introduction to file formats. intro.4
 intro: introduction to games. intro.6
 intro: introduction to miscellany. intro.5
 facilities. net: introduction to networking net.5
 intro: introduction to special files. intro.7
 and libraries. intro: introduction to subroutines intro.3
 and error numbers. intro: introduction to system calls intro.2
 maintenance commands/ intro: introduction to system intro.1m
 maintenance/ intro: introduction to system intro.8
 ncheck: generate names from i-numbers. ncheck.1m
 aliens: The alien invaders attack the earth. aliens.6
 select: synchronous i/o multiplexing. select.2
 abort: generate an ioctl: control device. ioctl.2
 LOT fault. abort.3c
 ip: Internet Protocol. ip.5
 semaphore set or shared/ ipcrm: remove a message queue, ipcrm.1
 communication facilities/ ipc: report inter-process ipc.1
 /islower, isdigit, isxdigit, isalnum, isspace, ispunct,/ ctype.3c
 isdigit, isxdigit, isalnum,/ isalpha, isupper, islower, ctype.3c
 /isprint, isgraph, iscntrl, isascii: classify characters. ctype.3c
 terminal. ttyname, isatty: find name of a ttyname.3c
 /ispunct, isprint, isgraph, iscntrl, isascii: classify/ ctype.3c
 isalpha, isupper, islower, isdigit, isxdigit, isalnum,/ ctype.3c
 /isspace, ispunct, isprint, isgraph, iscntrl, isascii:/ ctype.3c
 islower, isdigit, isxdigit, isalnum, / isalpha, isupper, ctype.3c
 /isalnum, isspace, ispunct, isprint, isgraph, iscntrl,/ ctype.3c
 /isxdigit, isalnum, isspace, ispunct, isprint, isgraph,/ ctype.3c
 /isdigit, isxdigit, isalnum, isspace, ispunct, isprint,/ ctype.3c
 system: issue a shell command. system.3s
 issue: issue identification file. issue.4
 file. issue: issue identification issue.4
 isxdigit, isalnum,/ isalpha, isupper, islower, isdigit, ctype.3c
 /isupper, islower, isdigit, isxdigit, isalnum, isspace,/ ctype.3c
 news: print news items. news.1
 functions. j0, j1, jn, y0, y1, yn: Bessel bessel.3m
 functions. j0, j1, jn, y0, y1, yn: Bessel bessel.3m
 bj: the game of black jack. bj.6
 functions. j0, j1, jn, y0, y1, yn: Bessel bessel.3m
 operator. join: relational database join.1
 /lrand48, nrand48, mrand48, jrand48, srand48, seed48,/ drand48.3c
 makekey: generate encryption key. makekey.1

killall: kill all active processes. killall.1m
 process or a group of/
 kill: send a signal to a kill.2
 kill: terminate a process. kill.1
 processes. killall: kill all active killall.1m
 chase: Try to escape the chase.6
 mem. kmem: core memory. mem.7
 quiz: test your quiz.6
 3-byte integers and long/ l3tol, ltol3: convert between l3tol.3c
 integer and base-64/ a64l, l64a: convert between long a64l.3c
 copy file systems with label checking. /labelit: volcopy.1m
 with label checking. volcopy, volcopy.1m
 scanning and processing labelit: copy file systems
 arbitrary-precision arithmetic language. awk: pattern awk.1
 efl: Extended Fortran language. bc: bc.1
 command programming Language. efl.1
 cpp: the C language. /standard/restricted sh.1
 chargefee, ckpacct, dodisk, language preprocessor. cpp.1
 /jrand48, srand48, seed48, lastlogin, monacct, nulladm,/ acctsh.1m
 ld: link editor. ld.1
 ldexp, modf: manipulate parts frexp.3c
 letter from argument vector. getopt.3c
 simple lexical tasks. lex: generate programs for lex.1
 generate programs for simple lexical tasks. lex: lex.1
 to subroutines and libraries. /introduction intro.3
 relation for an object library. /find ordering lorder.1
 ar: archive (library) file format. ar.4
 library maintainer. ar.1
 ulimit: get and set user limits. ulimit.2
 line: read one line.1
 an out-going terminal line connection. /establish dial.3c
 type, modes, speed, and line discipline. /set terminal getty.1m
 nl: line numbering filter. nl.1
 out selected fields of each line of a file. cut: cut cut.1
 send/cancel requests to an LP line printer. lp, cancel: lp.1
 lpr: line printer spooler. lpr.1
 line: read one line. line.1
 lsearch: linear search and update. lsearch.3c
 col: filter reverse col.1
 head: give first few head.1
 files. comm: select or reject comm.1
 uniq: report repeated uniq.1
 of several files or subsequent lines of one file. /same lines paste.1
 subsequent/ paste: merge same paste.1
 link, unlink: exercise link.1m
 ld: link editor. ld.1
 a.out: assembler and a.out.4
 link editor output. link.2
 link: link to a file. cp.1
 cp, ln, mv: copy, link.2
 link: link to a file. link.1m
 link, unlink: exercise link link.1
 link: a C program checker. lint.1
 nlist: get entries from name nlist.3c
 nm: print name nm.1
 ls: list contents of directories. ls.1
 (Berkeley version). ls7: list contents of directory ls7.1
 for a file system. ff: list file names and statistics ff.1m
 by fsck. checklist: list of file systems processed checklist.4
 xargs: construct argument xargs.1
 files. cp, ln, mv: copy, link or move cp.1
 tzset: convert date/ ctime, localtime, gmtime, asctime, ctime.3c
 end, etext, edata: last end.3c
 memory. plock: lock process, text, or data in plock.2
 regions for reading or/ lockf: provide exclusive file lockf.2
 gamma: log gamma function. gamma.3m

newgrp: log in to a new group. newgrp.1
 exponential, logarithm,/ exp, log, log10, pow, sqrt: exp.3m
 logarithm, power,/ exp, log, log10, pow, sqrt: exponential, exp.3m
 /log10, pow, sqrt: exponential, logarithm, power, square root/ exp.3m
 errpt: process a report of errpt.1m
 logged errors. errpt.1m
 logged in on local machines rwho.1
 rwho: who is rwho.1
 rlogin: remote rlogin.1
 getlogin: get getlogin.3c
 login name. login.1
 login name. login.1
 login name of the user. cuserid.3s
 cuserid: get character cuserid.3s
 logname: return logname.3x
 logname: return logname.3x
 passwd: change passwd.1
 login: sign on. login.1
 login time. profile: profile.4
 logins of users and teletypes. last.1
 last: indicate last last.1
 logname: get login name. logname.1
 user. logname: return login name of logname.3x
 a64l, l64a: convert between a64l.3c
 long integer and base-64 ASCII/ a64l.3c
 between 3-byte integers and long integers. /ltol3: convert l3tol.3c
 sputl, sgetl: access sputl.3x
 setjmp, setjmp.3c
 interface. setjmp.3c
 loop: software lo.5
 for an object library. lo.5
 mklost+found: make a mklost+found.1m
 nice: run a command at nice.1
 requests to an LP line/ lp.1
 send/cancel requests to an lp.1
 disable: enable/disable enable.1
 /lpshut, lpmove: start/stop the lpshched.1m
 accept, reject: allow/prevent lpshched.1m
 lpadmin: configure the lpadmin.1m
 lpstat: print lpstat.1
 spooling system. lpadmin.1m
 request/ lpshched, lpshut, lpshched.1m
 lpshut, lpmove: lpshched.1m
 LP request scheduler/ lpshched, lpshched.1m
 information. lpstat.1
 lpstat: print LP status lpstat.1
 jrand48,/ drand48, erand48, drand48.3c
 directories. ls.1
 ls: list contents of ls.1
 ls7: list contents of ls7.1
 lsearch: linear search and lsearch.3c
 lseek: move read/write file lseek.2
 ltol3: convert between 3-byte l3tol.3c
 integers and long/ l3tol, m4.1
 m4: macro processor. m4.1
 truth value about your/ machid.1
 put: puts a file onto a remote put.1c
 puts a file onto a remote put.1c
 machine. put7: put7.1c
 takes a file from a remote take.1c
 takes a file from a remote take7.1c
 machine. take7: take7.1c
 /access long numeric data in a sputl.3x
 show host status of local ruptime.1
 who is logged in on local rwho.1
 update files between two updater.1
 update files between two updater.1
 machines. updater: updater.1
 machines. updater: updater.1m
 permuted index. mptx: the mptx.5
 documents. mm: the MM mm.5
 mosd: the OSDD adapter mosd.5
 view graphs and/ mv: a troff mv.5
 m4: macro processor. m4.1
 formatted with the MM mm.1
 in this manual. man: man.5
 tp: macros for formatting entries tp.4
 magnetic tape format. tp.4

send mail to users or read users or read mail.
 netmail: the bnet network netmailer: deliver delivermail: deliver mail, rmail: send malloc, free, realloc, calloc: program. ctags: regenerate groups of/ ar: archive and library intro: introduction to system intro: introduction to system SCCS file. delta: mkdir: or ordinary file. mknod: for fsck. mklost+found: mktemp: regenerate groups of/ ssp: banner: key. main memory allocator. entries in this manual. this manual. tsearch, tdelete, twalk: hsearch, hcreate, hdestroy: records. fwtmp, wtmpfix: frexp, ldexp, modf: tp: manual. man, manprog: print entries in this for formatting entries in this ascii: files. diffmk: umask: set file-creation mode set and get file creation an error message file by table. master: information table. regular expression compile and eqn, neqn, checked: format function. maze: generate a bcd: convert to antique memcopy, memset: memory/ memset: memory/ memcopy, operations. memcopy, memchr, memcopy, memchr, memcopy, memchr, memcopy, mem, kmem: core lock process, text, or data in free, realloc, calloc: main shmctl: shared queue, semaphore set or shared memcopy, memcopy, memset: shmop: shared shmget: get shared /memchr, memcopy, memcopy, sort: sort and/or files. acctmrg: files or subsequent/ paste: msgctl: mail. mail, rmail: mail.1 mail, rmail: send mail to mail.1 mail system. netmail.8 mail to. netmailer.8 mail to arbitrary people. delivermail.8 mail to users or read mail. mail.1 main memory allocator. malloc.3c maintain a tags file for a C ctags.1 maintain, update, and make.1 maintainer. ar.1 maintenance commands and/ intro.1m maintenance procedures. intro.8 make a delta (change) to an delta.1 make a directory. mkdir.1 make a directory, or a special mknod.2 make a lost+found directory mklost+fnd.1m make a unique file name. mktemp.3c make: maintain, update, and make.1 make output single spaced. ssp.1 make posters. banner.1 makekey: generate encryption makekey.1 malloc, free, realloc, calloc: malloc.3c man: macros for formatting man.5 man, manprog: print entries in man.1 manage binary search trees. tsearch.3c manage hash search tables. hsearch.3c manipulate connect accounting fwtmp.1m manipulate parts of/ frexp.3c manipulate tape archive. tp.1 manprog: print entries in this man.1 manual. man, man.1 manual. man: macros man.5 map of ASCII character set. ascii.5 mark differences between diffmk.1 mask. umask.1 mask. umask: umask.2 massaging C source. /create mkstr.1 master device information master.4 master: master device master.4 match routines. regexp: regexp.5 mathematical text for nroff or/ eqn.1 matherr: error-handling matherr.3m maze. maze.6 maze: generate a maze. maze.6 media. bcd.6 mem, kmem: core memory. mem.7 memcopy, memchr, memcopy, memory.3c memchr, memcopy, memcopy, memory.3c memcopy, memcopy, memset: memory memory.3c memcopy, memset: memory/ memory.3c memory. mem.7 memory. plock: plock.2 memory allocator. malloc, malloc.3c memory control operations. shmctl.2 memory id. /remove a message ipcrm.1 memory operations. /memchr, memory.3c memory operations. shmop.2 memory segment. shmget.2 memset: memory operations. memory.3c merge files. sort.1 merge or add total accounting acctmrg.1m merge same lines of several paste.1 msg: permit or deny messages. msg.1 msgctl: message control operations. msgctl.2

mkstr: create an error receive: receive send: send msgop: msgget: get or shared/ ipcrm: remove a msg: permit or deny sys_nerr: system error message file by massaging C/ mkstr.1 message from a socket. receive.2 message from a socket. send.2 message operations. msgop.2 message queue. msgget.2 message queue, semaphore set ipcrm.1 messages. msg.1 messages. /errno, sys_errlist, perror.3c mkdir: make a directory. mkdir.1 mkfs: construct a file system. mkfs.1m mkfs512: construct a file mkfs512.1m mklost+found: make a mklost+fnd.1m mknod: build special file. mknod.1m mknod: make a directory, or a mknod.2 mkstr: create an error message mkstr.1 mktemp: make a unique file mktemp.3c MM macro package for mm.5 MM macros. /print/check mm.1 mm, osdd, checkmm: print/check mm.1 mm: the MM macro package for mm.5 mmt, mvt: typeset documents, mmt.1 mnttab: mounted file system mnttab.4 mode. chmod.1 mode mask. umask.1 mode of file. chmod.2 modes. tset.1 modes, speed, and line/ getty.1m modest-sized programs. bs.1 modf: manipulate parts of frexp.3c modification times. utime.2 modification times of a file. touch.1 monacct, nulladm, prtmp, / acctsh.1m monitor: prepare execution monitor.3c monitor uucp network. uucp.1m moo: guessing game. moo.6 mosd: the OSDD adapter macro mosd.5 Motorola S-record downloading. hex.1 Motorola S-records from/ rcvhex.1 mount a file system. mount.2 mount and dismount file mount.1m mount: mount a file system. mount.2 mount table. setmnt.1m mount, umount: mount and mount.1m mounted file system table. mnttab.4 move a directory. mvdir.1m move files. cp.1 move read/write file pointer. lseek.2 the LP request scheduler and lpsched.1m formatting a permutd index. mptx.5 mrand48, jrand48, srand48, / drand48.3c msgctl: message control msgctl.2 msgget: get message queue. msgget.2 msgop: message operations. msgop.2 multiplexing. select.2 mv: a troff macro package for mv.5 mv: copy, link or move files. cp.1 mvdir: move a directory. mvdir.1m mvt: typeset documents, view mmt.1 i-numbers. ncheck: generate names from ncheck.1m neqn. /special character eqnchar.5 neqn, checked: format eqn.1 net: introduction to net.5 netmail: the bnet network mail netmail.8 netmailer: deliver mail to. netmailer.8

uusub: monitor uuap network. uusub.1m
 netmail: the bnet network mail system. netmail.8
 rstat: network statistics program rstat.1
 net: introduction to networking facilities. net.5
 a text file. newform: change the format of newform.1
 newgrp: log in to a new group. newgrp.1
 news: print news items. news.1
 news: print news items. news.2
 process. nice: change priority of a nice.2
 priority. nice: run a command at low nice.1
 list. nl: line numbering filter. nl.1
 nlist: get entries from name nlist.3c
 nm: print name list. nm.1
 hangups (*sh* only). nohup: run a command immune to nohup.1
 setjmp, longjmp: non-local goto. setjmp.3c
 drand48, erand48, lrand48, nrand48, mrand48, jrand48, /
 format mathematical text for nroff: format text. nroff.1
 tbl: format tables for nroff or troff. /checked: eqn.1
 typesetting. nroff or troff. tbl.1
 constructs. deroff: remove nroff7: text formatting and nroff7.1
 null: the null file. deroff.1
 null: the null file. null.7
 null: the null file. null.7
 /dodisk, lastlogin, monacct, nulladm, prctmp, prdaily, /
 nl: line numbering filter. acctsh.1m
 number: convert Arabic numerals to English. nl.1
 sputl, sgetl: access long numeric data in a machine/ sputl.3x
 dump selected parts of an object file. dump: dump.1
 size: size of an object file. size.1
 formats/ hex: translates object files into ASCII hex.1
 find ordering relation for an object library. lorder: lorder.1
 /the printable strings in an object, or other binary file. strings.1
 od: octal dump. od.1
 od: octal dump. od.1
 only). nohup: run a command on/off the extended errors in nohup.1
 the specified/ exterr - turn on/off the extended errors in exterr.1
 put: puts a file onto a remote machine.. . . . put.1c
 put7: puts a file onto a remote machine.. . . . put7.1c
 fopen, freopen, fdopen, open a stream. fopen.3s
 dup: duplicate an open file descriptor. dup.2
 open: open for reading or writing. open.2
 writing. open: open for reading or open.2
 /prfdc, prfsnap, prfpr: operating system profiler. profiler.1m
 tputs: terminal independent operation routines. /tgoto, termcap.3
 memcmp, memcpy, memset: memory operations. memccpy, memchr, memory.3c
 msgctl: message control operations. msgctl.2
 msgop: message operations. msgop.2
 semctl: semaphore control operations. semctl.2
 semop: semaphore operations. semop.2
 shmctl: shared memory control operations. shmctl.2
 shmop: shared memory operations. shmop.2
 strcsn, strtok: string operations. /strpbrk, strspn, string.3c
 join: relational database operator. join.1
 dcopy: copy file systems for optimal access time. dcopy.1m
 vector. getopt: get option letter from argument getopt.3c
 fcntl: file control options. fcntl.5
 getopt: parse command options. getopt.1
 stty: set the options for a terminal. stty.1
 object library. lorder: find ordering relation for an lorder.1
 a directory, or a special ordinary file. mknod: make mknod.2
 editor based/ vi, view: screen oriented (visual) display vi.1
 formatting/ mosd: the OSDD adapter macro package for mosd.5
 documents formatted with/ mm, osdd, checkmm: print/check mm.1
 dial: establish an out-going terminal line/ dial.3c

assembler and link editor output. a.out: a.out.4
 printf: print formatted output. printf, sprintf, printf.3s
 ssp: make output single spaced. ssp.1
 /acctdusg, accton, acctwtmpt: overview of accounting and/ acct.1m
 chown: change owner and group of a file. chown.2
 chown, chgrp: change owner or group. chown.1
 and expand files. pack, pcat, unpack: compress pack.1
 sadc: system activity report package. sa1, sa2, sar.1m
 standard buffered input/output package. stdio: stdio.3s
 interprocess communication package. stdipc: standard stdipc.3c
 permuted/ mptx: the macro package for formatting a mptx.5
 documents. mm: the MM macro package for formatting mm.5
 mosd: the OSDD adapter macro package for formatting/ mosd.5
 graphs and/ mv: a troff macro package for typesetting view mv.5
 4014 terminal. 4014: paginator for the Tektronix 4014.1
 tune floppy disk settling time parameters. diskturne - diskturne.1m
 process, process group, and parent process IDs. /get getpid.2
 getopt: parse command options. getopt.1
 passwd: change login password. passwd.1
 passwd: password file. passwd.4
 getpass: read a password. getpass.3c
 passwd: change login password. passwd.1
 passwd: password file. passwd.4
 /setpwent, endpwent: get password file entry. getpwent.3c
 putpwent: write password file entry. putpwent.3c
 pwck, grpck: password/group file checkers. pwck.1m
 several files or subsequent/ paste: merge same lines of paste.1
 dirname: deliver portions of pathnames. basename, basename.1
 directory. getcwd: get pathname of current working getcwd.3c
 fgrep: search a file for a pattern. grep, egrep, grep.1
 processing language. awk: pattern scanning and awk.1
 signal. pause: suspend process until pause.2
 expand files. pack, pcat, unpack: compress and pack.1
 a process. popen, pclose: initiate pipe to/from popen.3s
 value about your/ m68k, pdp11, u3b, vax: provide truth machid.1
 msg: permit or deny messages. msg.1
 macro package for formatting a permuted index. mptx: the mptx.5
 ptx: permuted index. ptx.1
 format. acct: per-process accounting file acct.4
 acctcms: command summary from per-process accounting/ acctcms.1m
 sys_nerr: system error/ perror, errno, sys_errlist, perror.3c
 viewing. more: file perusal filter for crt more.1
 tc: phototypesetter simulator. tc.1
 access physical addresses. phys: allow a process to phys.2
 allow a process to access physical addresses. phys: phys.2
 split: split a file into pieces. split.1
 channel. pipe: create an interprocess pipe.2
 tee: pipe fitting. tee.1
 popen, pclose: initiate pipe to/from a process. popen.3s
 fish: play "Go Fish". fish.6
 life: play the game of life. life.6
 worm: Play the growing worm game. worm.6
 data in memory. plock: lock process, text, or plock.2
 subroutines. plot: graphics interface. plot.4
 images. plot: graphics interface plot.3x
 lseek: move read/write file pnch: file format for card pnch.4
 ftell: reposition a file pointer. lseek.2
 to/from a process. pointer in a stream. /rewind, fseek.3s
 data base of terminal types by popen, pclose: initiate pipe popen.3s
 basename, dirname: deliver port. ttytype: ttytype.4
 banner: make portions of path names. basename.1
 logarithm,/ exp, log, log10, posters. banner.1
 /sqrt: exponential, logarithm, pow, sqrt: exponential, exp.3m
 power, square root functions. exp.3m

brc, bcheckrc, rc, powerfail: system/ brc.1m
 pr: print files. pr.1
 /lastlogin, monacct, nulladm, prctmp, prdaily, prtacct, acctsh.1m
 /monacct, nulladm, prctmp, prdaily, prtacct, runacct, acctsh.1m
 for troff. cw, checkcw: prepare constant-width text cw.1
 monitor: prepare execution profile. monitor.3c
 cpp: the C language preprocessor. cpp.1
 unget: undo a previous get of an SCCS file. unget.1
 operating/ prfld, prfstat, prfsnap, prfpr: operating/ prfld, prfstat, prfdc, profiler.1m
 /prfstat, prfdc, prfsnap, prfpr: operating system/ prfld, prfstat, prfdc, profiler.1m
 system/ prfld, prfstat, prfdc, prfpr: operating/ prfld, prfstat, prfdc, prfsnap, profiler.1m
 graphical/ gps: graphical primitive string, format of gps.4
 types: primitive system data types. types.5
 interesting, adage. fortune: print a random, hopefully fortune.6
 prs: print an SCCS file. prs.1
 date: print and set the date. date.1
 cal: print calendar. cal.1
 of a file. sum: print checksum and block count sum.1
 editing activity. sact: print current SCCS file sact.1
 man, manprog: print entries in this manual. man.1
 cat: concatenate and print files. cat.1
 pr: print files. pr.1
 printf, fprintf, sprintf: print formatted output. printf.3s
 banner7: print large banner on printer. banner7.1
 lpstat: print LP status information. lpstat.1
 nm: print name list. nm.1
 system hostname: set or print name of current host hostname.1
 System. uname: print name of current UNIX uname.1
 news: print news items. news.1
 printenv: print out the environment. printenv.1
 file(s). acctcom: search and print process accounting acctcom.1
 pstat: print system facts. pstat.1m
 names. id: print user and group IDs and id.1
 object, or/ strings: find printable strings in an strings.1
 formatted/ mm, osdd, checkmm: print/check documents mm.1
 environment. printenv: print out the printenv.1
 banner7: print large banner on printer. banner7.1
 requests to an LP line printer. /cancel: send/cancel lp.1
 lpr: line printer spooler. lpr.1
 disable: enable/disable LP printers. enable, enable.1
 print formatted output. printf, fprintf, sprintf: printf.3s
 nice: run a command at low priority. nice.1
 nice: change priority of a process. nice.2
 exit, _exit: terminate process. exit.2
 fork: create a new process. fork.2
 inittab: script for the init process. inittab.4
 kill: terminate a process. kill.1
 nice: change priority of a process. nice.2
 initiate pipe to/from a process. popen, pclose: popen.3s
 wait: await completion of process. wait.1
 errors. errpt: process a report of logged errpt.1m
 acct: enable or disable process accounting. acct.2
 acctprcl, acctprc2: process accounting. acctprc.1m
 acctcom: search and print process accounting file(s). acctcom.1
 times. times: get process and child process times.2
 init, telinit: process control/ init.1m
 timex: time a command; report process data and system/ timex.1
 /getgrp, getppid: get process, process group, and parent/ getpid.2
 setpgrp: set process group ID. setpgrp.2
 process group, and parent process IDs. /get process, getpid.2
 kill: send a signal to a process or a group of/ kill.2
 getpid, getpgrp, getppid: get process, process group, and/ getpid.2

ps: report process status. ps.1
 memory. plock: lock process, text, or data in plock.2
 times: get process and child process times. times.2
 addresses. phys: allow a process to access physical phys.2
 wait: wait for child process to stop or terminate. wait.2
 ptrace: process trace. ptrace.2
 pause: suspend process until signal. pause.2
 list of file systems processed by fsck. checklist: checklist.4
 to a process or a group of processes. /send a signal kill.2
 killall: kill all active processes. killall.1m
 structure. fuser: identify processes using a file or file fuser.1m
 shutdown: terminate all processing. shutdown.1m
 awk: pattern scanning and processing language. awk.1
 m4: macro processor. m4.1
 provide truth value about your processor type. /u3b, vax: machid.1
 alarm: set a process's alarm clock. alarm.2
 profile: prof: display profile data. prof.1
 profile: execution time profil.2
 monitor: prepare execution profile. monitor.3c
 profil: execution time profile. profil.2
 prof: display profile data. prof.1
 environment at login time. profile: setting up an profile.4
 prfpr: operating system profiler. /prfdc, prfsnap, profiler.1m
 sadp: disk access profiler. sadp.1
 standard/restricted command programming language. /the sh.1
 ip: Internet Protocol. ip.5
 Internet Transmission Control Protocol. tcp: tcp.5
 udp: Internet User Datagram Protocol. udp.5
 inet: Internet protocol family. inet.5
 arithmetic: provide drill in number facts. arithmetic.6
 for reading or/ lockf: provide exclusive file regions lockf.2
 m68k, pdpl1, u3b, vax: provide truth value about your/ machid.1
 true, false: provide truth values. true.1
 prs: print an SCCS file. prs.1
 prtacct, runacct, shutacct, /acctsh.1m
 ps: report process status. ps.1
 /generate uniformly distributed pseudo-random numbers. drand48.3c
 pstat: print system facts. pstat.1m
 ptrace: process trace. ptrace.2
 ptx: permuted index. ptx.1
 stream. ungetc: push character back into input ungetc.3s
 remote machine.. put7: puts a file onto a put7.1c
 put character or word on a/ putc, putchar, fputc, putw: putc.3s
 character or word on a/ putc, putchar, fputc, putw: put putc.3s
 entry. putpwent: write password file putpwent.3c
 machine.. put: puts a file onto a remote put.1c
 machine.. put7: puts a file onto a remote put7.1c
 stream. puts, fputs: put a string on a puts.3s
 getutent, getutid, getutline, pututline, setutent, endutent, / getut.3c
 a/ putc, putchar, fputc, putw: put character or word on putc.3s
 file checkers. pwck, grpck: password/group pwck.1m
 pwd: working directory name. pwd.1
 qsort: quicker sort. qsort.3c
 msgget: get message queue. msgget.2
 ipcrm: remove a message queue, semaphore set or shared/ ipcrm.1
 qsort: quicker sort. qsort.3c
 quiz: test your knowledge. quiz.6
 by name or address. rhost, raddr: look up internet hosts rhost.3
 display. rain: animated raindrops rain.6
 rain: animated raindrops display. rain.6
 random, srand: simple random-number generator. rand.3c
 adage. fortune: print a random, hopefully interesting, fortune.6
 rand, srand: simple random-number generator. rand.3c
 fsplit: split fortran, ratfor, or efl files. fsplit.1

initialization/ brc, bcheckrc, rc, powerfail: system brc.1m
 rcp: remote file copy rcp.1
 S-records from downloading/ rcvhex: translates Motorola rcvhex.1
 getpass: read a password. getpass.3c
 read: read from file. read.2
 rmail: send mail to users or read mail. mail, mail.1
 line: read one line. line.1
 read: read from file. read.2
 exclusive file regions for reading or writing. /provide lockf.2
 open: open for reading or writing. open.2
 lseek: move read/write file pointer. lseek.2
 allocator. malloc, free, realloc, calloc: main memory malloc.3c
 reboot: reboot the system. reboot.2
 reboot: reboot the system. reboot.2
 specify what to do upon receipt of a signal. signal: signal.2
 receive: receive message from a socket. receive.2
 a socket. receive: receive message from receive.2
 from per-process accounting records. /command summary acctcms.1m
 manipulate connect accounting records. fwtmpt, wtmptfix: fwtmpt.1m
 errdead: extract error records from dump. errdead.1m
 tape. frec: recover files from a backup frec.1m
 ed, red: text editor. ed.1
 generate C program cross reference. cxref: cxref.1
 execute regular expression. regcmp, regex: compile and regcmp.3x
 compile. regcmp: regular expression regcmp.1
 make: maintain, update, and regenerate groups of programs. make.1
 regular expression. regcmp, regex: compile and execute regcmp.3x
 compile and match routines. regexp: regular expression regexp.5
 lockf: provide exclusive file regions for reading or/ lockf.2
 regex: compile and execute regular expression. regcmp, regcmp.3x
 regcmp: regular expression compile. regcmp.1
 match routines. regexp: regular expression compile and regexp.5
 requests. accept, reject: allow/prevent LP accept.1m
 sorted files. comm: select or reject lines common to two comm.1
 lorder: find ordering relation for an object/ lorder.1
 join: relational database operator. join.1
 strip: remove symbols and relocation bits. strip.1
 /fmod, fabs: floor, ceiling, remainder, absolute value/ floor.3m
 calendar: reminder service. calendar.1
 rcp: remote file copy rcp.1
 rlogin: remote login rlogin.1
 put: puts a file onto a remote machine.. put.1c
 put7: puts a file onto a remote machine.. put7.1c
 take: takes a file from a remote machine. take.1c
 take7: takes a file from a remote machine.. take7.1c
 remsh: remote shell remsh.1
 ct: spawn getty to a remote terminal. ct.1c
 file. rmdel: remove a delta from an SCCS rmdel.1
 semaphore set or/ ipcrm: remove a message queue. ipcrm.1
 unlink: remove directory entry. unlink.2
 rm, rmdir: remove files or directories. rm.1
 eqn constructs. deroff: remove nroff/troff, tbl, and deroff.1
 bits. strip: remove symbols and relocation strip.1
 remsh: remote shell remsh.1
 check and interactive repair. /system consistency fsck.1m
 uniq: report repeated lines in a file. uniq.1
 clock: report CPU time used. clock.3c
 communication/ ipc: report inter-process ipc.1
 blocks. df: report number of free disk df.1m
 errpt: process report of logged errors. errpt.1m
 frequencies in a file. freq: report on character freq.1
 sa2, sadc: system activity report package. sal, sar.1m
 timex: time a command; report process data and system/ timex.1
 ps: report process status. ps.1

file. uniq: report repeated lines in a uniq.1
 sar: system activity reporter. sar.1
 files. version: reports version number of version.1
 stream. fseek, rewind, ftell: reposition a file pointer in a fseek.3s
 /lpmove: start/stop the LP request scheduler and move/ lpshed.1m
 reject: allow/prevent LP requests. accept, accept.1m
 LP request scheduler and move requests. /start/stop the lpshed.1m
 lp, cancel: send/cancel requests to an LP line/ lp.1
 to a sensible state. reset: reset the teletype bits reset.1
 sensible state. reset: reset the teletype bits to a reset.1
 a socket. socketaddr: return address associated with socketaddr.2
 abs: return integer absolute value. abs.3c
 logname: return login name of user. logname.3x
 name. getenv: return value for environment getenv.3c
 stat: data returned by stat system call. stat.5
 configuration/ uvar: returns system-specific uvar.2
 col: filter reverse line-feeds. col.1
 file pointer in a/ fseek, rewind, ftell: reposition a fseek.3s
 creat: create a new file or rewrite an existing one. creat.2
 hosts by name or address. rhost, raddr: look up internet rhost.3
 rlogin: remote login rlogin.1
 rm, rmdir: remove files or rm.1
 read mail. mail, rmail: send mail to users or mail.1
 SCCS file. rmdel: remove a delta from an rmdel.1
 directories. rm, rmdir: remove files or rm.1
 Escape from the automatic robots. autorobots: autorobots.6
 Try to escape the killer robots. chase: chase.6
 robots: Escape from the robots. robots.6
 robots: Escape from the robots. robots.6
 chroot: change root directory. chroot.2
 chroot: change root directory for a command. chroot.1m
 logarithm, power, square root functions. /exponential, exp.3m
 expression compile and match routines. regexp: regular regexp.5
 terminal independent operation routines. /tgoto, tputs: termcap.3
 standard/restricted/ sh, rsh: shell, the sh.1
 program rstat: network statistics rstat.1
 nice: run a command at low priority. nice.1
 hangups (sh/ nohup: run a command immune to nohup.1
 runacct: run daily accounting. runacct.1m
 runacct: run daily accounting. runacct.1m
 /prctmp, prdaily, prtacct, runacct, shutacct, startup,/ acctsh.1m
 local machines ruptime: show host status of ruptime.1
 local machines rwho: who is logged in on rwho.1
 activity report package. sal, sa2, sadc: system sar.1m
 report package. sal, sa2, sadc: system activity sar.1m
 editing activity. sact: print current SCCS file sact.1
 package. sal, sa2, sadc: system activity report sar.1m
 sadp: disk access profiler. sadp.1
 sag: system activity graph. sag.1g
 sar: system activity reporter. sar.1
 space allocation. brk, sbrk: change data segment brk.2
 formatted input. scanf, fscanf, sscanf: convert scanf.3s
 bfs: big file scanner. bfs.1
 language. awk: pattern scanning and processing awk.1
 the delta commentary of an SCCS delta. cdc: change cdc.1
 comb: combine SCCS deltas. comb.1
 make a delta (change) to an SCCS file. delta: delta.1
 get: get a version of an SCCS file. get.1
 prs: print an SCCS file. prs.1
 rmdel: remove a delta from an SCCS file. rmdel.1
 compare two versions of an SCCS file. scsdiff: scsdiff.1
 scsfile: format of an SCCS file. scsfile.4
 undo a previous get of an SCCS file. unget: unget.1
 val: validate SCCS file. val.1

sact: print current
 admin: create and administer
 what: identify
 of an SCCS file.
 /start/stop the LP request
 clear: clear terminal
 twinkle: twinkle stars on the
 terminals. se:
 display editor/ vi, view:
 inittab:
 system initialization shell
 program.
 terminals.
 bsearch: binary
 grep, egrep, fgrep:
 accounting file(s). acctcom:
 lsearch: linear
 hcreate, hdestroy: manage hash
 tdelete, twalk: manage binary
 /mrand48, jrand48, srand48,
 shmget: get shared memory
 brk, sbrk: change data
 to two sorted files. comm:
 multiplexing.
 greek:
 of a file. cut: cut out
 file. dump:
 semctl:
 semop:
 ipcrm: remove a message queue,
 semget: get set of
 operations.
 a group of processes. kill:
 mail. mail, rmail:
 send:
 socket.
 line printer. lp, cancel:
 reset the teletype bits to a
 stream.
 IDs. setuid,
 getgrent, getgrgid, getgrnam,
 cpu.
 goto.
 encryption. crypt,
 getpwent, getpwuid, getpwnam,
 login time. profile:
 gettydefs: speed and terminal
 disktune - tune floppy disk
 group IDs.
 /getutid, getutline, pututline,
 data in a machine/ sputl,
 standard/restricted command/
 operations. shmctl:
 queue, semaphore set or
 shmop:
 shmget: get
 remsh: remote
 system: issue a
 SCCS file editing activity. sact.1
 SCCS files. admin.1
 SCCS files. what.1
 sccsdiff: compare two versions sccsdiff.1
 sccsfile: format of SCCS file. sccsfile.4
 scheduler and move requests. lpsched.1m
 screen. clear.1
 screen. twinkle.6
 screen editor for video se.1
 screen oriented (visual) vi.1
 script for the init process. inittab.4
 scripts. /rc, powerfail: brc.1m
 sdiff: side-by-side difference sdiff.1
 se: screen editor for video se.1
 search. bsearch.3c
 search a file for a pattern. grep.1
 search and print process acctcom.1
 search and update. lsearch.3c
 search tables. hsearch, hsearch.3c
 search trees. tsearch, tsearch.3c
 sed: stream editor. sed.1
 seed48, lcong48: generate/ drand48.3c
 segment. shmget.2
 segment space allocation. brk.2
 select or reject lines common comm.1
 select: synchronous i/o select.2
 select terminal filter. greek.1
 selected fields of each line cut.1
 selected parts of an object dump.1
 semaphore control operations. semctl.2
 semaphore operations. semop.2
 semaphore set or shared memory/ ipcrm.1
 semaphores. semget.2
 semctl: semaphore control semctl.2
 semget: get set of semaphores. semget.2
 semop: semaphore operations. semop.2
 send a signal to a process or kill.2
 send mail to users or read mail.1
 send message from a socket. send.2
 send: send message from a send.2
 send/cancel requests to an LP lp.1
 sensible state. reset: reset.1
 setbuf: assign buffering to a setbuf.3s
 setgid: set user and group setuid.2
 setgrent, endgrent: get group/ getgrent.3c
 sethostname: set name of host sethostname.2
 setjmp, longjmp: non-local setjmp.3c
 setkey, encrypt: generate DES crypt.3c
 setmnt: establish mount table. setmnt.1m
 setpgrp: set process group ID. setpgrp.2
 setpwent, endpwent: get/ getpwent.3c
 setting up an environment at profile.4
 settings used by getty. gettydefs.4
 settling time parameters. disktime.1m
 setuid, setgid: set user and setuid.2
 setutent, endutent, utmpname:/ getut.3c
 sgetl: access long numeric sputl.3x
 sh, rsh: shell, the sh.1
 shared memory control shmctl.2
 shared memory id. /a message ipcrm.1
 shared memory operations. shmop.2
 shared memory segment. shmget.2
 shell remsh.1
 shell command. system.3s

with C-like syntax. csh: a
 shutacct, startup, turnacct,
 system initialization
 command programming/ sh, rsh:
 operations.
 segment.
 operations.
 /prdaily, prtacct, runacct,
 processing.
 program. sdiff:
 login:
 pause: suspend process until
 what to do upon receipt of a
 upon receipt of a signal.
 of processes. kill: send a
 ssignal, gsignal: software
 lex: generate programs for
 generator. rand, srand:
 tc: phototypesetter
 atan, atan2: trigonometric/
 ssp: make output
 functions.
 size:
 an interval.
 interval.
 documents, view graphs, and
 typesetting view graphs and
 current/ ttyslot: find the
 spline: interpolate
 sno:
 SNOBOL interpreter. sno.1
 SNOBOL interpreter. sno.1
 accept a connection on a
 initiate a connection on a
 receive message from a
 send: send message from a
 address associated with a
 communication.
 associated with a socket.
 loop:
 ssignal, gsignal:
 qsort: quicker
 tsort: topological
 sort:
 sort and/or merge files.
 sort: sort and/or merge files.
 sorted files. comm: select comm.1
 source. /create an error mkstr.1
 space allocation. brk.2
 spaced. ssp.1
 spawn getty to a remote ct.1c
 specification in text files. fspec.4
 specified device. /turn on/off exterr.1
 specify what to do upon signal.2
 speed, and line discipline. getty.1m
 used by getty. gettydefs:
 hashcheck: find spelling/
 spelling/ spell, hashmake, spellin, spell.1
 spelling/ spell, hashmake: find
 spellin, hashcheck: find
 curve.
 csplit: context
 split:
 efl files. fsplit:
 pieces.
 uuclean: uucp
 shell (command interpreter) csh.1
 shell procedures for/ /runacct, acctsh.1m
 shell scripts. /rc, powerfail: brc.1m
 shell, the standard/restricted sh.1
 shmctl: shared memory control shmctl.2
 shmget: get shared memory shmget.2
 shmop: shared memory shmop.2
 shutacct, startup, turnacct:/ acctsh.1m
 shutdown: terminate all shutdown.1m
 side-by-side difference sdiff.1
 sign on. login.1
 signal. pause.2
 signal: signal: specify signal.2
 signal: specify what to do signal.2
 signal to a process or a group kill.2
 signals. ssignal.3c
 simple lexical tasks. lex.1
 simple random-number rand.3c
 simulator. tc.1
 sin, cos, tan, asin, acos, trig.3m
 single spaced. ssp.1
 sinh, cosh, tanh: hyperbolic sinh.3m
 size: size of an object file. size.1
 size: size of an object file. size.1
 sleep: suspend execution for sleep.1
 sleep: suspend execution for sleep.3c
 slides. mmt, mvt: typeset mmt.1
 slides. /macro package for mv.5
 slot in the utmp file of the ttyslot.3c
 smooth curve. spline.1g
 sno: SNOBOL interpreter. sno.1
 SNOBOL interpreter. sno.1
 socket. accept: accept.2
 socket. connect: connect.2
 socket. receive: receive.2
 socket. send.2
 socket. socketaddr: return socketaddr.2
 socket: create an endpoint for socket.2
 socketaddr: return address socketaddr.2
 software loopback interface. lo.5
 software signals. ssignal.3c
 sort. qsort.3c
 sort. tsort.1
 sort and/or merge files. sort.1
 sort: sort and/or merge files. sort.1
 sorted files. comm: select comm.1
 source. /create an error mkstr.1
 space allocation. brk.2
 spaced. ssp.1
 spawn getty to a remote ct.1c
 specification in text files. fspec.4
 specified device. /turn on/off exterr.1
 specify what to do upon signal.2
 speed, and line discipline. getty.1m
 speed and terminal settings gettydefs.4
 spell, hashmake, spellin, spell.1
 spellin, hashcheck: find spell.1
 spelling errors. /hashmake, spell.1
 spline: interpolate smooth spline.1g
 split. csplit.1
 split a file into pieces. split.1
 split fortran, ratfor, or fsplit.1
 split: split a file into split.1
 spool directory clean-up. uuclean.1m

lpr: line printer
 lpadm: configure the LP output. printf, fprintf, numeric data in a machine/ power, exp, log, log10, pow, exponential, logarithm, power, generator. rand, /nrand48, mrand48, jrand48, formats suitable for Motorola rcvhex: translates Motorola input. scanf, fscanf, signals. spaced.
 package. stdio: communication/ stdipc: sh, rsh: shell, the twinkle: twinkle
 lpsched, lpshut, lpmove: boot: /prtacct, runacct, shutacct, system call.
 stat: data returned by ustat: get file system ff: list file names and rstat: network communication facilities ps: report process stat, fstat: get file lpstat: print LP feof, clearerr, fileno: stream control. uustat: uucp ruptime: show host input/output package. communication package.
 wait for child process to strncmp, strcpy, strncpy, /strcpy, strncpy, strlen, strncpy, / strcat, strncat, /strncat, strcmp, strncmp, /strcmp, strcmp, strlen, /strchr, strpbrk, strspn, fflush: close or flush a fopen, freopen, fdopen: open a reposition a file pointer in a get character or word from fgets: get a string from a put character or word on a puts, fputs: put a string on a setbuf: assign buffering to a push character back into input sed: /feof, clearerr, fileno: long integer and base-64 ASCII convert date and time to floating-point number to gps: graphical primitive gets, fgets: get a puts, fputs: put a strspn, strcspn, strtok: number. atoi: convert ASCII strtol, atol, atoi: convert strings in an object, or/ strings: find the printable
 spooler. lpr.1
 spooling system. lpadmin.1m
 sprintf: print formatted printf.3s
 sputl, sgetl: access long sputl.3x
 sqrt: exponential, logarithm, exp.3m
 square root functions. /sqrt: exp.3m
 srand: simple random-number rand.3c
 srand48, seed48, lcong48: drand48.3c
 S-record downloading. /ASCII hex.1
 S-records from downloading/ rcvhex.1
 sscanf: convert formatted scanf.3s
 ssignal, gsignal: software ssignal.3c
 ssp: make output single ssp.1
 standard buffered input/output stdio.3s
 standard interprocess stdipc.3c
 standard/restricted command/ sh.1
 stars on the screen. twinkle.6
 start/stop the LP request/ lpsched.1m
 startup procedures. boot.8
 startup, turnacct: shell/ acctsh.1m
 stat: data returned by stat stat.5
 stat, fstat: get file status. stat.2
 stat system call. stat.5
 statistics. ustat.2
 statistics for a file system. ff.1m
 statistics program rstat.1
 status. /report inter-process ipcs.1
 status. ps.1
 status. stat.2
 status information. lpstat.1
 status inquiries. ferror, ferror.3s
 status inquiry and job uustat.1c
 status of local machines ruptime.1
 stdio: standard buffered stdio.3s
 stdipc: standard interprocess stdipc.3c
 stime: set time. stime.2
 stop or terminate. wait: wait.2
 strcat, strncat, strcmp, string.3c
 strchr, strchr, strpbrk, / string.3c
 strcmp, strncmp, strcpy, string.3c
 strcpy, strncpy, strlen, / string.3c
 strcspn, strtok: string/ string.3c
 stream. fclose, fclose.3s
 stream. fopen.3s
 stream. fseek, rewind, ftell: fseek.3s
 stream. /getchar, fgetc, getw:getc.3s
 stream. gets, gets.3s
 stream. /putchar, fputc, putw:putc.3s
 stream. puts.3s
 stream. setbuf.3s
 stream. ungetc: ungetc.3s
 stream editor. sed.1
 stream status inquiries. ferror.3s
 string. /l64a: convert between a64l.3c
 string. /asctime, tzset: ctime.3c
 string. /fcvt, gcvt: convert ecvt.3c
 string. format of graphical/ gps.4
 string from a stream. gets.3s
 string on a stream. puts.3s
 string operations. /strpbrk, string.3c
 string to floating-point atof.3c
 string to integer. strtol.3c
 strings: find the printable strings.1
 strings in an object, or other/ strings.1

relocation bits.
 /strncmp, strcpy, strncpy, string.3c
 strcpy, strncpy, / strcat, string.3c
 strcat, strncat, strcmp, string.3c
 /strcmp, strncmp, strcpy, string.3c
 /strlen, strchr, strchr, string.3c
 /strncpy, strlen, strchr, string.3c
 /strchr, strchr, strpbrk, string.3c
 /strpbrk, strspn, strcspn, string.3c
 string to integer.
 processes using a file or file terminal.
 another user.
 plot: graphics interface
 intro: introduction to
 /same lines of several files or
 /files into ASCII formats
 file. sum7:
 the files in the/ sumdir:
 count of a file.
 a file.
 characters in the files in/
 du:
 accounting/ acctcms: command
 sync: update the
 sync: update
 su: become
 interval. sleep:
 interval. sleep:
 pause:
 swab:
 strip: remove
 select:
 interpreter) with C-like
 error/ perror, errno,
 perror, errno, sys_errlist,
 information. uvar: returns
 uuto, uupick: public UNIX
 master device information
 mnttab: mounted file system
 setmnt: establish mount
 /etc/hosts: host
 hdestroy: manage hash search
 tbl: format
 tabs: set
 ctags: maintain a
 a file.
 remote machine.
 remote machine..
 machine. take:
 machine.. take7:
 trigonometric/ sin, cos,
 sinh, cosh,
 recover files from a backup
 tp: manipulate
 hpio: HP 2645A terminal
 tar:
 tp: magnetic
 file system backup. filesave,
 strip: remove symbols and strip.1
 strlen, strchr, strchr, / string.3c
 strncat, strcmp, strncmp, string.3c
 strncmp, strcpy, strncpy, / string.3c
 strncpy, strlen, strchr, / string.3c
 strpbrk, strspn, strcspn, / string.3c
 strchr, strpbrk, strspn, / string.3c
 strspn, strcspn, strtok: / string.3c
 strtok: string operations. string.3c
 strtol, atol, atoi: convert strtol.3c
 structure. fuser: identify fuser.1m
 stty: set the options for a stty.1
 su: become super-user or su.1
 subroutines. plot.3x
 subroutines and libraries. intro.3
 subsequent lines of one file. paste.1
 suitable for Motorola S-record/ hex.1
 sum and count blocks in a sum7.1
 sum and count characters in sumdir.1
 sum: print checksum and block sum.1
 sum7: sum and count blocks in sum7.1
 sumdir: sum and count sumdir.1
 summarize disk usage. du.1
 summary from per-process acctcms.1m
 super block. sync.1
 super-block. sync.2
 super-user or another user. su.1
 suspend execution for an sleep.1
 suspend execution for sleep.3c
 suspend process until signal. pause.2
 swab: swap bytes. swab.3c
 swap bytes. swab.3c
 symbols and relocation bits. strip.1
 sync: update super-block. sync.2
 sync: update the super block. sync.1
 synchronous i/o multiplexing. select.2
 syntax. csh: a shell (command csh.1
 sys_errlist, sys_nerr: system perror.3c
 sys_nerr: system error/ perror.3c
 system-specific configuration uvar.2
 System-to-UNIX System file/ uuto.1c
 table. master: master.4
 table. mnttab.4
 table. setmnt.1m
 table for bnet. hosts.7
 tables. hsearch, hcreate, hsearch.3c
 tables for nroff or troff. tbl.1
 tabs on a terminal. tabs.1
 tabs: set tabs on a terminal. tabs.1
 tags file for a C program. ctags.1
 tail: deliver the last part of tail.1
 take: takes a file from a take.1c
 take7: takes a file from a take7.1c
 takes a file from a remote take.1c
 takes a file from a remote take7.1c
 tan, asin, acos, atan, atan2: trig.3m
 tanh: hyperbolic functions. sinh.3m
 tape. frec: frec.1m
 tape archive. tp.1
 tape file archiver. hpio.1
 tape file archiver. tar.1
 tape format. tp.4
 tapesave: daily/weekly UNIX filesave.1m
 tar: tape file archiver. tar.1

programs for simple lexical
deroff: remove nroff/troff,
or troff.
Control Protocol.
search trees. tsearch,
4014: paginator for the
state. reset: reset the
last logins of users and
initialization. init,
temporary file. tmpnam,
tmpfile: create a
tempnam: create a name for a
terminals.
data base.
for the Tektronix 4014
functions of the DASI 450
ct: spawn getty to a remote
generate file name for
stty: set the options for a
tabs: set tabs on a
isatty: find name of a
animate worms on a display
termcap:
greek: select
/tgetstr, tgoto, tputs:
termio: general
tty: controlling
dial: establish an out-going
tset: set
clear: clear
getty. gettydefs: speed and
hpio: HP 2645A
and line/ getty: set
ttytype: data base of
functions of DASI 300 and 300s
of HP 2640 and 2621-series
se: screen editor for video
term: conventional names for
tty: get the
for child process to stop or
kill:
shutdown:
exit, _exit:
daemon. errstop:
interface.
command.
quiz:
nroff: format
troff: typeset
ed, red:
ex, edit:
change the format of a
fspec: format specification in
/checkeq: format mathematical
prepare constant-width
typesetting. nroff7:
typesetting. troff7:
plock: lock process,
tgetstr, tgoto, tputs:/
tputs:/ tgetent, tgetnum,
tgoto, tputs:/ tgetent,
tgetent, tgetnum, tgetflag,

tasks. lex: generate lex.1
tbl, and eqn constructs. deroff.1
tbl: format tables for nroff tbl.1
tc: phototypesetter simulator. tc.1
tcp: Internet Transmission tcp.5
tdelete, twalk: manage binary tsearch.3c
tee: pipe fitting. tee.1
Tektronix 4014 terminal. 4014.1
teletype bits to a sensible reset.1
teletypes. last: indicate last.1
telinit: process control init.1m
tempnam: create a name for a tmpnam.3s
temporary file. tmpfile.3s
temporary file. tmpnam, tmpnam.3s
term: conventional names for term.5
termcap: terminal capability termcap.5
terminal. 4014: paginator 4014.1
terminal. 450: handle special 450.1
terminal. ct.1c
terminal. ctermid: ctermid.3s
terminal. stty.1
terminal. tabs.1
terminal. ttyname, ttyname.3c
terminal. worms: worms.6
terminal capability data base. termcap.5
terminal filter. greek.1
terminal independent operation/ termcap.3
terminal interface. termio.7
terminal interface. tty.7
terminal line connection. dial.3c
terminal modes. tset.1
terminal screen. clear.1
terminal settings used by gettydefs.4
terminal tape file archiver. hpio.1
terminal type, modes, speed, getty.1m
terminal types by port. ttytype.4
terminals. /handle special 300.1
terminals. /special functions hp.1
terminals. se.1
terminals. term.5
terminal's name. tty.1
terminate. wait: wait wait.2
terminate a process. kill.1
terminate all processing. shutdown.1m
terminate process. exit.2
terminate the error-logging errstop.1m
termio: general terminal termio.7
test: condition evaluation test.1
test your knowledge. quiz.6
text. nroff.1
text. troff.1
text editor. ed.1
text editor ex.1
text file. newform: newform.1
text files. fspec.4
text for nroff or troff. eqn.1
text for troff. cw, checkcw: cw.1
text formatting and nroff7.1
text formatting and troff7.1
text, or data in memory. plock.2
tgetent, tgetnum, tgetflag, termcap.3
tgetflag, tgetstr, tgoto, termcap.3
tgetnum, tgetflag, tgetstr, termcap.3
tgetstr, tgoto, tputs:/ termcap.3

/tgetnum, tgetflag, tgetstr, termcap.3
tic-tac-toe. ttt.6
time. at: at.1
time. dcopy: copy file dcopy.1m
time. profile: setting profile.4
time. stime.2
time. time.2
time. time.1
time a command. time.1
time a command; report process timex.1
time: get time. time.2
time parameters. disktime disktime.1m
time profile. profil.2
time: time a command. time.1
time to string. /asctime, ctime.3c
time used. clock.3c
times. times: times.2
times. utime: set utime.2
times: get process and child times.2
times of a file. touch: touch.1
timex: time a command; report timex.1
tmpfile: create a temporary tmpfile.3s
tmpnam, tempnam: create a name tmpnam.3s
toascii: translate characters. conv.3c
to/from a process. popen.3s
_tolower, toascii: translate/ conv.3c
tolower, _toupper, _tolower, conv.3c
topological sort. tsort.1
total accounting files. acctmrg.1m
touch: update access and touch.1
_toupper, _tolower, toascii: conv.3c
toupper, tolower, _toupper, conv.3c
tp: magnetic tape format. tp.4
tp: manipulate tape archive. tp.1
tplot: graphics filters. tplot.1g
tputs: terminal independent/ termcap.3
tr: translate characters. tr.1
trace. ptrace.2
transfer data. blt.3
translate characters. conv.3c
translate characters. tr.1
translates Motorola S-records rcvhex.1
translates object files into hex.1
Transmission Control Protocol. tcp.5
tree. ftw.3c
trees. tsearch, tdelete, tsearch.3c
trek: trekkie game. trek.6
trekkie game. trek.6
trigonometric functions. /cos, trig.3m
troff. cw, checkcw: prepare cw.1
troff. /neqn, checkeq: format eqn.1
troff. tbl: tbl.1
troff macro package for mv.5
troff: typeset text. troff.1
troff7: text formatting and troff7.1
true, false: provide truth true.1
truth value about your/ machid.1
truth values. true.1
Try to escape the killer chase.6
tsearch, tdelete, twalk: tsearch.3c
tset: set terminal modes. tset.1
tsort: topological sort. tsort.1
ttt, cubic: tic-tac-toe. ttt.6
tty: controlling terminal tty.7
tty: get the terminal's name. tty.1

- tune floppy disk settling
profil: execution
tzset: convert date and
clock: report CPU
get process and child process
file access and modification
process times.
update access and modification
process data and system/
file.
for a temporary file.
/tolower, _toupper, _tolower,
popen, pclose: initiate pipe
toupper, tolower, _toupper,
toascii: translate/ _toupper,
tsort:
acctmrg: merge or add
modification times of a file.
translate/ _toupper, tolower,
_tolower, toascii: translate/
/tgetflag, tgetstr, tgoto,
ptrace: process
blt, blt512: block
/_toupper, _tolower, toascii:
tr:
from downloading into/ rcvhex:
ASCII formats suitable/ hex:
tcp: Internet
ftw: walk a file
twalk: manage binary search
trek:
tan, asin, acos, atan, atan2:
constant-width text for
mathematical text for nroff or
format tables for nroff or
typesetting view graphs/ mv: a
typesetting.
values.
m68k, pdp11, u3b, vax: provide
true, false: provide
robots. chase:
manage binary search trees.
interface.

graphics for the extended
a terminal.
utmp file of the current/
types by port.
parameters. disktime -
/runacct, shutacct, startup,
trees. tsearch, tdelete,
twinkle:
screen.
file: determine file
value about your processor
getty: set terminal
for the extended TTY-37
types: primitive system data
ttytype: data base of terminal
types.
graphs, and slides. mmt, mvt:
troff:
nroff7: text formatting and
troff7: text formatting and
mv: a troff macro package for
/localtime, gmtime, asctime,
about your/ m68k, pdp11,
Protocol.
getpw: get name from
limits.
creation mask.
mask.
file system. mount,
UNIX system.
UNIX System.
ul: do
file. unget:
an SCCS file.
into input stream.
/seed48, lcong48: generate
a file.
mktemp: make a
unlink system calls. link,
entry.
unlink: exercise link and
umount:
files. pack, pcatt,
lsearch: linear search and
times of a file. touch:
of programs. make: maintain,
badblk: program to set or
machines. updater:
machines. updater:
sync:
sync:
two machines.
two machines.
du: summarize disk
character login name of
logname: return login name of
become super-user or another
the utmp file of the current
write: write to another
setuid, setgid: set
id: print
TTY-37 type-box. greek:
ttyname, isatty: find name of
ttslot: find the slot in the
ttytype: data base of terminal
tune floppy disk settling time
turnacct: shell procedures for/
twalk: manage binary search
twinkle: twinkle stars on the screen.
twinkle: twinkle stars on the
type.
type. /u3b, vax: provide truth
type, modes, speed, and line/
type-box. greek: graphics
types.
types by port.
types: primitive system data
typeset documents, view
typeset text.
typesetting.
typesetting.
typesetting view graphs and/
tzset: convert date and time/
u3b, vax: provide truth value
udp: Internet User Datagram
UID.
ul: do underlining.
ulimit: get and set user
umask: set and get file
umask: set file-creation mode
umount: mount and dismount
umount: unmount a file system.
uname: get name of current
uname: print name of current
underlining.
undo a previous get of an SCCS
unget: undo a previous get of
ungetc: push character back
uniformly distributed/
uniq: report repeated lines in
unique file name.
units: conversion program.
unlink: exercise link and
unlink: remove directory
unlink system calls. link,
unmount a file system.
unpack: compress and expand
update.
update access and modification
update, and regenerate groups
update bad block information.
update files between two
update files between two
update super-block.
update the super block.
updater: update files between
updater: update files between
usage.
user. cuserid: get
user.
user. su:
user. /find the slot in
user.
user and group IDs.
user and group IDs and names.

udp: Internet
/getgid, getegid: get real
environ:
environ:
ulimit: get and set
/get real user, effective
wall: write to all
last: indicate last logins of
mail, rmail: send mail to
fuser: identify processes
statistics.
modification times.
utmp, wtmp:
endutent, utmpname: access
ttslot: find the slot in the
entry formats.
/pututline, setutent, endutent,
clean-up.
uucp: monitor
uuclean:
control. uustat:
unix copy.
copy. uucp,
uucp, uulog,
System-to-UNIX System/ uuto,
and job control.
System-to-UNIX System file/
execution.
configuration information.
val:
abs: return integer absolute
/pdp11, u3b, vax: provide truth
getenv: return
ceiling, remainder, absolute
true, false: provide truth
your/ m68k, pdp11, u3b,
option letter from argument
assert:
of directory (Berkeley
vchk:
vc:
version: reports
get: get a
number of files.
scsdiff: compare two
(visual) display editor based/
se: screen editor for
mmt, mvt: typeset documents,
macro package for typesetting
display editor based on/ vi,
file perusal filter for crt
on/ vi, view: screen oriented
systems with label checking.
file system: format of system
process.
or terminate. wait:
to stop or terminate.
ftw:
User Datagram Protocol.
user, effective user, real/
user environment.
user environment.
user limits.
user, real group, and/
users.
users and teletypes.
users or read mail.
using a file or file/
ustat: get file system
utime: set file access and
utmp and wtmp entry formats.
utmp file entry. /setutent,
utmp file of the current user.
utmp, wtmp: utmp and wtmp
utmpname: access utmp file/
uuclean: uucp spool directory
uucp network.
uucp spool directory clean-up.
uucp status inquiry and job
uucp, uulog, uuname: unix to
uulog, uuname: unix to unix
uuname: unix to unix copy.
uupick: public UNIX
uustat: uucp status inquiry
uustat: uucp status inquiry
uustat: uucp status inquiry
uuto, uupick: public UNIX
uux: unix to unix command
uvar: returns system-specific
val: validate SCCS file.
validate SCCS file.
value.
value about your processor/
value for environment name.
value functions. /fabs: floor,
values.
vax: provide truth value about
vc: version control.
vchk: version checkup.
vector. getopt: get
verify program assertion.
version). ls7: list contents
version checkup.
vc:
version: reports
version number of files.
version of an SCCS file.
version: reports version
versions of an SCCS file.
vi, view: screen oriented
video terminals.
view graphs, and slides.
view graphs and slides. /troff
view: screen oriented (visual)
viewing. more:
(visual) display editor based
volcopy, labelit: copy file
volume.
wait: await completion of
wait for child process to stop
wait: wait for child process
walk a file tree.
wall: write to all users.
wc: word count.

see: see what a file has in it. see.1
 what: identify SCCS files. what.1
 signal. signal: specify what to do upon receipt of a signal.2
 crashes. crash: what to do when the system crash.8
 whodo: who is doing what. whodo.1m
 machines rwho: who is logged in on local rwho.1
 who: who is on the system. who.1
 who: who is on the system. who.1
 whodo: who is doing what. whodo.1m
 cd: change working directory. cd.1
 chdir: change working directory. chdir.2
 get pathname of current working directory. getcwd: getcwd.3c
 pwd: working directory name. pwd.1
 worm: Play the growing worm game. worm.6
 game. worm: Play the growing worm worm.6
 display terminal. worms: animate worms on a worms.6
 worms: animate worms on a display terminal. worms.6
 write: write on a file. write.2
 putpwent: write password file entry. putpwent.3c
 wall: write to all users. wall.1m
 write: write to another user. write.1
 write: write on a file. write.2
 write: write to another user. write.1
 writing. /provide exclusive lockf.2
 writing. open.2
 file regions for reading or wtmp entry formats. utmp.4
 open: open for reading or wtmp: utmp and wtmp entry utmp.4
 utmp, wtmp: utmp and formats. utmp, wtmpfix: manipulate connect fwtmp.1m
 accounting records. fwtmp, wump: the game of wump.6
 hunt-the-wumpus. xargs: construct argument xargs.1
 list(s) and execute command. y0, y1, yn: Bessel functions. bessel.3m
 j0, j1, jn, y1, yn: Bessel functions. bessel.3m
 j0, j1, jn, y0, compiler-compiler. yacc: yet another yacc.1
 j0, j1, jn, y0, y1, yn: Bessel functions. bessel.3m

INTRO (IM)

INTRO (IM)

NAME

intro — introduction to system maintenance commands and application programs

DESCRIPTION

This section describes, in alphabetical order, commands that are used chiefly for system maintenance and administration purposes. The commands in this section should be used along with those listed in Section 1 of the *UniPlus+ User's Manual*. References to other manual entries not of the form *name(1M)*, *name(7)* or *name(8)* refer to entries of that manual.

COMMAND SYNTAX

Unless otherwise noted, commands described in this section accept options and other arguments according to the following syntax:

name [*option(s)*] [*cmdarg(s)*]

where:

name The name of an executable file.

option — *noargletter(s)* or,
 — *argletter<>optarg*
 where <> is optional white space.

noargletter A single letter representing an option without an argument.

argletter A single letter representing an option requiring an argument.

optarg Argument (character string) satisfying preceding *argletter*.

cmdarg Path name (or other command argument) *not* beginning with
 — or, — by itself indicating the standard input.

SEE ALSO

getopt(1), getopt(3C).
UniPlus+ User's Manual.
UniPlus+ Administrator's Guide.

DIAGNOSTICS

Upon termination, each command returns two bytes of status, one supplied by the system and giving the cause for termination, and (in the case of "normal" termination) one supplied by the program (see *wait(2)* and *exit(2)*). The former byte is 0 for normal termination; the latter is customarily 0 for successful execution and non-zero to indicate troubles such as erroneous parameters, bad or inaccessible data, or other inability to cope with the task at hand. It is called variously "exit code", "exit status", or "return code", and is described only where special conventions are involved.

BUGS

Regretfully, many commands do not adhere to the aforementioned syntax.

NAME

accept, reject — allow/prevent LP requests

SYNOPSIS

/usr/lib/accept destinations
/usr/lib/reject [-r[reason]] destinations

DESCRIPTION

Accept allows *lp(1)* to accept requests for the named *destinations*. A *destination* can be either a printer or a class of printers. Use *lpstat(1)* to find the status of *destinations*.

Reject prevents *lp(1)* from accepting requests for the named *destinations*. A *destination* can be either a printer or a class of printers. Use *lpstat(1)* to find the status of *destinations*. The following option is useful with *reject*.

-r[reason] Associates a *reason* with preventing *lp* from accepting requests. This *reason* applies to all printers mentioned up to the next **-r** option. *Reason* is reported by *lp* when users direct requests to the named *destinations* and by *lpstat(1)*. If the **-r** option is not present or the **-r** option is given without a *reason*, then a default *reason* will be used.

FILES

/usr/spool/lp/*

SEE ALSO

enable(1), lp(1), lpadmin(1M), lpsched(1M), lpstat(1).

NAME

acctdisk, acctdusg, accton, acctwtmp - overview of accounting and miscellaneous accounting commands

SYNOPSIS

```
/usr/lib/acct/acctdisk
/usr/lib/acct/acctdusg [-u file] [-p file]
/usr/lib/acct/accton [file]
/usr/lib/acct/acctwtmp "reason"
```

DESCRIPTION

Accounting software is structured as a set of tools (consisting of both C programs and shell procedures) that can be used to build accounting systems. *Acctsh*(1M) describes the set of shell procedures built on top of the C programs.

Connect time accounting is handled by various programs that write records into */usr/adm/utmp*, as described in *utmp*(4). The programs described in *acctcon*(1M) convert this file into session and charging records, which are then summarized by *acctmerg*(1M).

Process accounting is performed by the UNIX System kernel. Upon termination of a process, one record per process is written to a file (normally */usr/adm/pacct*). The programs in *acctprc*(1M) summarize this data for charging purposes; *acctcms*(1M) is used to summarize command usage. Current process data may be examined using *acctcom*(1).

Process accounting and connect time accounting (or any accounting records in the format described in *acct*(4)) can be merged and summarized into total accounting records by *acctmerg* (see *tacct* format in *acct*(4)). *Prtacct* (see *acctsh*(1M)) is used to format any or all accounting records.

Acctdisk reads lines that contain user ID, login name, and number of disk blocks and converts them to total accounting records that can be merged with other accounting records.

Acctdusg reads its standard input (usually from *find* / *-print*) and computes disk resource consumption (including indirect blocks) by login. If *-u* is given, records consisting of those file names for which *acctdusg* charges no one are placed in *file* (a potential source for finding users trying to avoid disk charges). If *-p* is given, *file* is the name of the password file. This option is not needed if the password file is */etc/passwd*.

Accton alone turns process accounting off. If *file* is given, it must be the name of an existing file, to which the kernel appends process accounting records (see *acct*(2) and *acct*(4)).

Acctwtmp writes a *utmp*(4) record to its standard output. The record contains the current time and a string of characters that describe the *reason*. A record type of ACCOUNTING is assigned (see *utmp*(4)). *Reason* must be a string of 11 or less characters, numbers, \$, or spaces. For example, the following are suggestions for use in reboot and shutdown procedures, respectively:

```
acctwtmp `uname` >> /etc/wtmp
acctwtmp "file save" >> /etc/wtmp
```

FILES

/etc/passwd used for login name to user ID conversions

/usr/lib/acct holds all accounting commands listed in
sub-class 1M of this manual
/usr/adm/pacct current process accounting file
/etc/wtmp login/logoff history file

SEE ALSO

acctcms(1M), acctcom(1), acctcon(1M), acctmerg(1M), acctprc(1M),
acctsh(1M), fwtmp(1M), runacct(1M), acct(2), acct(4), utmp(4).
"UNIX System Accounting" in the *UniPlus+ Administrator's Guide*.

NAME

acctcms — command summary from per-process accounting records

SYNOPSIS

/usr/lib/acct/acctcms [options] files

DESCRIPTION

Acctcms reads one or more *files*, normally in the form described in *acct(4)*. It adds all records for processes that executed identically-named commands, sorts them, and writes them to the standard output, normally using an internal summary format. The *options* are:

- a Print output in ASCII rather than in the internal summary format. The output includes command name, number of times executed, total kcore-minutes, total CPU minutes, total real minutes, mean size (in K), mean CPU minutes per invocation, and "hog factor", as in *acctcom(1)*. Output is normally sorted by total kcore-minutes.
- c Sort by total CPU time, rather than total kcore-minutes.
- j Combine all commands invoked only once under "***other".
- n Sort by number of command invocations.
- s Any file names encountered hereafter are already in internal summary format.

EXAMPLE

A typical sequence for performing daily command accounting and for maintaining a running total is:

```
acctcms file ... > today
cp total previoustotal
acctcms -s today previoustotal > total
acctcms -a -s today
```

SEE ALSO

acct(1M), acctcom(1), acctcon(1M), acctmerg(1M), acctprc(1M),
acctsh(1M), fwtmp(1M), runacct(1M), acct(2), acct(4), utmp(4).

NAME

acctcon1, acctcon2 — connect-time accounting

SYNOPSIS

/usr/lib/acct/acctcon1 [options]

/usr/lib/acct/acctcon2

DESCRIPTION

Acctcon1 converts a sequence of login/logoff records read from its standard input to a sequence of records, one per login session. Its input should normally be redirected from /etc/wtmp. Its output is ASCII, giving device, user ID, login name, prime connect time (seconds), non-prime connect time (seconds), session starting time (numeric), and starting date and time. The *options* are:

- p** Print input only, showing line name, login name, and time (in both numeric and date/time formats).
- t** *Acctcon1* maintains a list of lines on which users are logged in. When it reaches the end of its input, it emits a session record for each line that still appears to be active. It normally assumes that its input is a current file, so that it uses the current time as the ending time for each session still in progress. The **-t** flag causes it to use, instead, the last time found in its input, thus assuring reasonable and repeatable numbers for non-current files.
- i file** *File* is created to contain a summary of line usage showing line name, number of minutes used, percentage of total elapsed time used, number of sessions charged, number of logins, and number of logoffs. This file helps track line usage, identify bad lines, and find software and hardware oddities. Hang-up, termination of *login(1)* and termination of the login shell generate a logoff records, so that the number of logoffs is often three to four times the number of sessions. See *init(1M)* and *utmp(4)*.
- o file** *File* is filled with an overall record for the accounting period, giving starting time, ending time, number of reboots, and number of date changes.

Acctcon2 expects as input a sequence of login session records and converts them into total accounting records (see *tacct* format in *acct(4)*).

EXAMPLE

These commands are typically used as shown below. The file *ctmp* is created only for the use of *acctprc(1M)* commands:

```
acctcon1 -t -l lineuse -o reboots <wtmp | sort +1n +2 >ctmp
acctcon2 <ctmp | acctmerg >ctacct
```

FILES

/etc/wtmp

SEE ALSO

acct(1M), *acctcms(1M)*, *acctcom(1)*, *acctmerg(1M)*, *acctprc(1M)*, *acctsh(1M)*, *fwtmp(1M)*, *runacct(1M)*, *acct(2)*, *acct(4)*, *utmp(4)*.

BUGS

The line usage report is confused by date changes. Use *wtmpfix* (see *fwtmp(1M)*) to correct this situation.

NAME

acctmerg — merge or add total accounting files

SYNOPSIS

/usr/lib/acct/acctmerg [options] [file] . . .

DESCRIPTION

Acctmerg reads its standard input and up to nine additional files, all in the **tacct** format (see *acct(4)*), or an ASCII version thereof. It merges these inputs by adding records whose keys (normally user ID and name) are identical, and expects the inputs to be sorted on those keys. *Options* are:

- a Produce output in ASCII version of **tacct**.
- l Input files are in ASCII version of **tacct**.
- p Print input with no processing.
- t Produce a single record that totals all input.
- u Summarize by user ID, rather than user ID and name.
- v Produce output in verbose ASCII format, with more precise notation for floating point numbers.

EXAMPLE

The following sequence is useful for making “repairs” to any file kept in this format:

```
acctmerg -v <file1 >file2
      edit file2 as desired ...
acctmerg -a <file2 >file1
```

SEE ALSO

acct(1M), acctcms(1M), acctcom(1), acctcon(1M), acctprc(1M), acctsh(1M), fwtmp(1M), runacct(1M), acct(2), acct(4), utmp(4).

NAME

acctprc1, acctprc2 — process accounting

SYNOPSIS

/usr/lib/acct/acctprc1 [ctmp]

/usr/lib/acct/acctprc2

DESCRIPTION

Acctprc1 reads input in the form described by *acct(4)*, adds login names corresponding to user IDs, then writes for each process an ASCII line giving user ID, login name, prime CPU time (tics), non-prime CPU time (tics), and mean memory size (in 64-byte units). If *ctmp* is given, it is expected to contain a list of login sessions, in the form described in *acctcon(1M)*, sorted by user ID and login name. If this file is not supplied, it obtains login names from the password file. The information in *ctmp* helps it distinguish among different login names that share the same user ID.

Acctprc2 reads records in the form written by *acctprc1*, summarizes them by user ID and name, then writes the sorted summaries to the standard output as total accounting records.

EXAMPLE

These commands are typically used as shown below:

```
acctprc1 ctmp </usr/adm/pacct | acctprc2 >ptacct
```

FILES

/etc/passwd

SEE ALSO.

acct(1M), acctcms(1M), acctcom(1), acctcon(1M), acctmerg(1M), acctsh(1M), fwtmp(1M), runacct(1M), acct(2), acct(4), utmp(4).

BUGS

Although it is possible to distinguish among login names that share user IDs for commands run normally, it is difficult to do this for those commands run from *cron(1M)*, for example. More precise conversion can be done by faking login sessions on the console via the *acctwtm* program in *acct(1M)*.

NAME

chargefee, ckpacct, dodisk, lastlogin, monacct, nulladm, prctmp, prdaily, prtacct, runacct, shutacct, startup, turnacct — shell procedures for accounting

SYNOPSIS

```
/usr/lib/acct/chargefee login-name number
/usr/lib/acct/ckpacct [blocks]
/usr/lib/acct/dodisk
/usr/lib/acct/lastlogin
/usr/lib/acct/monacct number
/usr/lib/acct/nulladm file
/usr/lib/acct/prctmp
/usr/lib/acct/prdaily [ mmdd ]
/usr/lib/acct/prtacct file [ "heading" ]
/usr/lib/acct/runacct [mmdd] [mmdd state]
/usr/lib/acct/shutacct [ "reason" ]
/usr/lib/acct/startup
/usr/lib/acct/turnacct on | off | switch
```

DESCRIPTION

Chargefee can be invoked to charge a *number* of units to *login-name*. A record is written to */usr/adm/fee*, to be merged with other accounting records during the night.

Ckpacct should be initiated via *cron*(1M). It periodically checks the size of */usr/adm/pacct*. If the size exceeds *blocks*, 1000 by default, *turnacct* will be invoked with argument *switch*. If the number of free disk blocks in the */usr* file system falls below 500, *ckpacct* will automatically turn off the collection of process accounting records via the *off* argument to *turnacct*. When at least this number of blocks is restored, the accounting will be activated again. This feature is sensitive to the frequency at which *ckpacct* is executed, usually by *cron*.

Dodisk should be invoked by *cron* to perform the disk accounting functions.

Lastlogin is invoked by *runacct* to update */usr/adm/acct/sum/loginlog*, which shows the last date on which each person logged in.

Monacct should be invoked once each month or each accounting period. *Number* indicates which month or period it is. If *number* is not given, it defaults to the current month (01–12). This default is useful if *monacct* is to be executed via *cron*(1M) on the first day of each month. *Monacct* creates summary files in */usr/adm/acct/fiscal* and restarts summary files in */usr/adm/acct/sum*.

Nulladm creates *file* with mode 664 and insures owner and group are *adm*. It is called by various accounting shell procedures.

Prctmp can be used to print the session record file (normally */usr/adm/acct/nlte/ctmp* created by *acctcon*1 (see *acctcon*(1M))).

Prdaily is invoked by *runacct* to format a report of the previous day's accounting data. The report resides in */usr/adm/acct/sum/rprtmmdd*

where *mmdd* is the month and day of the report. The current daily accounting reports may be printed by typing *prdaily*. Previous days' accounting reports can be printed by using the *mmdd* option and specifying the exact report date desired. Previous daily reports are cleaned up and therefore inaccessible after each invocation of *monacct*.

Prtacct can be used to format and print any total accounting (*taacct*) file.

Runacct performs the accumulation of connect, process, fee, and disk accounting on a daily basis. It also creates summaries of command usage. For more information, see *runacct*(1M).

Shutacct should be invoked during a system shutdown (usually in */etc/shutdown*) to turn process accounting off and append a "reason" record to */etc/wtmp*.

Startup should be called by */etc/rc* to turn the accounting on whenever the system is brought up.

Turnacct is an interface to *accton* (see *acct*(1M)) to turn process accounting on or off. The switch argument turns accounting off, moves the current */usr/adm/pacct* to the next free name in */usr/adm/pacctincr* (where *incr* is a number starting with 1 and incrementing by one for each additional *pacct* file), then turns accounting back on again. This procedure is called by *ckpacct* and thus can be taken care of by the *cron* and used to keep *pacct* to a reasonable size.

FILES

| | |
|---------------------------|--|
| <i>/usr/adm/fee</i> | accumulator for fees |
| <i>/usr/adm/pacct</i> | current file for per-process accounting |
| <i>/usr/adm/pacct*</i> | used if <i>pacct</i> gets large and during execution of daily accounting procedure |
| <i>/etc/wtmp</i> | login/logoff summary |
| <i>/usr/adm/acct/nite</i> | working directory |
| <i>/usr/lib/acct</i> | holds all accounting commands listed in sub-class 1M of this manual |
| <i>/usr/adm/acct/sum</i> | summary directory, should be saved |

SEE ALSO

acct(1M), *acctcms*(1M), *acctcom*(1), *acctcon*(1M), *acctmerg*(1M), *acctprc*(1M), *fwtmp*(1M), *runacct*(1M), *acct*(2), *acct*(4), *utmp*(4).

NAME

badblk — program to set or update bad block information

SYNOPSIS

badblk [*-w*] [*-m N*] /dev/rXYZ [*#S*]

DESCRIPTION

Badblk sets or updates bad block information for those disk drives that support soft sector bad block remapping.

If invoked with the *-w* option, write/verify is performed to determine if there is a bad block; otherwise only read is done.

If invoked with the *-mN* option, the number of alternate blocks will be set to *N*. *Badblk* returns an error if *N* > *NICALT* (currently 50).

/dev/rXYZ is the device name.

#S is one or more block numbers separated by blanks.

If invoked with no specific block numbers and no bad block verification has been done before, then each block on the disk is checked (either read or write/verify) and bad block information in block 0 is set up from scratch.

If invoked with no specific block numbers, but block 0 already contains bad block information set up earlier, then a verification on the whole disk is performed; any new bad blocks not already on the block 0 table will be added.

If invoked with the device name plus block numbers, then only the indicated blocks are updated in block 0.

After alternate blocks are assigned, block 0 is updated and the updated blocks are verified to make sure alternate blocks are good. If alternate blocks are not good, new alternate block numbers are assigned.

The raw device that accesses the entire disk and allows for writing block zero should be specified.

EXAMPLE

badblk -w /dev/rwlhw0

does a full write/verify on winchester 1 and updates the header block. The *rwlhw0* specifies raw (r) winchester 1 (wl), the full disk (h), with the capability of writing block 0 (w0).

badblk /dev/rwlhw0 3754 8123

adds blocks 3754 and 8123 to the badblock list.

NAME

bcopy — interactive block copy

SYNOPSIS

/etc/bcopy

DESCRIPTION

Bcopy dates from a time when neither the UNIX file system nor disk drives were as reliable as they are now. *Bcopy* copies from and to files starting at arbitrary block (512-byte) boundaries.

The following questions are asked:

to: (you name the file or device to be copied to).
offset: (you provide the starting "to" block number).
from: (you name the file or device to be copied from).
offset: (you provide the starting "from" block number).
count: (you reply with the number of blocks to be copied).

After **count** is exhausted, the **from** question is repeated (giving you a chance to concatenate blocks at the **to+offset+count** location). If you answer **from** with a carriage return, everything starts over.

Two consecutive carriage returns terminate *bcopy*.

SEE ALSO

cpio(1), dd(1).

NAME

brc, bcheckrc, rc, powerfail — system initialization shell scripts

SYNOPSIS

/etc/brc

/etc/bcheckrc

/etc/rc

/etc/powerfail

DESCRIPTION

Except for *powerfail*, these shell procedures are executed via entries in */etc/inittab* by *init*(1M) when the system is changed out of *SINGLE USER* mode. *Powerfail* is executed whenever a system power failure is detected.

The *brc* procedure clears the mounted file system table, */etc/mnttab* (see *mnttab*(4)), and loads any programmable micro-processors with their appropriate scripts.

The *bcheckrc* procedure performs all the necessary consistency checks to prepare the system to change into multi-user mode. It will prompt to set the system date and to check the file systems with *fsck*(1M).

The *rc* procedure starts all system daemons before the terminal lines are enabled for multi-user mode. In addition, file systems are mounted and accounting, error logging, system activity logging and the Remote Job Entry (RJE) system are activated in this procedure.

The *powerfail* procedure is invoked when the system detects a power failure condition. Its chief duty is to reload any programmable micro-processors with their appropriate scripts, if appropriate. It also logs the fact that a power failure occurred.

These shell procedures, in particular *rc* may be used for several run-level states. The *who*(1) command may be used to get the run-level information.

SEE ALSO

init(1M), *shutdown*(1M), *who*(1), *inittab*(4).

NAME

chroot — change root directory for a command

SYNOPSIS

/etc/chroot newroot command

DESCRIPTION

The given command is executed *relative to the new root*. The meaning of any initial slashes (/) in path names is changed for a command and any of its children to *newroot*. Furthermore, the initial working directory is *newroot*.

Notice that:

chroot newroot command > x

will create the file x relative to the original root, not the new one.

This command is restricted to the super-user.

The new root path name is always relative to the current root: even if a *chroot* is currently in effect, the *newroot* argument is relative to the current root of the running process.

EXAMPLE

chroot /users/asa ls /src

will cause the command "ls /src" to list the directory "/users/asa/src" since "/users/asa" is now effectively "/".

SEE ALSO

chdir(2).

BUGS

One should exercise extreme caution when referencing special files in the new root file system.

NAME

clri — clear i-node

SYNOPSIS

/etc/clri *file-system* *i-number* ...

DESCRIPTION

Clri writes zeros on the 64 bytes occupied by the i-node numbered *i-number*. *File-system* must be a special file name referring to a device containing a file system. After *clri* is executed, any blocks in the affected file will show up as "missing" in an *fsck(1M)* of the *file-system*. This command should only be used in emergencies and extreme care should be exercised.

Read and write permission is required on the specified *file-system* device. The i-node becomes allocatable.

The primary purpose of this routine is to remove a file which for some reason appears in no directory. If it is used to *zap* an i-node which does appear in a directory, care should be taken to track down the entry and remove it. Otherwise, when the i-node is reallocated to some new file, the old entry will still point to that file. At that point removing the old entry will destroy the new file. The new entry will again point to an unallocated i-node, so the whole cycle is likely to be repeated again and again.

EXAMPLE

clri /dev/yyyy n

where "yyyy" is a legitimate system device name, and "n" is the inode number to be cleared, will cause inode numbered "n" for device "/dev/yyyy" to be cleared to 64-bytes of 0s. Note: this instruction should only be used with caution.

SEE ALSO

fsck(1M), *fsdb(1M)*, *ncheck(1M)*, *fs(4)*.

BUGS

If the file is open, *clri* is likely to be ineffective.

NAME

cron - clock daemon

SYNOPSIS

/etc/cron

DESCRIPTION

Cron executes commands at specified dates and times according to the instructions in the file */usr/lib/crontab*. Because *cron* never exits, it should be executed only once. This is best done by running *cron* from the initialization process through the file */etc/rc* (see *init(1M)*).

The file *crontab* consists of lines of six fields each. The fields are separated by spaces or tabs. The first five are integer patterns that specify in order:

minute (0-59),
hour (0-23),
day of the month (1-31),
month of the year (1-12),
and day of the week (0-6, with 0=Sunday).

Each of these patterns may contain:

a number in the (respective) range indicated above;
two numbers separated by a minus (indicating an inclusive range);
a list of numbers separated by commas (meaning all of these numbers); or
an asterisk (meaning all legal values).

The sixth field is a string that is executed by the shell at the specified time(s). A % in this field is translated into a new-line character. Only the first line (up to a % or the end of line) of the command field is executed by the shell. The other lines are made available to the command as standard input.

Cron examines *crontab* once a minute to see if it has changed; if it has, *cron* reads it. Thus it takes only a minute for entries to become effective.

EXAMPLE

If the shell file */etc/rc* contains the command line

/etc/cron

the clock daemon will be started every time */etc/rc* is invoked, i.e., each time the system goes into multi-user mode after booting.

FILES

/usr/lib/crontab
/usr/adm/cronlog

SEE ALSO

init(1M), *sh(1)*.

DIAGNOSTICS

A history of all actions by *cron* are recorded in */usr/adm/cronlog*.

BUGS

Cron reads *crontab* only when it has changed, but it reads the in-core version of that table once a minute. A more efficient algorithm could be used. The overhead in running *cron* is about one percent of the CPU, exclusive of any commands executed by *cron*.

NAME

dcopy — copy file systems for optimal access time

SYNOPSIS

/etc/dcopy [-sX] [-an] [-d] [-v] [-ffsize:isize] inputfs outputfs

DESCRIPTION

Dcopy copies file system *inputfs* to *outputfs*. *Inputfs* is the existing file system; *outputfs* is an appropriately sized file system, to hold the reorganized result. For best results *inputfs* should be the raw device and *outputfs* should be the block device. *Dcopy* should be run on unmounted file systems (in the case of the root file system, copy to a new pack). With no arguments, *dcopy* copies files from *inputfs* compressing directories by removing vacant entries, and spacing consecutive blocks in a file by the optimal rotational gap. The possible options are:

- sX supply device information for creating an optimal organization of blocks in a file. The forms of *X* are the same as the -s option of *fsck*(1M).
- an place the files not accessed in *n* days after the free blocks of the destination file system (default for *n* is 7). If no *n* is specified then no movement occurs.
- d leave order of directory entries as is (default is to move sub-directories to the beginning of directories).
- v currently reports how many files were processed, and how big the source and destination freelists are.
- ffsize[:isize] specify the *outputfs* file system and inode list sizes (in blocks). If not given, the values from the *inputfs* are used. UniPlus⁺.1 *Dcopy* catches interrupts and quits and reports on its progress. To terminate *dcopy*, send a quit signal and *dcopy* will no longer catch interrupts or quits. *Dcopy* also attempts to modify its command line arguments so its progress can be monitored with *ps*(1).

SEE ALSO

fsck(1M), mkfs(1M), ps(1).

NAME

devnm — device name

SYNOPSIS

/etc/devnm [names]

DESCRIPTION

Devnm identifies the special file associated with the mounted file system where the argument *name* resides (as a special case, both the block device name and the swap device name is printed for the argument name / if swapping is done on the same disk section as the **root** file system). Argument names must be full path names.

This command is most commonly used by */etc/rc* (see *brc(1M)*) to construct a mount table entry for the **root** device.

EXAMPLE

/etc/devnm /usr

produces

rp1 /usr

if /usr is mounted on /dev/rp1.

FILES

/dev/rp*, /dev/dsk*
/etc/mnttab

SEE ALSO

brc(1M), setmnt(1M).

NAME

df — report number of free disk blocks

SYNOPSIS

df [-t] [-f] [file-systems]

DESCRIPTION

Df prints out the number of free blocks and free i-nodes available for on-line file systems by examining the counts kept in the super-blocks; *file-systems* may be specified either by device name (e.g., */dev/dsk1*) or by mounted directory name (e.g., */usr*). If the *file-systems* argument is unspecified, the free space on all of the mounted file systems is printed.

The *-t* flag causes the total allocated block figures to be reported as well.

If the *-f* flag is given, only an actual count of the blocks in the free list is made (free i-nodes are not reported). With this option, *df* will report on raw devices.

FILES

/dev/dsk*
/etc/mnttab

SEE ALSO

fs(4), mnttab(4).

NAME

diskformat - format a disk

SYNOPSIS

diskformat [-size #] [-dens #] [-cyl f[-t]] [-sec f[-t]] [-i #] device

DESCRIPTION

Diskformat initializes a hard disk or floppy disk and formats it according to your specifications.

The following parameters may be specified ("device" is required):

| | |
|--------------------|--|
| device | device to be formatted (must be raw device) |
| -size # | specify sector size in bytes |
| -dens # | specify density |
| -cyl #[-#] | format cylinders <i>f</i> to <i>t</i> (default <i>f</i>). A specification such as #- means "until the end". |
| -head #[-#] | Format heads <i>f</i> to <i>t</i> (default <i>f</i>). A specification such as #- means "until the end". |
| -sec #[-#] | Format sectors <i>f</i> to <i>t</i> (default <i>f</i>). A specification such as #- means "until the end". |
| -il # | Interleave factor for the disk. |

EXAMPLE

diskformat /dev/rfdc0 -dens 1 -size 128 -il 3

will format the floppy disk on drive 0, single density, 128 bytes per sector with an interleave factor of 3. This format is the only truly portable floppy format.

NAME

disktune - tune floppy disk settling time parameters

SYNOPSIS

disktune [-srt #] [-hlt #] [-hut #] device

DESCRIPTION

Disktune tunes floppy disk settling time parameters. These include the motor stepping rate and the rate at which the head loads and unloads. *Disktune* thus enables you to obtain the most efficient operation from your floppy on those systems that support it.

If no settable parameters are given, *disktune* will report the current settings on *device*. *Disktune* retains the current settings on parameters which are not specified.

The raw device, */dev/rflop*, must be specified.

The settable parameters are:

- srt # seek motor stepping rate time in milliseconds
- hlt # head loading time in milliseconds
- hut # head unload time in milliseconds

EXAMPLE

disktune -srt 3 /dev/rfdc0

will set the step rate time on the floppy controller to 3 ms per step.

NAME

errdead — extract error records from dump

SYNOPSIS

/etc/errdead *dumpfile* [*namelist*]

DESCRIPTION

When hardware errors are detected by the system, an error record that contains information pertinent to the error is generated. If the error-logging daemon *errdemon*(1M) is not active or if the system crashes before the record can be placed in the error file, the error information is held by the system in a local buffer. *Errdead* examines a system dump (or memory), extracts such error records, and passes them to *errpt*(1M) for analysis.

The *dumpfile* specifies the file (or memory) that is to be examined. The system *namelist* is specified by *namelist*; if not given, */unix* is used.

FILES

| | |
|---------------------------|------------------------|
| <i>/unix</i> | system <i>namelist</i> |
| <i>/usr/bin/errpt</i> | analysis program |
| <i>/usr/tmp/errXXXXXX</i> | temporary file |

DIAGNOSTICS

Diagnostics may come from either *errdead* or *errpt*. In either case, they are intended to be self-explanatory.

SEE ALSO

errdemon(1M), *errpt*(1M).

NAME

errdemon — error-logging daemon

SYNOPSIS

/usr/lib/errdemon [file]

DESCRIPTION

The error logging daemon *errdemon* collects error records from the operating system by reading the special file */dev/error* and places them in *file*. If *file* is not specified when the daemon is activated, */usr/adm/errfile* is used. Note that *file* is created if it does not exist; otherwise, error records are appended to it, so that no previous error data is lost. No analysis of the error records is done by *errdemon*; that responsibility is left to *errpt*(1M). The error-logging daemon is terminated by sending it a software kill signal (see *signal*(2)). Only the super-user may start the daemon, and only one daemon may be active at any time.

FILES

| | |
|------------------|------------------------------|
| /dev/error | source of error records |
| /usr/adm/errfile | repository for error records |

DIAGNOSTICS

The diagnostics produced by *errdemon* are intended to be self-explanatory.

SEE ALSO

errpt(1M), errstop(1M), kill(1), err(7).

NAME

errpt — process a report of logged errors

SYNOPSIS

errpt [options] [files]

DESCRIPTION

Errpt processes data collected by the error logging mechanism (*errdemon*(1M)) and generates a report of that data. The default report is a summary of all errors posted in the files named. Options apply to all files and are described below. If no files are specified, *errpt* attempts to use */usr/adm/errfile* as *file*.

A summary report notes the options that may limit its completeness, records the time stamped on the earliest and latest errors encountered, and gives the total number of errors of one or more types. Each device summary contains the total number of unrecovered errors, recovered errors, errors unable to be logged, I/O operations on the device, and miscellaneous activities that occurred on the device. The number of times that *errpt* has difficulty reading input data is included as read errors.

Any detailed report contains, in addition to specific error information, all instances of the error logging process being started and stopped, and any time changes (via *date*(1)) that took place during the interval being processed. A summary of each error type included in the report is appended to a detailed report.

A report may be limited to certain records in the following ways:

- s *date* Ignore all records posted earlier than *date*, where *date* has the form *mmddhhmm**yy*, consistent in meaning with the *date*(1) command.
- e *date* Ignore all records posted later than *date*, whose form is as described above.
- a Produce a detailed report that includes all error types.
- d *devlist* A detailed report is limited to data about devices given in *devlist*, where *devlist* can be one of two forms: a list of device identifiers separated from one another by a comma, or a list of device identifiers enclosed in double quotes and separated from one another by a comma and/or more spaces. *Errpt* is familiar with the common form of identifiers (see Section 7 of this volume). The devices for which errors are logged are system dependent. Additional identifiers are *int* and *mem* which include detailed reports of stray-interrupt and memory-parity type errors respectively.
- p *n* Limit the size of a detailed report to *n* pages.
- f In a detailed report, limit the reporting of block device errors to unrecovered errors.

FILES

/usr/adm/errfile default error file

SEE ALSO

errdemon(1M), *errfile*(4).

NAME

errstop — terminate the error-logging daemon

SYNOPSIS

/etc/errstop [namelist]

DESCRIPTION

The error-logging daemon *errdemon*(1M) is terminated by using *errstop*. This is accomplished by executing *ps*(1) to determine the daemon's identity and then sending it a software kill signal (see *signal*(2)); */unix* is used as the system namelist if none is specified. Only the super-user may use *errstop*.

FILES

/unix default system namelist

DIAGNOSTICS

The diagnostics produced by *errstop* are intended to be self-explanatory.

SEE ALSO

errdemon(1M), *ps*(1), *kill*(2).

NAME

ff — list file names and statistics for a file system

SYNOPSIS

/etc/ff [options] special

DESCRIPTION

Ff reads the i-list and directories of the *special* file, assuming it to be a file system, saving i-node data for files which match the selection criteria. Output consists of the path name for each saved i-node, plus any other file information requested using the print *options* below. Output fields are positional. The output is produced in i-node order; fields are separated by tabs. The default line produced by *ff* is:

path-name i-number

With all *options* enabled, output fields would be:

path-name i-number size uid

The argument *n* in the *option* descriptions that follow is used as a decimal integer (optionally signed), where *+n* means more than *n*, *-n* means less than *n*, and *n* means exactly *n*. A day is defined as a 24 hour period.

- I** Do not print the i-node number after each path name.
- l** Generate a supplementary list of all path names for multiply linked files.
- p prefix** The specified *prefix* will be added to each generated path name. The default is ..
- s** Print the file size, in bytes, after each path name.
- u** Print the owner's login name after each path name.
- a n** Select if the i-node has been accessed in *n* days.
- m n** Select if the i-node has been modified in *n* days.
- c n** Select if the i-node has been changed in *n* days.
- n file** Select if the i-node has been modified more recently than the argument *file*.
- i i-node-list** Generate names for only those i-nodes specified in *i-node-list*.

EXAMPLE

ff -l /dev/diskroot

generates a list of the names of all files on a specified file system.

ff -m -l /dev/diskusr > /log/incbackup/usr/tuesday

produces an index of files and i-numbers which are on a file system and have been modified in the last 24 hours.

ff -i 451,76 /dev/rrp7

obtains the path names for i-nodes 451 and 76 on a specified file system.

SEE ALSO

finc(1M), find(1), frec(1M), ncheck(1M).

BUGS

Only a single path name out of any possible ones will be generated for a multiply linked i-node, unless the **-l** option is specified. When **-l** is

specified, no selection criteria apply to the names generated. All possible names for every linked file on the file system will be included in the output. On very large file systems, memory may run out before *ff* does.

NAME

filesave, tapesave — daily/weekly UNIX file system backup

SYNOPSIS

/etc/filesave.?
/etc/tapesave

DESCRIPTION

These shell scripts are provided as models. They are designed to provide a simple, interactive operator environment for file backup. *Filesave.?* is for daily disk-to-disk backup and *tapesave* is for weekly disk-to-tape.

The suffix *.?* can be used to name another system where two (or more) machines share disk drives (or tape drives) and one or the other of the systems is used to perform backup on both.

SEE ALSO

shutdown(1M), volcopy(1M).

/

NAME

finc — fast incremental backup

SYNOPSIS

finc [*selection-criteria*] *file-system* *raw-tape*

DESCRIPTION

Finc selectively copies the input *file-system* to the output *raw-tape*. The cautious will want to mount the input *file-system* read-only to insure an accurate backup, although acceptable results can be obtained in read-write mode. The tape must be previously labelled by *labelit* (see *volcopy*(1M)). The selection is controlled by the *selection-criteria*, accepting only those inodes/files for whom the conditions are true.

It is recommended that production of a *finc* tape be preceded by the *ff* command, and the output of *ff* be saved as an index of the tape's contents. Files on a *finc* tape may be recovered with the *frec* command.

The argument *n* in the *selection-criteria* which follow is used as a decimal integer (optionally signed), where *+ n* means more than *n*, *- n* means less than *n*, and *n* means exactly *n*. A day is defined as a 24 hours.

-a n True if the file has been accessed in *n* days.

-m n True if the file has been modified in *n* days.

-c n True if the i-node has been changed in *n* days.

-n file True for any file which has been modified more recently than the argument *file*.

EXAMPLE

finc -m -2 /dev/rdiskur /dev/rtp0

writes a tape consisting of all files from *file-system* */usr* modified in the last 48 hours.

SEE ALSO

cpio(1), *ff*(1M), *frec*(1M), *volcopy*(1M).

NAME

freq — recover files from a backup tape

SYNOPSIS

/etc/freq [*-p path*] [*-f reqfile*] *raw-tape i-number:name ...*

DESCRIPTION

Frec recovers files from the specified *raw-tape* backup tape written by *volcopy*(1M) or *finc*(1M), given their *i-numbers*. The data for each recovery request will be written into the file given by *name*.

The *-p path* option allows you to specify a default prefixing *path* different from your current working directory. This will be prefixed to any *names* that are not fully qualified, i.e. that do not begin with */* or *./*. If any directories are missing in the paths of recovery *names* they will be created.

-p path Specifies a prefixing *path* to be used to fully qualify any names that do not start with */* or *./*.

-f reqfile Specifies a file which contains recovery requests. The format is *i-number:newname*, one per line.

EXAMPLE

```
freq /dev/rmt0 1216:junk
```

recovers a file, *i-number* 1216 when backed-up, into a file named *junk* in your current working directory.

```
freq -p /usr/src/cmd /dev/rmt0 14156:a 1232:b
3141:/usr/joe/a.c
```

recovers files with *i-numbers* 14156, 1232, and 3141 into files */usr/src/cmd/a*, */usr/src/cmd/b* and */usr/joe/a.c*.

SEE ALSO

cpio(1), *ff*(1M), *finc*(1M), *volcopy*(1M).

BUGS

While paving a path (i.e. creating the intermediate directories contained in a pathname) *freq* can only recover inode fields for those directories contained on the tape and requested for recovery.

NAME

fsck, *dfscck* — file system consistency check and interactive repair

SYNOPSIS

/etc/fsck [-y] [-n] [-sX] [-SX] [-t file] [-q] [-D] [-f] [file-systems]

/etc/dfscck [options1] filesystem ... - [options2] filesystem ...

DESCRIPTION**Fsck**

Fsck audits and interactively repairs inconsistent conditions for UNIX System files. If the file system is consistent then the number of files, number of blocks used, and number of blocks free are reported. If the file system is inconsistent the operator is prompted for concurrence before each correction is attempted. It should be noted that most corrective actions will result in some loss of data. The amount and severity of data lost may be determined from the diagnostic output. The default action for each consistency correction is to wait for the operator to respond yes or no. If the operator does not have write permission *fsck* will default to a -n action.

Fsck has more consistency checks than its predecessors *check*, *dcheck*, *fcheck*, and *icheck* combined.

The following options are interpreted by *fsck*.

- y Assume a yes response to all questions asked by *fsck*.
- n Assume a no response to all questions asked by *fsck*; do not open the file system for writing.
- sX Ignore the actual free list and (unconditionally) reconstruct a new one by rewriting the super-block of the file system. The file system should be unmounted while this is done; if this is not possible, care should be taken that the system is quiescent and that it is rebooted immediately afterwards. This precaution is necessary so that the old, bad, in-core copy of the superblock will not continue to be used, or written on the file system.

The -sX option allows for creating an optimal free-list organization. The following forms of *X* are supported for the following devices:

- s3 (RP03)
- s4 (RP04, RP05, RP06)
- sBlocks-per-cylinder:Blocks-to-skip (for anything else)

If *X* is not given, the values used when the file system was created are used. If these values were not specified, then the value 400:7 is used.

- SX Conditionally reconstruct the free list. This option is like -sX above except that the free list is rebuilt only if there were no discrepancies discovered in the file system. Using -S will force a no response to all questions asked by *fsck*. This option is useful for forcing free list reorganization on uncontaminated file systems.
- t If *fsck* cannot obtain enough memory to keep its tables, it uses a scratch file. If the -t option is specified, the file named in the next argument is used as the scratch file, if needed. Without the -t flag, *fsck* will prompt the operator for the name of the scratch file. The

file chosen should not be on the file system being checked, and if it is not a special file or did not already exist, it is removed when *fsck* completes.

- q Quiet *fsck*. Do not print size-check messages in Phase 1. Unreferenced fifos will silently be removed. If *fsck* requires it, counts in the superblock will be automatically fixed and the free list salvaged.
- D Directories are checked for bad blocks. Useful after system crashes.
- f Fast check. Check block and sizes (Phase 1) and check the free list (Phase 5). The free list will be reconstructed (Phase 6) if it is necessary.

If no *file-systems* are specified, *fsck* will read a list of default file systems from the file */etc/checklist*.

Inconsistencies checked are as follows:

1. Blocks claimed by more than one inode or the free list.
2. Blocks claimed by an inode or the free list outside the range of the file system.
3. Incorrect link counts.
4. Size checks:
 - Incorrect number of blocks.
 - Directory size not 16-byte aligned.
5. Bad inode format.
6. Blocks not accounted for anywhere.
7. Directory checks:
 - File pointing to unallocated inode.
 - Inode number out of range.
8. Super Block checks:
 - More than 65536 inodes.
 - More blocks for inodes than there are in the file system.
9. Bad free block list format.
10. Total free block and/or free inode count incorrect.

Orphaned files and directories (allocated but unreferenced) are, with the operator's concurrence, reconnected by placing them in the *lost+found* directory, if the files are nonempty. The user will be notified if the file or directory is empty or not. If it is empty, *fsck* will silently remove them. *Fsck* will force the reconnection of nonempty directories. The name assigned is the inode number. The only restriction is that the directory *lost+found* must preexist in the root of the file system being checked and must have empty slots in which entries can be made. This is accomplished by making *lost+found*, copying a number of files to the directory, and then removing them (before *fsck* is executed).

Checking the raw device is almost always faster and should be used with everything but the *root* file system.

Dfsck

Dfsck allows two file system checks on two different drives simultaneously. *options1* and *options2* are used to pass options to *fsck* for the two sets of file systems. A *-* is the separator between the file system groups.

The *d/fsck* program permits an operator to interact with two *fsck*(1M) programs at once. To aid in this, *d/fsck* will print the file system name for each message to the operator. When answering a question from *d/fsck*, the operator must prefix the response with a 1 or a 2 (indicating that the

answer refers to the first or second file system group).

Do not use *d/fsck* to check the *root* file system.

EXAMPLE

```
fsck /dev/rdisk0
```

checks the consistency of device *rdisk0*.

FILES

/etc/checklist contains default list of file systems to check.

SEE ALSO

clri(1M), *ncheck*(1M), *checklist*(4), *fs*(4), *crash*(8).
"Setting up the UNIX System"

BUGS

Inode numbers for *.* and *..* in each directory should be checked for validity.

DIAGNOSTICS

The diagnostics produced by *fsck* are intended to be self-explanatory.

NAME

fsdb — file system debugger

SYNOPSIS

/etc/fsdb special [-]

DESCRIPTION

Fsdb can be used to patch up a damaged file system after a crash. It has conversions to translate block and i-numbers into their corresponding disk addresses. Also included are mnemonic offsets to access different parts of an i-node. These greatly simplify the process of correcting control block entries or descending the file system tree.

Fsdb contains several error checking routines to verify i-node and block addresses. These can be disabled if necessary by invoking *fsdb* with the optional - argument or by the use of the O symbol. (*Fsdb* reads the i-size and f-size entries from the superblock of the file system as the basis for these checks.)

Numbers are considered decimal by default. Octal numbers must be prefixed with a zero. During any assignment operation, numbers are checked for a possible truncation error due to a size mismatch between source and destination.

Fsdb reads a block at a time and will therefore work with raw as well as block I/O. A buffer management routine is used to retain commonly used blocks of data in order to reduce the number of read system calls. All assignment operations result in an immediate write-through of the corresponding block.

The symbols recognized by *fsdb* are:

| | |
|------|---|
| # | absolute address |
| i | convert from i-number to i-node address |
| b | convert to block address |
| d | directory slot offset |
| +, - | address arithmetic |
| q | quit |
| >, < | save, restore an address |
| = | numerical assignment |
| = + | incremental assignment |
| = - | decremental assignment |
| = " | character string assignment |
| O | error checking flip flop |
| p | general print facilities |
| f | file print facility |
| B | byte mode |
| W | word mode |
| D | double word mode |
| ! | escape to shell |

The print facilities generate a formatted output in various styles. The current address is normalized to an appropriate boundary before printing begins. It advances with the printing and is left at the address of the last item printed. The output can be terminated at any time by typing the delete character. If a number follows the p symbol, that many entries are printed. A check is made to detect block boundary overflows since logically sequential blocks are generally not physically sequential. If a count of zero

is used, all entries to the end of the current block are printed. The print options available are:

| | |
|----------|------------------------|
| l | print as i-nodes |
| d | print as directories |
| o | print as octal words |
| e | print as decimal words |
| c | print as characters |
| b | print as octal bytes |

The **f** symbol is used to print data blocks associated with the current i-node. If followed by a number, that block of the file is printed. (Blocks are numbered from zero.) The desired print option letter follows the block number, if present, or the **f** symbol. This print facility works for small as well as large files. It checks for special devices and that the block pointers used to find the data are not zero.

Dots, tabs and spaces may be used as function delimiters but are not necessary. A line with just a new-line character will increment the current address by the size of the data type last printed. That is, the address is set to the next byte, word, double word, directory entry or i-node, allowing the user to step through a region of a file system. Information is printed in a format appropriate to the data type. Bytes, words and double words are displayed with the octal address followed by the value in octal and decimal. A **.B** or **.D** is appended to the address for byte and double word values, respectively. Directories are printed as a directory slot offset followed by the decimal i-number and the character representation of the entry name. Inodes are printed with labeled fields describing each element.

The following mnemonics are used for i-node examination and refer to the current working i-node:

| | |
|------------|-----------------------------|
| md | mode |
| ln | link count |
| uid | user ID number |
| gid | group ID number |
| sz | file size |
| a# | data block numbers (0 - 12) |
| at | access time |
| mt | modification time |
| maj | major device number |
| min | minor device number |

EXAMPLE

386i prints i-number 386 in an i-node format. This now becomes the current working i-node.

ln=4 changes the link count for the working i-node to 4.

ln+=1 increments the link count by 1.

fc prints, in ASCII, block zero of the file associated with the working i-node.

2i.fd prints the first 32 directory entries for the root i-node of this file system.

d5i.fc changes the current i-node to that associated with the 5th directory entry (numbered from zero) found from the above command. The first logical block of the file is then printed in ASCII.

512B.p0o

prints the superblock of this file system in octal.

2i.a0b.d7=3

changes the i-number for the seventh directory slot in the root directory to 3. This example also shows how several operations can be combined on one command line.

d7.nm="name"

changes the name field in the directory slot to the given string. Quotes are optional when used with **nm** if the first character is alphabetic.

a2b.p0d

prints the third block of the current inode as directory entries.

SEE ALSO

fsck(1M), **dir(4)**, **fs(4)**.

NAME

fuser — identify processes using a file or file structure

SYNOPSIS

/etc/fuser [-ku] files [-] [[-ku] files]

DESCRIPTION

Fuser lists the process IDs of the processes using the *files* specified as arguments. For block special devices, all processes using any file on that device are listed. The process ID is followed by *c*, *p* or *r* if the process is using the file as its current directory, the parent of its current directory (only when in use by the system), or its root directory, respectively. If the *-u* option is specified, the login name, in parentheses, also follows the process ID. In addition, if the *-k* option is specified, the **SIGKILL** signal is sent to each process. Only the super-user can terminate another user's process (see *kill(2)*). Options may be respecified between groups of files. The new set of options replaces the old set, with a lone dash canceling any options currently in force.

The process IDs are printed as a single line on the standard output, separated by spaces and terminated with a single new line. All other output is written on standard error.

EXAMPLE

fuser -ku /dev/dsk1?

will terminate all processes that are preventing disk drive one from being unmounted if typed by the super-user, listing the process ID and login name of each as it is killed.

fuser -u /etc/passwd

will list process IDs and login names of processes that have the password file open.

fuser -ku /dev/dsk1? -u /etc/passwd

will do both of the above examples in a single command line.

Note that the device names for disks are system dependent.

FILES

| | |
|-----------|-----------------------|
| /unix | for namelist |
| /dev/kmem | for system image |
| /dev/mem | also for system image |

SEE ALSO

mount(1M), ps(1), kill(2), signal(2).

NAME

fwtmp, wtmpfix — manipulate connect accounting records

SYNOPSIS

```
/usr/lib/acct/fwtmp [-ic]
/usr/lib/acct/wtmpfix [files]
```

DESCRIPTION**Fwtmp**

Fwtmp reads from the standard input and writes to the standard output, converting binary records of the type found in **wtmp** to formatted ASCII records. The ASCII version is useful to enable editing, via *ed(1)*, bad records or general purpose maintenance of the file.

The argument **-ic** is used to denote that input is in ASCII form, and output is to be written in binary form.

Wtmpfix

Wtmpfix examines the standard input or named files in **wtmp** format, corrects the time/date stamps to make the entries consistent, and writes to the standard output. A **-** can be used in place of *files* to indicate the standard input. If time/date corrections are not performed, *acctcon1* will fault when it encounters certain date change records.

Each time the date is set, a pair of date change records are written to */etc/wtmp*. The first record is the old date denoted by the string **old time** placed in the line field and the flag **OLD_TIME** placed in the type field of the **<utmp.h>** structure. The second record specifies the new date and is denoted by the string **new time** placed in the line field and the flag **NEW_TIME** placed in the type field. *Wtmpfix* uses these records to synchronize all time stamps in the file.

In addition to correcting time/date stamps, *wtmpfix* will check the validity of the name field to ensure that it consists solely of alphanumeric characters, a **\$** or spaces. If it encounters a name that is considered invalid, it will change the login name to **INVALID** and write a diagnostic to the standard error. In this way, *wtmpfix* reduces the chance that *acctcon1* will fail when processing connect accounting records.

FILES

```
/etc/wtmp
/usr/include/utmp.h
```

SEE ALSO

acct(1M), *acctems(1M)*, *acctcom(1)*, *acctcon(1M)*, *acctmerge(1M)*, *acctprc(1M)*, *acctsh(1M)*, *runacct(1M)*, *acct(2)*, *acct(4)*, *utmp(4)*.

NAME

getty — set terminal type, modes, speed, and line discipline

SYNOPSIS

```
/etc/getty [ -h ] [ -t timeout ] line [ speed [ type [ linedisc ] ] ]
/etc/getty -c file
```

DESCRIPTION

Getty is a program that is invoked by *init*(1M). It is the second process in the series, (*init-getty-login-shell*) that ultimately connects a user with the UNIX System. Initially *getty* prints the login message field for the entry it is using from */etc/gettydefs*. *Getty* reads the user's login name and invokes the *login*(1) command with the user's name as argument. While reading the name, *getty* attempts to adapt the system to the speed and type of terminal being used.

Line is the name of a tty line in */dev* to which *getty* is to attach itself. *Getty* uses this string as the name of a file in the */dev* directory to open for reading and writing. Unless *getty* is invoked with the *-h* flag, *getty* will force a hangup on the line by setting the speed to zero before setting the speed to the default or specified speed. The *-t* flag plus *timeout* in seconds, specifies that *getty* should exit if the open on the line succeeds and no one types anything in the specified number of seconds. The optional second argument, *speed*, is a label to a speed and tty definition in the file */etc/gettydefs*. This definition tells *getty* what speed to initially run at, what the login message should look like, what the initial tty settings are, and what speed to try next should the user indicate that the speed is inappropriate. (By typing a *<break>* character.) The default *speed* is 300 baud. The optional third argument, *type*, is a character string describing to *getty* what type of terminal is connected to the line in question. *Getty* understands the following types:

| | |
|--------------|----------------------|
| none | default |
| vt61 | DEC vt61 |
| vt100 | DEC vt100 |
| hp45 | Hewlett-Packard HP45 |
| c100 | Concept 100 |

The default terminal is *none*; i.e., any crt or normal terminal unknown to the system. Also, for terminal type to have any meaning, the virtual terminal handlers must be compiled into the operating system. They are available, but not compiled in the default condition. The optional fourth argument, *linedisc*, is a character string describing which line discipline to use in communicating with the terminal. Again the hooks for line disciplines are available in the operating system but there is only one presently available, the default line discipline, LDISC0.

When given no optional arguments, *getty* sets the *speed* of the interface to 300 baud, specifies that raw mode is to be used (awaken on every character), that echo is to be suppressed, either parity allowed, newline characters will be converted to carriage return-line feed, and tab expansion performed on the standard output. It types the login message before reading the user's name a character at a time. If a null character (or framing error) is received, it is assumed to be the result of the user pushing the "break" key. This will cause *getty* to attempt the next *speed* in the series. The series that *getty* tries is determined by what it finds in */etc/gettydefs*.

The user's name is terminated by a new-line or carriage-return character. The latter results in the system being set to treat carriage returns appropriately (see *ioctl(2)*).

The user's name is scanned to see if it contains any lower-case alphabetic characters; if not, and if the name is non-empty, the system is told to map any future upper-case characters into the corresponding lower-case characters.

Finally, *login* is called with the user's name as an argument. Additional arguments may be typed after the login name. These are passed to *login*, which will place them in the environment (see *login(1)*).

A check option is provided. When *getty* is invoked with the *-c* option and *file*, it scans the file as if it were scanning */etc/gettydefs* and prints out the results to the standard output. If there are any unrecognized modes or improperly constructed entries, it reports these. If the entries are correct, it prints out the values of the various flags. See *ioctl(2)* to interpret the values. Note that some values are added to the flags automatically.

FILES

/etc/gettydefs

SEE ALSO

ct(1C), *init(1M)*, *login(1)*, *ioctl(2)*, *gettydefs(4)*, *inittab(4)*, *tty(7)*.

NAME

init, *telinit* — process control initialization

SYNOPSIS

/etc/init [0123456SsQq]

/etc/telinit [0123456sSQqabc]

DESCRIPTION

Init

Init is a general process spawner. Its primary role is to create processes from a script stored in the file */etc/inittab* (see *inittab(4)*). This file usually has *init* spawn *getty*'s on each line that a user may log in on. It also controls autonomous processes required by any particular system.

Init considers the system to be in a *run-level* at any given time. A *run-level* can be viewed as a software configuration of the system where each configuration allows only a selected group of processes to exist. The processes spawned by *init* for each of these *run-levels* is defined in the *inittab* file. *Init* can be in one of eight *run-levels*, 0–6 and S or s. The *run-level* is changed by having a privileged user run */etc/init* (which is linked to */etc/telinit*). This user spawned *init* sends appropriate signals to the original *init* spawned by the operating system when the system was rebooted, telling it which *run-level* to change to.

Init is invoked inside the UNIX System as the last step in the boot procedure. The first thing *init* does is to look for */etc/inittab* and see if there is an entry of the type *initdefault* (see *inittab(4)*). If there is, *init* uses the *run-level* specified in that entry as the initial *run-level* to enter. If this entry is not in *inittab* or *inittab* is not found, *init* requests that the user enter a *run-level* from the virtual system console, */dev/syscon*. If an S (s) is entered, *init* goes into the *SINGLE USER* level. This is the only *run-level* that doesn't require the existence of a properly formatted *inittab* file. If */etc/inittab* doesn't exist, then by default the only legal *run-level* that *init* can enter is the *SINGLE USER* level. In the *SINGLE USER* level the virtual console terminal */dev/syscon* is opened for reading and writing and the command */bin/su* is invoked immediately. To exit from the *SINGLE USER run-level* one of two options can be elected. First, if the shell is terminated (via an end-of-file), *init* will reprompt for a new *run-level*. Second, the *init* or *telinit* command can signal *init* and force it to change the *run-level* of the system.

When attempting to boot the system, failure of *init* to prompt for a new *run-level* may be due to the fact that the device */dev/syscon* is linked to a device other than the physical system teletype (*/dev/systty*). If this occurs, *init* can be forced to relink */dev/syscon* by typing a delete on the system teletype which is co-located with the processor.

When *init* prompts for the new *run-level*, the operator may only enter one of the digits 0 through 6 or the letters S or s. If S is entered *init* operates as previously described in *SINGLE USER* mode with the additional result that */dev/syscon* is linked to the user's terminal line, thus making it the virtual system console. A message is generated on the physical console, */dev/systty*, saying where the virtual terminal has been relocated.

When *init* comes up initially and whenever it switches out of *SINGLE USER* state to normal run states, it sets the *ioctl(2)* states of the virtual console, */dev/syscon*, to those modes saved in the file */etc/ioctl.syscon*. This file is

written by *init* whenever *SINGLE USER* mode is entered. If this file doesn't exist when *init* wants to read it, a warning is printed and default settings are assumed.

If a 0 through 6 is entered *init* enters the corresponding *run-level*. Any other input will be rejected and the user will be re-prompted. If this is the first time *init* has entered a *run-level* other than *SINGLE USER*, *init* first scans *inittab* for special entries of the type *boot* and *bootwait*. These entries are performed, providing the *run-level* entered matches that of the entry before any normal processing of *inittab* takes place. In this way any special initialization of the operating system, such as mounting file systems, can take place before users are allowed onto the system. The *inittab* file is scanned to find all entries that are to be processed for that *run-level*.

Run-level 2 is usually defined by the user to contain all of the terminal processes and daemons that are spawned in the multi-user environment.

In a multi-user environment, the *inittab* file is usually set up so that *init* will create a process for each terminal on the system.

For terminal processes, ultimately the shell will terminate because of an end-of-file either typed explicitly or generated as the result of hanging up. When *init* receives a child death signal, telling it that a process it spawned has died, it records the fact and the reason it died in */etc/utmp* and */etc/wtmp* if it exists (see *who(1)*). A history of the processes spawned is kept in */etc/wtmp* if such a file exists.

To spawn each process in the *inittab* file, *init* reads each entry and for each entry which should be respawned, it forks a child process. After it has spawned all of the processes specified by the *inittab* file, *init* waits for one of its descendant processes to die, a powerfail signal, or until *init* is signaled by *init* or *telinit* to change the system's *run-level*. When one of the above three conditions occurs, *init* re-examines the *inittab* file. New entries can be added to the *inittab* file at any time; however, *init* still waits for one of the above three conditions to occur. To provide for an instantaneous response the *init Q* or *initl q* command can wake *init* to re-examine the *inittab* file.

If *init* receives a *powerfail* signal (*SIGPWR*) and is not in *SINGLE USER* mode, it scans *inittab* for special powerfail entries. These entries are invoked (if the *run-levels* permit) before any further processing takes place. In this way *init* can perform various cleanup and recording functions whenever the operating system experiences a power failure. It is important to note that the powerfail entries should not use devices that must first be initialized (e.g. *dzb* lines) after a power failure has occurred.

When *init* is requested to change *run-levels* (via *telinit*), *init* sends the warning signal (*SIGTERM*) to all processes that are undefined in the target *run-level*. *Init* waits 20 seconds before forcibly terminating these processes via the kill signal (*SIGKILL*).

Telinit

Telinit, which is linked to */etc/init*, is used to direct the actions of *init*. It takes a one character argument and signals *init* via the kill system call to perform the appropriate action. The following arguments serve as directives to *init*.

0-6 tells *init* to place the system in one of the *run-levels* 0-6.

a,b,c

tells *init* to process only those */etc/inittab* file entries having the a, b or c *run-level* set.

Q,q

tells *init* to re-examine the */etc/inittab* file.

s,S

tells *init* to enter the single user environment. When this level change is effected, the virtual system teletype, */dev/syscon*, is changed to the terminal from which the command was executed.

Telinit can only be run by someone who is super-user or a member of group *sys*.

FILES

/etc/inittab
/etc/utmp
/etc/wtmp
/etc/ioctl.syscon
/dev/syscon
/dev/systty

SEE ALSO

getty(1M), *login(1)*, *sh(1)*, *who(1)*, *kill(2)*, *inittab(4)*, *utmp(4)*.

DIAGNOSTICS

If *init* finds that it is continuously respawning an entry from */etc/inittab* more than 10 times in 2 minutes, it will assume that there is an error in the command string, and generate an error message on the system console, and refuse to respawn this entry until either 5 minutes has elapsed or it receives a signal from a user *init* (*telinit*). This prevents *init* from eating up system resources when someone makes a typographical error in the *inittab* file or a program is removed that is referenced in the *inittab*.

NAME

install — install commands

SYNOPSIS

```
/etc/Install [-c dira] [-f dirb] [-i] [-n dirc] [-o] [-s] file [dirx ...]
```

DESCRIPTION

Install is a command most commonly used in "makefiles" (see *make(1)*) to install a *file* (updated target file) in a specific place within a file system. Each *file* is installed by copying it into the appropriate directory, thereby retaining the mode and owner of the original command. The program prints messages telling the user exactly what files it is replacing or creating and where they are going.

If no options or directories (*dirx ...*) are given, *install* will search a set of default directories (*/bin*, */usr/bin*, */etc*, */lib*, and */usr/lib*, in that order) for a file with the same name as *file*. When the first occurrence is found, *install* issues a message saying that it is overwriting that file with *file*, and proceeds to do so. If the file is not found, the program states this and exits without further action.

If one or more directories (*dirx ...*) are specified after *file*, those directories will be searched before the directories specified in the default list.

The meanings of the options are:

- c *dira*** Installs a new command (*file*) in the directory specified by *dira*, only if it is not found. If it is found, *install* issues a message saying that the file already exists, and exits without overwriting it. May be used alone or with the **-s** option.
- f *dirb*** Forces *file* to be installed in given directory, whether or not one already exists. If the file being installed does not already exist, the mode and owner of the new file will be set to 755 and *bin*, respectively. If the file already exists, the mode and owner will be that of the already existing file. May be used alone or with the **-o** or **-s** options.
- i** ignores default directory list, searching only through the given directories (*dirx ...*). May be used alone or with any other options other than **-c** and **-f**.
- n *dirc*** If *file* is not found in any of the searched directories, it is put in the directory specified in *dirc*. The mode and owner of the new file will be set to 755 and *bin*, respectively. May be used alone or with any other options other than **-c** and **-f**.
- o** If *file* is found, this option saves the "found" file by copying it to *OLDfile* in the directory in which it was found. This option is useful when installing a normally text busy file such as */bin/sh* or */etc/getty*, where the existing file cannot be removed. May be used alone or with any other options other than **-c**.
- s** Suppresses printing of messages other than error messages. May be used alone or with any other options.

SEE ALSO

make(1).

NAME

killall — kill all active processes

SYNOPSIS

/etc/killall [signal]

DESCRIPTION

Killall is a procedure used by /etc/shutdown to kill all active processes not directly related to the shut down procedure.

Killall is chiefly used to terminate all processes with open files so that the mounted file systems will be unbusied and can be unmounted.

Killall sends *signal* (see *kill(1)*) to all remaining processes not belonging to the above group of exclusions. If no *signal* is specified, a default of 9 is used.

FILES

/etc/shutdown

SEE ALSO

fuser(1M), kill(1), ps(1), shutdown(1M), signal(2).

NAME

link, unlink — exercise link and unlink system calls

SYNOPSIS

/etc/link file1 file2
/etc/unlink file

DESCRIPTION

Link and *unlink* perform their respective system calls on their arguments, abandoning all error checking. These commands may only be executed by the super-user, who (it is hoped) knows what he or she is doing.

EXAMPLE

link file1 file2

creates a directory entry for "file2" with the same inode number as "file1".
NOTE: *link* should be used with extreme caution.

SEE ALSO

rm(1), link(2), unlink(2).

NAME

lpadmin — configure the LP spooling system

SYNOPSIS

```
/usr/lib/lpadmin -p printer [options]
/usr/lib/lpadmin -x dest
/usr/lib/lpadmin -d[dest]
```

DESCRIPTION

Lpadmin configures LP spooling systems to describe printers, classes and devices. It is used to add and remove destinations, change membership in classes, change devices for printers, change printer interface programs and to change the system default destination. *Lpadmin* may not be used when the LP scheduler, *lpsched*(1M), is running, except where noted below.

Exactly one of the *-p*, *-d* or *-x* options must be present for every legal invocation of *lpadmin*.

- d[dest]* makes *dest*, an existing destination, the new system default destination. If *dest* is not supplied, then there is no system default destination. This option may be used when *lpsched*(1M) is running. No other *options* are allowed with *-d*.
- xdest* removes destination *dest* from the LP system. If *dest* is a printer and is the only member of a class, then the class will be deleted, too. No other *options* are allowed with *-x*.
- pprinter* names a *printer* to which all of the *options* below refer. If *printer* does not exist then it will be created.

The following *options* are only useful with *-p* and may appear in any order. For ease of discussion, the printer will be referred to as *P* below.

- cclass* inserts printer *P* into the specified *class*. *Class* will be created if it does not already exist.
- eprinter* copies an existing *printer's* interface program to be the new interface program for *P*.
- h* indicates that the device associated with *P* is hardwired. This *option* is assumed when creating a new printer unless the *-l* *option* is supplied.
- linterface* establishes a new interface program for *P*. *Interface* is the path name of the new program.
- l* indicates that the device associated with *P* is a login terminal. The LP scheduler, *lpsched*, disables all login terminals automatically each time it is started. Before re-enabling *P*, its current *device* should be established using *lpadmin*.
- mmodel* selects a model interface program for *P*. *Model* is one of the model interface names supplied with the LP software (see *Models* below).
- rclass* removes printer *P* from the specified *class*. If *P* is the last member of the *class*, then the *class* will be removed.
- vdevice* associates a new *device* with printer *P*. *Device* is the path-name of a file that is writable by the LP administrator, *lp*. Note that there is nothing to stop an administrator from

associating the same *device* with more than one *printer*. If only the **-p** and **-v** options are supplied, then *lpadmin* may be used while the scheduler is running.

Restrictions.

When creating a new printer, the **-v** option and one of the **-e**, **-i** or **-m** options must be supplied. Only one of the **-e**, **-i** or **-m** options may be supplied. The **-h** and **-l** keyletters are mutually exclusive. Printer and class names may be no longer than 14 characters and must consist entirely of the characters A-Z, a-z, 0-9 and **_** (underscore).

Models.

Model printer interface programs are supplied with the LP software. They are shell procedures which interface between *lpsched* and devices. All models reside in the directory */usr/spool/lp/model* and may be used as is with *lpadmin -m*. Alternatively, LP administrators may modify copies of models and then use *lpadmin -i* to associate them with printers. The following list describes the *models* and lists the options which they may be given on the *lp* command line using the **-o** keyletter:

- dumb** interface for a line printer without special functions and protocol. Form feeds are assumed. This is a good model to copy and modify for printers which do not have models.
- 1640** Diablo 1640 terminal running at 1200 baud, using XON/XOFF protocol. Options:
 - 12** 12-pitch (10-pitch is the default)
 - f** don't use the *450(1)* filter. The output has been pre-processed by either *450(1)* or the *nroff* 450 driving table.
- hp** Hewlett Packard 2631A line printer at 2400 baud. Options:
 - c** compressed print
 - e** expanded print
- prx** Printronix P300 printer using XON/XOFF protocol at 1200 baud.

EXAMPLE

1. Assuming there is an existing Hewlett Packard 2631A line printer named *hp2*, it will use the **hp** model interface after the command:


```
/usr/lib/lpadmin -php2 -mhp
```
2. To obtain compressed print on *hp2*, use the command:


```
lp -dhp2 -o-c files
```
3. A Diablo 1640 printer called *stl* can be added to the LP configuration with the command:


```
/usr/lib/lpadmin -pstl -v/dev/tty20 -m1640
```
4. An *nroff* document may be printed on *stl* in any of the following ways:


```
nroff -T450 files | lp -dstl -of
nroff -T450-12 files | lp -dstl -of
nroff -T37 files | col | lp -dstl
```
5. The following command prints the password file on *stl* in 12-pitch:


```
lp -dstl -o12 /etc/passwd
```

NOTE: the **-12** option to the **1640** model should never be used in conjunction with *nroff*.

FILES

*/usr/spool/lp/**

SEE ALSO

450(1), *accept(1M)*, *enable(1)*, *lp(1)*, *lpsched(1M)*, *lpstat(1)*.

NAME

lpsched, *lpshut*, *lpmove* — start/stop the LP request scheduler and move requests

SYNOPSIS

```
/usr/lib/lpsched
/usr/lib/lpshut
/usr/lib/lpmove requests dest
/usr/lib/lpmove dest1 dest2
```

DESCRIPTION

Lpsched schedules requests taken by *lp(1)* for printing on line printers.

Lpshut shuts down the line printer scheduler. All printers that are printing at the time *lpshut* is invoked will stop printing. Requests that were printing at the time a printer was shut down will be reprinted in their entirety after *lpsched* is started again. All LP commands perform their functions even when *lpsched* is not running.

Lpmove moves requests that were queued by *lp(1)* between LP destinations. This command may be used only when *lpsched* is not running.

The first form of the command moves the named *requests* to the LP destination, *dest*. *Requests* are request ids as returned by *lp*. The second form moves all requests for destination *dest1* to destination *dest2*. As a side effect, *lp* will reject requests for *dest1*.

Note that *lpmove* never checks the acceptance status (see *accept(1M)*) for the new destination when moving requests.

FILES

/usr/spool/lp/*

SEE ALSO

accept(1M), *enable(1)*, *lp(1)*, *lpadmin(1M)*, *lpstat(1)*.

NAME

mkfs — construct a file system

SYNOPSIS

```
/etc/mkfs special blocks[:inodes] [gap blocks/cyl]
/etc/mkfs special proto [gap blocks/cyl]
```

DESCRIPTION

Mkfs constructs a file system by writing on the special file according to the directions found in the remainder of the command line. If the second argument is given as a string of digits, *mkfs* builds a file system with a single empty directory on it. The size of the file system is the value of *blocks* interpreted as a decimal number. This is the number of *physical* disk blocks the file system will occupy. The boot program is left uninitialized. If the optional number of inodes is not given, the default is the number of *logical* blocks divided by 4.

If the second argument is a file name that can be opened, *mkfs* assumes it to be a prototype file *proto*, and will take its directions from that file. The prototype file contains tokens separated by spaces or new-lines. The first token is the name of a file to be copied onto block zero as the bootstrap program. The second token is a number specifying the size of the created file system in *physical* disk blocks. Typically it will be the number of blocks on the device, perhaps diminished by space for swapping. The next token is the number of inodes in the file system. The maximum number of inodes configurable is 65500. The next set of tokens comprise the specification for the root file. File specifications consist of tokens giving the mode, the user ID, the group ID, and the initial contents of the file. The syntax of the contents field depends on the mode.

The mode token for a file is a 6 character string. The first character specifies the type of the file. (The characters *-bcd* specify regular, block special, character special and directory files respectively.) The second character of the type is either *u* or *-* to specify set-user-id mode or not. The third is *g* or *-* for the set-group-id mode. The rest of the mode is a three digit octal number giving the owner, group, and other read, write, execute permissions (see *chmod(1)*).

Two decimal number tokens come after the mode; they specify the user and group ID's of the owner of the file.

If the file is a regular file, the next token is a path name whence the contents and size are copied. If the file is a block or character special file, two decimal number tokens follow which give the major and minor device numbers. If the file is a directory, *mkfs* makes the entries *.* and *..* and then reads a list of names and (recursively) file specifications for the entries in the directory. The scan is terminated with the token *\$*.

A sample prototype specification follows:

```
/stand/diskboot
4872 110
d- -777 3 1
usr    d- -777 3 1
        sh    - - -755 3 1 /bin/sh
        ken   d- -755 6 1
        $
        b0    b- -644 3 1 0 0
```

```

      c0      c--644 3 1 0 0
      $
$

```

In both command syntaxes, the rotational *gap* and the number of *blocks/cyl* can be specified.

The *default* will be used if the supplied *gap* and *blocks/cyl* are considered illegal values or if a short argument count occurs.

EXAMPLE

```
mkfs /dev/fd0 2000 7 50
```

makes a file system in which 2000 is the total size of the file system to be put on */dev/fd0*; 7 is a sector interleave number which is used to stagger the disk blocks for more rapid reading, every 7 blocks, and 50 is a modulo operator that forces the sector interlace number first to allocate all blocks in the first 50 sectors, then the next 50, etc.

NOTE: The proper selection of the *m* and *n* parameters can improve disk efficiency. Disks which have full or partial track buffering should specify a *m* and *n* of 1 and 1; *m* and *n* for other disks must be determined by trial and error as the disk latency is related to rotational latency and cpu speed.

SEE ALSO

dir(4), fs(4), boot(8).

BUGS

If a prototype is used, it is not possible to initialize a file larger than 64K bytes, nor is there a way to specify links.

NAME

mkfs512 — construct a file system

SYNOPSIS

```
mkfs512 special size [ m n ]
mkfs512 special proto
```

DESCRIPTION

Mkfs512 constructs a file system by writing on the special file *special*. In the first form of the command a numeric size is given and *mkfs512* builds a file system with a single empty directory on it. The number of i-nodes is calculated as a function of the filesystem size. *M* is an interleave factor for building the freelist and *n* is a modulo for *m*. See the example for usage.

N.B.: All filesystems should have a *lost+found* directory for *fsck*(1M); this should be created for each file system by running *mklost+found*(1M) in the root directory of a newly created file system, after the file system is first mounted.

In bootstrapping, the second form of *mkfs512* is sometimes used. In this form, the file system is constructed according to the directions found in the prototype file *proto*. The prototype file contains tokens separated by spaces or new lines. The first token is the name of a file to be copied onto sector zero as the bootstrap program. The second token is a number specifying the size of the created file system. Typically it will be the number of blocks on the device, perhaps diminished by space for swapping. The next token is the number of i-nodes in the i-list. The next set of tokens comprise the specification for the root file. File specifications consist of tokens giving the mode, the user ID the group ID, and the initial contents of the file. The syntax of the contents field depends on the mode.

The mode token for a file is a 6 character string. The first character specifies the type of the file. (The characters *-bcd* specify regular, block special, character special and directory files, respectively.) The second character of the type is either *u* or *-* to specify set-user-id mode or not. The third is *g* or *-* for the set-group-id mode. The rest of the mode is a three digit octal number giving the owner, group, and other read, write, execute permissions, see *chmod*(1).

Two decimal number tokens come after the mode; they specify the user and group IDs of the owner of the file.

If the file is a regular file, the next token is a pathname whence the contents and size are copied.

If the file is a block or character special file, two decimal number tokens follow which give the major and minor device numbers.

If the file is a directory, *mkfs512* makes the entries *.* and *..* and then reads a list of names and (recursively) file specifications for the entries in the directory. The scan is terminated with the token *\$*.

A sample prototype specification follows:

```
/usr/mdec/uboot
4872 55
d--777 3 1
usr    d--777 3 1
      sh      --755 3 1 /bin/sh
      ken     d--755 6 1
          $
      b0      b--644 3 1 0 0
      c0      c--644 3 1 0 0
          $
$
```

EXAMPLE

```
mkfs512 /dev/fd0 2000 7 50
```

makes a file system in which 2000 is the total size of the file system to be put on **/dev/fd0**; 7 is a sector interleave number which is used to stagger the disk blocks for more rapid reading, every 7 blocks, and 50 is a modulo operator that forces the sector interlace number first to allocate all blocks in the first 50 sectors, then the next 50, etc.

NOTE: The proper selection of the *m* and *n* parameters can improve disk efficiency. Disks which have full or partial track buffering should specify a *m* and *n* of 1 and 1. *M* and *n* for other disks must be determined by trial and error as the disk latency is related to rotational latency and cpu speed.

SEE ALSO

fsck(1M), mklost+found(1M), dir(4).

BUGS

The default is 3500, which is probably not useful on any disk.
There should be some way to specify links.
There should be some way to specify bad blocks.
Should make *lost+found* automatically.

NAME

mklost+found -- make a lost+found directory for fsck

SYNOPSIS

mklost+found

DESCRIPTION

A directory **lost+found** is created in the current directory and a number of empty files are created therein and then removed so that there will be empty slots for *fsck*(1M). This command should be run immediately after first mounting and changing directory to a newly created file system. For small file systems, it is sufficient (and much faster) to simply make a **lost+found** directory. Up to 30 files can be recovered in it.

EXAMPLE

```
mklost+found
```

in the current directory, creates a directory with empty slots named **lost+found**.

SEE ALSO

fsck(1M), mkfs(1M)

BUGS

Should be done automatically by *mkfs*.

NAME

mknod — build special file

SYNOPSIS

```
/etc/mknod name c | b major minor  
/etc/mknod name p
```

DESCRIPTION

Mknod makes a directory entry and corresponding i-node for a special file. The first argument is the *name* of the entry. In the first case, the second is *b* if the special file is block-type (disks, tape) or *c* if it is character-type (other devices). The last two arguments are numbers specifying the *major* device type and the *minor* device (e.g. unit, drive, or line number), which may be either decimal or octal.

The assignment of major device numbers is specific to each system. They have to be dug out of the system source file **conf.c**.

Mknod can also be used to create fifo's (a.k.a named pipes) (second case in *SYNOPSIS* above).

EXAMPLE

```
mknod /dev/tty4 c 3 4
```

would create file **/dev/tty4** as a character special device with major number 3 and minor number 4.

SEE ALSO

mknod(2).

NAME

mount, umount -- mount and dismount file system

SYNOPSIS

/etc/mount [special directory [-r]]

/etc/umount special

DESCRIPTION

Mount announces to the system that a removable file system is present on the device *special*. The *directory* must exist already; it becomes the name of the root of the newly mounted file system.

These commands maintain a table of mounted devices. If invoked with no arguments, *mount* prints the table.

The optional last argument indicates that the file is to be mounted read-only. Physically write-protected and magnetic tape file systems must be mounted in this way or errors will occur when access times are updated, whether or not any explicit write is attempted.

Umount announces to the system that the removable file system previously mounted on device *special* is to be removed.

FILES

/etc/mnttab mount table

EXAMPLE

mount /dev/xxxx /t

mounts device /dev/xxxx as file system /t.

SEE ALSO

setmnt(1M), mount(2), mnttab(4).

DIAGNOSTICS

Mount issues a warning if the file system to be mounted is currently mounted under another name.

Umount complains if the special file is not mounted or if it is busy. The file system is busy if it contains an open file or some user's working directory.

BUGS

Some degree of validation is done on the file system, however it is generally unwise to mount garbage file systems.

NAME

`mkdir` — move a directory

SYNOPSIS

`/etc/mkdir dirname name`

DESCRIPTION

Mkdir renames directories within a file system. *Dirname* must be a directory; *name* must not exist. Neither name may be a sub-set of the other (*/x/y* cannot be moved to */x/y/z*, nor vice versa).

Only super-user can use *mkdir*.

EXAMPLE

`mkdir dir1 dir2`

renames existing directory "dir1" to be a new directory "dir2".

SEE ALSO

`mkdir(1)`.

NAME

ncheck — generate names from i-numbers

SYNOPSIS

/etc/ncheck [*-i* numbers] [*-a*] [*-s*] [file-system]

DESCRIPTION

N.B.: For most normal file system maintenance, the function of *ncheck* is subsumed by *fsck*(1M).

Ncheck with no argument generates a path name vs. i-number list of all files on a set of default file systems. Names of directory files are followed by */..*. The *-i* option reduces the report to only those files whose i-numbers follow. The *-a* option allows printing of the names *.* and *...*, which are ordinarily suppressed. The *-s* option reduces the report to special files and files with set-user-ID mode; it is intended to discover concealed violations of security policy.

A file system may be specified.

The report is in no useful order, and probably should be sorted.

EXAMPLE

ncheck /dev/rdisk1

will report the pathnames and i-numbers of files on the specified device.

SEE ALSO

fsck(1M), *sort*(1).

DIAGNOSTICS

When the file system structure is improper, *??* denotes the “parent” of a parentless file and a path name beginning with *...* denotes a loop.

NAME

prfld, *prfstat*, *prfdc*, *prfsnap*, *prfpr* — operating system profiler

SYNOPSIS

```
/etc/prfld [ namelist ]
/etc/prfstat [ on | off ]
/etc/prfdc file [ period [ off_hour ] ]
/etc/prfsnap file
/etc/prfpr file [ cutoff [ namelist ] ]
```

DESCRIPTION

Prfld, *prfstat*, *prfdc*, *prfsnap*, and *prfpr* form a system of programs to facilitate an activity study of the UNIX operating system.

Prfld is used to initialize the recording mechanism in the system. It generates a table containing the starting address of each system subroutine as extracted from *namelist*.

Prfstat is used to enable or disable the sampling mechanism. Profiler overhead is less than 1% as calculated for 500 text addresses. *Prfstat* will also reveal the number of text addresses being measured.

Prfdc and *prfsnap* perform the data collection function of the profiler by copying the current value of all the text address counters to a file where the data can be analyzed. *Prfdc* will store the counters into *file* every *period* minutes and will turn off at *off_hour* (valid values for *off_hour* are 0–24). *Prfsnap* collects data at the time of invocation only, appending the counter values to *file*.

Prfpr formats the data collected by *prfdc* or *prfsnap*. Each text address is converted to the nearest text symbol (as found in *namelist*) and is printed if the percent activity for that range is greater than *cutoff*.

FILES

```
/dev/prf  interface to profile data and text addresses
/unix     default for namelist file
```


the file used can be a core image and the address 0.

-f Print the open file table with these headings:
LOC The core location of this table entry.
FLG Miscellaneous state variables encoded thus:
 R open for reading
 W open for writing
 P pipe
CNT Number of processes that know this open file.
INO The location of the inode table entry for this file.
OFFS The file offset, see *lseek(2)*.

FILES

/unix namelist
/dev/mem default source of tables

EXAMPLE

`pstat -i`

displays all the active inodes in a table format with headings.

SEE ALSO

`ps(1)`, `stat(2)`, `fs(5)`
UNIX Implementation, by K. Thompson.

4 being created
5 being terminated
6 stopped under trace
F Miscellaneous state variables, or-ed together:
 01 loaded
 02 the scheduler process
 04 locked
 010 swapped out
 020 traced
 040 used in tracing
 0100

locked in by *lock(2)*.

PRI Scheduling priority, see *nice(2)*.

SIGNAL Signals received (signals 1-16 coded in bits 0-15),

UID Real user ID.

TIM Time resident in seconds; times over 127 coded as 127.

CPU Weighted integral of CPU time, for scheduler.

NI Nice level, see *nice(2)*.

PGRP Process number of root of process group (the opener of the controlling terminal).

PID The process ID number.

PPID The process ID of parent process.

ADDR If in core, the physical address of the "u-area" of the process measured in multiples of 64 bytes. If swapped out, the position in the swap area measured in multiples of 512 bytes.

SIZE Size of process image in multiples of 64 bytes.

WCHAN Wait channel number of a waiting process.

LINK Link pointer in list of runnable processes.

TEXT If text is pure, pointer to location of text table entry.

CLKT Countdown for *alarm(2)* measured in seconds.

-t Print table for terminals (only DH11 and DL11 handled) with these headings:

RAW Number of characters in raw input queue.

CAN Number of characters in canonicalized input queue.

OUT Number of characters in output queue.

MODE See *tty(4)*.

ADDR Physical device address.

DEL Number of delimiters (newlines) in canonicalized input queue.

COL Calculated column position of terminal.

STATE Miscellaneous state variables encoded thus:

W waiting for open to complete

O open

S has special (output) start routine

C carrier is on

B busy doing output

A process is awaiting output

X open for exclusive use

H hangup on close

PGRP Process group for which this is controlling terminal.

-u print information about a user process; the next argument is its address as given by *ps(1)*. The process must be in main memory, or

NAME

pstat — print system facts

SYNOPSIS

pstat [-aixptuf] [suboptions] [file]

DESCRIPTION

Pstat interprets the contents of certain system tables. If *file* is given, the tables are sought there, otherwise in */dev/mem*. The required namelist is taken from */unix*. Options are:

- a Under -p, describe all process slots rather than just active ones.
- i Print the inode table with these headings:
 - LOC The core location of this table entry.
 - FLAGS Miscellaneous state variables encoded thus:
 - L locked
 - U update time *fs(5)* must be corrected
 - A access time must be corrected
 - M file system is mounted here
 - W wanted by another process (L flag is on)
 - T contains a text file
 - C changed time must be corrected
 - CNT Number of open file table entries for this inode.
 - DEV Major and minor device number of file system in which this inode resides.
 - INO I-number within the device.
 - MODE Mode bits, see *chmod(2)*.
 - NLK Number of links to this inode.
 - UID User ID of owner.
 - SIZ/DEV Number of bytes in an ordinary file, or major and minor device of special file.
- x Print the text table with these headings:
 - LOC The core location of this table entry.
 - FLAGS Miscellaneous state variables encoded thus:
 - T *ptrace(2)* in effect
 - W text not yet written on swap device
 - L loading in progress
 - K locked
 - w wanted (L flag is on)
 - DADDR Disk address in swap, measured in multiples of 512 bytes.
 - CADDR Core address, measured in multiples of core clicks (machine dependent).
 - SIZE Size of text segment, measured in multiples of core clicks (machine dependent).
 - IPTR Core location of corresponding inode.
 - CNT Number of processes using this text segment.
 - CCNT Number of processes in core using this text segment.
- p Print process table for active processes with these headings:
 - LOC The core location of this table entry.
 - S Run state encoded thus:
 - 0 no process
 - 1 waiting for some event
 - 3 runnable

NAME

pwck, grpck — password/group file checkers

SYNOPSIS

/etc/pwck [file]

/etc/grpck [file]

DESCRIPTION

Pwck scans the password file and notes any inconsistencies. The checks include validation of the number of fields, login name, user ID, group ID, and whether the login directory and optional program name exist. The criteria for determining a valid login name is derived from "Setting up the UNIX System" in the *UniPlus+ Administrator's Guide*. The default password file is */etc/passwd*.

Grpck verifies all entries in the group file. This verification includes a check of the number of fields, group name, group ID, and whether all login names appear in the password file. The default group file is */etc/group*.

EXAMPLE

pwck

will list inconsistencies in */etc/passwd*.

grpck

will list inconsistencies in */etc/group*.

FILES

/etc/group

/etc/passwd

SEE ALSO

group(4), passwd(4).

"Setting up the UNIX System" in *UniPlus+ Administrator's Guide*.

DIAGNOSTICS

Group entries in */etc/group* with no login names are flagged.

NAME

runacct — run daily accounting

SYNOPSIS

/usr/lib/acct/runacct [mmdd [state]]

DESCRIPTION

Runacct is the main daily accounting shell procedure. It is normally initiated via *cron*(1M). *Runacct* processes connect, fee, disk, and process accounting files. It also prepares summary files for *prdaily* or billing purposes.

Runacct takes care not to damage active accounting files or summary files in the event of errors. It records its progress by writing descriptive diagnostic messages into *active*. When an error is detected, a message is written to */dev/console*, mail (see *mail*(1)) is sent to *root* and *adm*, and *runacct* terminates. *Runacct* uses a series of lock files to protect against re-invocation. The files *lock* and *lock1* are used to prevent simultaneous invocation, and *lastdate* is used to prevent more than one invocation per day.

Runacct breaks its processing into separate, restartable *states* using *statefile* to remember the last *state* completed. It accomplishes this by writing the *state* name into *statefile*. *Runacct* then looks in *statefile* to see what it has done and to determine what to process next. *States* are executed in the following order:

| | |
|-------------------|---|
| SETUP | Move active accounting files into working files. |
| WTMPFIX | Verify integrity of <i>wtmp</i> file, correcting date changes if necessary. |
| CONNECT1 | Produce connect session records in <i>ctmp.h</i> format. |
| CONNECT2 | Convert <i>ctmp.h</i> records into <i>tacct.h</i> format. |
| PROCESS | Convert process accounting records into <i>tacct.h</i> format. |
| MERGE | Merge the connect and process accounting records. |
| FEES | Convert output of <i>chargefee</i> into <i>tacct.h</i> format and merge with connect and process accounting records. |
| DISK | Merge disk accounting records with connect, process, and fee accounting records. |
| MERGETACCT | Merge the daily total accounting records in <i>daytacct</i> with the summary total accounting records in <i>/usr/adm/acct/sum/tacct</i> . |
| CMS | Produce command summaries. |
| USEREXIT | Any installation-dependent accounting programs can be included here. |
| CLEANUP | Cleanup temporary files and exit. |

To restart *runacct* after a failure, first check the *active* file for diagnostics, then fix up any corrupted data files such as *pacct* or *wtmp*. The *lock* files and *lastdate* file must be removed before *runacct* can be restarted. The argument *mmdd* is necessary if *runacct* is being restarted, and specifies the month and day for which *runacct* will rerun the accounting. Entry point for processing is based on the contents of *statefile*; to override this, include the

desired *state* on the command line to designate where processing should begin.

EXAMPLE

```
nohup runacct 2> /usr/adm/acct/nite/fd2log &
starts runacct.
nohup runacct 0601 2>> /usr/adm/acct/nite/fd2log &
restarts runacct.
nohup runacct 0601 MERGE 2>> /usr/adm/acct/nite/fd2log &
restarts runacct at a specific state.
```

FILES

```
/etc/wtmp
/usr/adm/pacct*
/usr/src/cmd/acct/tacct.h
/usr/src/cmd/acct/ctmp.h
/usr/adm/acct/nite/active
/usr/adm/acct/nite/dayacct
/usr/adm/acct/nite/lock
/usr/adm/acct/nite/lock1
/usr/adm/acct/nite/lastdate
/usr/adm/acct/nite/statefile
/usr/adm/acct/nite/ptacct*.mmdd
```

SEE ALSO

acct(1M), acctcms(1M), acctcom(1), acctcon(1M), acctmerg(1M), acctprc(1M), acctsh(1M), cron(1M), fwtmp(1M), acct(2), acct(4), utmp(4).
 "UNIX Accounting System" in the *UniPlus+ Administrator's Guide*.

DIAGNOSTICS

The accounting system will start complaining with *****RECOMPILE pnpssplit WITH NEW HOLIDAYS***** after the last holiday of the year. See "The UNIX Accounting System" for more on how to correct this condition. Other diagnostics are placed in various error and log files.

BUGS

Normally it is not a good idea to restart *runacct* in the *SETUP state*. Run *SETUP* manually and restart via:

```
runacct mmdd WTMPFIX
```

If *runacct* failed in the *PROCESS state*, remove the last *ptacct* file because it will not be complete.

NAME

sa1, sa2, sadc — system activity report package

SYNOPSIS

```
/usr/lib/sa/sadc [t n] [ofile]
/usr/lib/sa/sa1 [t n]
/usr/lib/sa/sa2 [-ubdycwaqvm] [-s time] [-e time] [-i sec]
```

DESCRIPTION

System activity data can be accessed at the special request of a user (see *sar(1)*) and automatically on a routine basis as described here. The operating system contains a number of counters that are incremented as various system actions occur. These include CPU utilization counters, buffer usage counters, disk and tape I/O activity counters, TTY device activity counters, switching and system-call counters, file-access counters, queue activity counters, and counters for inter-process communications.

Sadc and shell procedures *sa1* and *sa2* are used to sample, save and process this data.

Sadc, the data collector, samples system data *n* times every *t* seconds and writes in binary format to *ofile* or to standard output. If *t* and *n* are omitted, a special record is written. This facility is used at system boot time to mark the time at which the counters restart from zero. The */etc/rc* entry:

```
su sys -c "/usr/lib/sa/sadc /usr/adm/sa/sa`date +%d`&"
```

writes the special record to the daily data file to mark the system restart.

The shell script *sa1*, a variant of *sadc*, is used to collect and store data in binary file */usr/adm/sa/sadd* where *dd* is the current day. The arguments *t* and *n* cause records to be written *n* times at an interval of *t* seconds, or once if omitted. The entries in *crontab* (see *cron(1M)*):

```
0 * * 0,6 su sys -c "/usr/lib/sa/sa1"
0 8-17 * * 1-5 su sys -c "/usr/lib/sa/sa1 1200 3"
0 18-7 * * 1-5 su sys -c "/usr/lib/sa/sa1"
```

will produce records every 20 minutes during working hours and hourly otherwise.

The shell script *sa2*, a variant of *sar(1)*, writes a daily report in file */usr/adm/sa/sardd*. The options are explained in *sar(1)*. The *crontab* entry:

```
5 18 * * 1-5 su adm -c "/usr/lib/sa/sa2 -s 8:00 -e 18:01 -i 3600 -A"
```

will report important activities hourly during the working day.

The structure of the binary daily data file is:

```
struct sa {
    struct sysinfo si;      /* see /usr/include/sys/sysinfo.h */
    int szinode;            /* current entries of inode table */
    int szfile;             /* current entries of file table */
    int sztext;            /* current entries of text table */
    int szproc;            /* current entries of proc table */
    int mszinode;          /* size of inode table */
    int mszfile;           /* size of file table */
    int msztext;           /* size of text table */
    int mszproc;           /* size of proc table */
    long inodeovf;         /* cumul. overflows of inode table */
    long textovf;          /* cumul. overflows of text table */
    long procovf;          /* cumul. overflows of proc table */
    time_t ts;            /* time stamp, seconds */
    long devio[NDEVS][4]; /* device info for up to NDEVS units */
#define IO_OPS      0      /* cumul. I/O requests */
#define IO_BCNT     1      /* cumul. blocks transferred */
#define IO_ACT      2      /* cumul. drive busy time in ticks */
#define IO_RESP     3      /* cumul. I/O resp time in ticks */
};
```

FILES

```
/usr/adm/sa/sadd  daily data file
/usr/adm/sa/sardd  daily report file
/tmp/sa.adrfl      address file
```

SEE ALSO

sag(1G), sar(1), timex(1).

NAME

setmnt — establish mount table

SYNOPSIS

/etc/setmnt

DESCRIPTION

Setmnt creates the /etc/mnttab table (see *mnttab(4)*), which is needed for both the *mount(1M)* and *umount* commands. *Setmnt* reads standard input and creates a *mnttab* entry for each line. Input lines have the format:

filesys node

where *filesys* is the name of the file system's *special file* (e.g., "rp??") and *node* is the root name of that file system. Thus *filesys* and *node* become the first two strings in the *mnttab(4)* entry.

EXAMPLE

```
/etc/devnm / | grep -vv swap | grep -v root | /etc/setmnt
```

will put an entry for the root file system and the device on which it is mounted into the file /etc/mnttab (except if it is mounted on a device named "swap" or "root").

FILES

/etc/mnttab

SEE ALSO

mnttab(4).

BUGS

Evil things will happen if *filesys* or *node* are longer than 10 characters. *Setmnt* silently enforces an upper limit on the maximum number of *mnttab* entries.

NAME

shutdown — terminate all processing

SYNOPSIS

/etc/shutdown

DESCRIPTION

Shutdown is part of the UNIX System operation procedures. Its primary function is to terminate all currently running processes in an orderly and cautious manner. The procedure is designed to interact with the operator (i.e., the person who invoked *shutdown*). *Shutdown* may instruct the operator to perform some specific tasks, or to supply certain responses before execution can resume. *Shutdown* goes through the following steps:

All users logged on the system are notified to log off the system by a broadcasted message. The operator may display his/her own message at this time. Otherwise, the standard file save message is displayed.

If the operator wishes to run the file-save procedure, *shutdown* unmounts all file systems.

All file systems' super blocks are updated before the system is to be stopped (see *sync(1)*). This must be done before re-booting the system, to insure file system integrity. The most common error diagnostic that will occur is *device busy*. This diagnostic happens when a particular file system could not be unmounted.

SEE ALSO

mount(1M), sync(1).

NAME

updater — update files between two machines

SYNOPSIS

updater [**key**] local remote ...

DESCRIPTION

Updater updates files between two machines.

One of the following key letters must be included:

t Take files from the remote machine, updating the local machine.

p Put files from the local machine onto the remote machine, updating the remote machine.

d List the difference between files on the local and remote machines.

The following key letters are optional:

u Update a file only if it exists on both machines; this is the default condition.

r Replace a file if it did not exist on the destination machine.

Local refers to the local directory name.

Remote refers to the remote directory names. Only one remote name can be specified if the **p** (put) key is specified.

ALGORITHM

Open */dev/tty0* to the remote machine.

Stty the local port and send a *stty* command to the remote machine to condition both ends of the connection.

Send a "cd remote ; sumdir . | sort +2 > /tmp/rXXXXXX" to remote machine for each remote system; "cd local ; sumdir . | sort > /tmp/lXXXXXX" for local machine.

Wait for remote to complete.

Take /tmp/rXXXXXX.

Do a comparison between the local and the union of the remotes:

exists on remote only:

If both the **t** and **r** keys are specified, take the file;
otherwise list the file.

exists on local only:

If both **p** and **r** keys are specified, put the file;
otherwise list the file.

exist on both but different:

If **t** key is specified, take the file.
If **p** key is specified, put the file.
If **d** key is specified, list the file.

same:

nothing

EXAMPLE

updater d . .

uses */dev/tty0* to communicate with a remote machine, and compares directories on the remote and local systems.

NAME

uuclean — uucp spool directory clean-up

SYNOPSIS

/usr/lib/uucp/uuclean [options]

DESCRIPTION

Uuclean will scan the spool directory for files with the specified prefix and delete all those which are older than the specified number of hours.

The following options are available.

-d*directory* Clean *directory* instead of the spool directory.

-p*pre* Scan for files with *pre* as the file prefix. Up to 10 **-p** arguments may be specified. A **-p** without any *pre* following will cause all files older than the specified time to be deleted.

-n*time* Files whose age is more than *time* hours will be deleted if the prefix test is satisfied. (default time is 72 hours)

-w*file* The default action for *uuclean* is to remove files which are older than a specified time (see **-n** option). The **-w** option is used to find those files older than *time* hours, however, the files are not deleted. If the argument *file* is present the warning is placed in *file*, otherwise, the warnings will go to the standard output.

-s*sys* Only files destined for system *sys* are examined. Up to 10 **-s** arguments may be specified.

-m*file* The **-m** option sends mail to the owner of the file when it is deleted. If a *file* is specified then an entry is placed in *file*.

This program is typically started by *cron*(1M).

EXAMPLE

uuclean -pT -pRC -n0 -m

removes all files in /usr/spool/uucp with a prefix of T or RC, and mails notifications to the owners of the removed files.

FILES

/usr/lib/uucp directory with commands used by *uuclean* internally
/usr/spool/uucp spool directory

SEE ALSO

cron(1M), uucp(1C), uux(1C).

NAME

uusub — monitor uucp network

SYNOPSIS

/usr/lib/uucp/uusub [options]

DESCRIPTION

Uusub defines a *uucp* subnetwork and monitors the connection and traffic among the members of the subnetwork. The following options are available:

- a sys* Add *sys* to the subnetwork.
- d sys* Delete *sys* from the subnetwork.
- l* Report the statistics on connections.
- r* Report the statistics on traffic amount.
- f* Flush the connection statistics.
- u hr* Gather the traffic statistics over the past *hr* hours.
- c sys* Exercise the connection to the system *sys*. If *sys* is specified as *all*, then exercise the connection to all the systems in the subnetwork.

The meanings of the connections report are:

sys #call #ok time #dev #login #nack #other

where *sys* is the remote system name, *#call* is the number of times the local system tries to call *sys* since the last flush was done, *#ok* is the number of successful connections, *time* is the latest successful connect time, *#dev* is the number of unsuccessful connections because of no available device (e.g. ACU), *#login* is the number of unsuccessful connections because of login failure, *#nack* is the number of unsuccessful connections because of no response (e.g. line busy, system down), and *#other* is the number of unsuccessful connections because of other reasons.

The meanings of the traffic statistics are:

sfile sbyte rfile rbyte

where *sfile* is the number of files sent and *sbyte* is the number of bytes sent over the period of time indicated in the latest *uusub* command with the —*u hr* option. Similarly, *rfile* and *rbyte* are the numbers of files and bytes received.

EXAMPLE

uusub -c all -u 24

is typically started by *cron*(1M) once a day.

FILES

| | |
|------------------------|-----------------------|
| /usr/spool/uucp/SYSLOG | system log file |
| /usr/lib/uucp/L_sub | connection statistics |
| /usr/lib/uucp/R_sub | traffic statistics |

SEE ALSO

uucp(1C), uustat(1C).

NAME

vchk — version checkup

SYNOPSIS

vchk [argument] ...

DESCRIPTION

Vchk is a highly specialized form of *make*(1) designed to check and maintain the modes, ownerships, and versions of a set of files specified in the *description file*. The description file is essentially a "photograph" of what a healthy system (i.e., one with all its components in the correct state) looks like. It contains a list of pathnames (for both files and directories) that should exist and have specific protections and contents. *Vchk* reads the description file, checks each item specified and prints error messages when a file does not match its description. Many problems can be fixed directly by *vchk*, such as incorrect mode and/or owner and missing link names. All other problems involve actually replacing a file, detected by comparing some combination of checksum, length, and/or version number (from the description file) with the value generated from the actual file being checked. When a file needs to be replaced *vchk* invokes the command named by the **REMAKE** macro (see **MACROS** below).

Each *argument* is either a definition or an option. Option arguments begin with the character **—** and consist of a string of letters (called *flags*) from the set **'DIPSabcdefiklmprstv'**. The **f** and **t** flags cause the next argument to be considered specially. The **p** and **P** flags cause the rest of the argument in which they appear to be considered specially. Other arguments are either macro definitions (i.e., *name* = *string* pairs) or simply strings which are saved as numeric macros. Briefly, the *flags* are as follows:

- A** *sysid*
specifies an alternate *sysid* rather than using the one found in */etc/sys_id*.
- D** enables debugging messages.
- I** process control lines only.
- P** *sysid*
preprocess the description file; *sysid* is optional and is explained below under **PREPROCESSING**.
- S** suppress printing of non-fatal error messages.
- a** checks all lines in the description file. Modifies the **b**, **P**, and **k** options.
- b** build a description file for the current directory.
- c** print shell commands to fix the file system.
- d** suppress re-installation commands and error messages.
- e** suppress checks for everything but existence.
- f** *filename*
cause *vchk* to read *filename* instead of */etc/vchk_tree*.
- i** go interactive: modifies **b**, **c**, and **x** options.
- k** perform checksums on files having checksum field.

- l suppress listing of files left in directories.
- m allow multiple copies of files.
- ppw *file*
force *vchk* to re-evaluate and/or use an alternate password file.
- r allow redundant password entries (user ID1).
- s remain silent about trivial problems.
- v suppress checking of version numbers.
- x execute shell commands to fix the file system (cf. the -c option which prints rather than executes).

DESCRIPTION FILE SYNTAX

Lines in the description file are either comments, control lines, specifications, or commands. Control lines provide a simple *ifdef* mechanism for selectively ignoring specification lines. Specification lines describe files and/or directories that need to be checked. Commands are not processed by *vchk* but (in the spirit of *make(1)*) are used when the file specified above them is found to need replacing.

Several conventions are observed to maintain the readability of the description file; for example, a trailing backslash and all leading white space on the following line are ignored when processed. In addition, backslash may be used to delay the expansion of macros (in macro definitions only) and, as described below, to alter the evaluation of parentheses and braces in pathnames.

COMMENTS

Comment lines always start with a '#'. If the second character on a comment line is also a '#', then that line is printed on the standard error when read by *vchk*. Any line may have a trailing comment, which is universally ignored.

CONTROL LINES

Control lines start with a '.' (period). The mechanism is similar to the C language pre-processor except that defined words do not have values associated with them; words are simply defined or not. The control commands supported are as follows:

.define wordlist

where *wordlist* is a list of white-space-separated words to be defined which have no associated values. Note that only the first twelve letters of defined words are significant. Storage for defined words is static. There is a maximum of sixty defined words at any given time.

.ifdef define_expression

where *define_expression* is an infix boolean expression involving defined words and the operators '!', '&', and '|', which mean 'not', 'and', and 'or', respectively. The value of each word evaluates to a boolean "yes" if that word is defined and "no" if not. If the expression evaluates to be false, lines are ignored until the matching *.endif* or *.else* control line is read. *ifdef* is also supported and reverses the sense of the expression test.

.include filename

is very similar the C pre-processor *include* with the exception that there are no default searching places and that the filename is not en-

closed in double quotes or angle brackets. In addition, if the first character of the filename is an exclamation mark (!), then the rest of line is considered to be a shell command and its standard output is what gets included.

.undef wordlist

undefines each word in the wordlist.

.unset wordlist

frees the storage associated with macro definitions (detailed in a following section) for the given wordlist (which is composed of macro names). Words in wordlist that are already unset (or were never set) are silently ignored.

.chdir directory_name

changes the current directory to the one specified and alters the starting location of pathnames anchored from the current directory.

.exit message

causes *vchk* to print the message and exit immediately.

As an aid to debugging the description file, a single '.' on a line by itself causes *vchk* to print the currently defined control symbols on the standard error when it reads that line.

MACROS

A macro processing facility very similar to the one used by *make(1)* is provided. Macros are defined when a line containing the macro name, an equal sign, and the value is read. The value may be null or include macro invocations. Unlike 'defined' words, macro names are fully significant and are saved in dynamic memory. Macros are invoked by the '\$' character. As in *make* scripts, macro names must be surrounded by ()s when they are longer than a single letter. There is a special macro (named '.', thus referenced with '\$.') which always expands to the name of the current directory. It is useful in the construction of link names since most files have their links close by.

Except in the definition of a new macro (where interpretation may need to be delayed) and in comments, it is always an error for a macro to be used if it is undefined. Since the '##' comment is printed after macro substitution, it is a useful debugging tool. In keeping with the spirit of the 'dump control words' command (.), a single '\$' on a line by itself prints all the currently defined macros and their values.

Note that lines are re-scanned once a macro has been substituted so that a macro may be defined to expand to a control line, comment, or even a macro definition. Note that this degenerates to a recursive loop if the definition of a macro contains a reference to that macro.

Two predefined macros exist. The first, called REMAKE, contains the name (and options) of the program to use to replace damaged or missing files. If the file */etc/sys_id* exists and is not empty, it is assumed to contain the UniSoft code name assigned to your system and *vchk* will setup the REMAKE macro to be the command "take -sN" where N is the name found in */etc/sys_id*. This allows systems that reside at UniSoft to be updated automatically over a direct tty line via the *take(1M)* program. If the */etc/sys_id* file has a single empty line in it, then REMAKE will be set to "take -s". This allows remote systems to be updated automatically over phone lines. If the */etc/sys_id* file does not exist, *vchk* sets the REMAKE

macro to be "install". Note that the description file may redefine the REMAKE macro at any time.

The second predefined macro is called ARGS and can be set but not referenced. Strings assigned to ARGS are treated as command line options. The - preceding option keyletters is still required, and enables that option. A plus sign, '+', must be used instead to disable a keyletter option. Resetting the b, p, and r is not allowed.

DESCRIPTION LINES

Each line that is not a comment, control line, macro definition, or command is considered to be the specification for a particular file or directory. These have a simple and regular syntax: the first and only mandatory field is the *pathname*, which must begin at the root (/) or the current directory (./). In practice we find that starting all lines with a macro allows easy relocation of the entire tree described and is very readable.

The rest of the line contains optional information about the contents and protection of the file. Contents specifications are separated from the pathname by white space. The entire protection specification is bracketed to separate it from the rest of the line.

PATHNAMES

Pathnames refer to directories (if and only if they end in a '/' character) or files (if they do not end in a '/'). Use of shell metacharacters (*globbing*) is not supported but two mechanisms are provided to allow variable pathnames: braces, {}, and parentheses. Braces are interpreted just as in *csh*(1); each of the expanded pathnames must exist and must match the description given. Parentheses in pathnames are interpreted similarly, except that *exactly one* of the resulting pathnames must exist. This feature is useful, for example, to allow a program to be in either /bin or /usr/bin, but not both.

Parentheses and braces are expanded left to right; for example, the construction (a,b){x,y} means either ax and ay must exist or bx and by. Backslashes may be used to delay or prevent the interpretation of ()s and {}s. For example, \ (a,b) {x,y} means one of ax or bx and one of ay or by must exist. One layer of backslashes are removed for each pass through the pathname and each time an unescaped parenthesis or bracket is detected and expanded, another pass is made.

Note that when alternative paths are used (i.e., parentheses occur in the pathname) the first one is considered the one to be rebuilt in the event that all are missing. For example, the pathname (/usr)/bin/ls would look first in /usr/bin for 'ls', then in /bin, and try to "REMAKE /usr/bin/ls" if both are missing. The reverse is true for (/usr)/bin/ls.

SPECIFICATIONS

Two kinds of specifications are implemented. The first kind deals with the contents of the file or directory and follows the pathname (separated from it by white space). The second kind deals with the files protection; these are enclosed in some type of parentheses to separate them from contents specifications. The kind of parentheses used, ()s, []s, <>s, or {}s, modify the action taken by *vchk* according to the table below:

- () Enables checking and replacing of the file.
- [] Enables checking but never replacing. If the file is missing, *vchk* will complain but not try to rebuild it.

<> Enables checking (if and only if the file exists or the -a command line option is given) and never replacing.

() Enables checking but not repairing, (i.e., if the file is missing then it will be remade, but if it exists and is incorrect it will not be remade).

Associated with each directory is a default mode and ownership for the files and directories contained within it. Unless explicitly given, each directory inherits its defaults from its parent directory. If unspecified, the uppermost directory (either the root or current directory) sets the mode and ownership of its contents from its own mode and ownership. These defaults may be reset at any time simply by following the directory name with a mode and/or user name.

Regular files have three optional contents specification fields: length, checksum, and version number. These may be specified with a word (either Length, Checksum, or Version), an optional space, or a numeric value. The word may be any prefix, for example, 'Length 34' or 'L34'. The checksums used are the same as those produced by *sum*(1). The length checked is that returned by *stat*(2). These checks do not apply to device files (only block and character devices are supported); thus their contents specification field must begin with either b or c and must be followed by the major and minor device number (separated by white space). If x is used instead of either the major or minor device number, *vchk* will allow the device to have any value.

The protection specification consists of a list of command prefixes separated by semicolons. The commands supported are *chmod*, *chown*, and *link to*. If angle brackets (i.e., <>s) are used instead of parentheses to enclose the protection specification, the file or directory so referenced is optional and will not generate diagnostics if it is missing. It can be raised to the status of []s by giving the -a command line option. If square brackets (i.e., []s) are used, the referenced file cannot be replaced automatically, as for example, the password file. If curly brackets (i.e., {}s) are used, the referenced file will be replaced only if it is missing, not if it exists and is wrong (according to the description file). This is useful for files like /etc/termcap.

Any other information in the protection specification is treated as a special comment that is printed with error messages about that file.

OPERATION

In order for *vchk* to check the ownership of files it must map user ID numbers onto login names. The password file is normally used for this mapping but it is too expensive to look up each name every time it is used so *vchk* creates a temporary file (/etc/vchk_pw) the first time it is run; whenever its temporary is out of date with respect to the real password file, *vchk* recreates the temporary file.

In the process of reading the password file *vchk* inspects each account and prints diagnostics when it finds questionable data there. These messages are warnings or simply situations which bear reporting; the format of these messages is "Line <number>: message". The word "Error:" is prepended to the warnings for a particular line if *vchk* has decided to ignore that line of the password file.

The -p[*pw_file*] option is provided to allow users who do not have write permission in /etc to use *vchk*. If specified with a filename after it, *vchk*

will get the saved password information from that file. If the file does not exist, *vchk* will create it. Use of the *-p* option without a filename informs *vchk* to reprocess the password file even if it is not out of date.

Vchk normally expects the description file to be */etc/vchk_tree*, but if the standard input to *vchk* is a regular file, that file will be read instead.

Instead of redirecting the standard input, the *-f* option can be used to respecify the description file. It is an error to use both.

The best way to build a new description file is to *chdir* to the appropriate directory and run *vchk* with the *-b* option. A description file for the current directory will be produced on the standard output. The *-l* option may also be used, causing *vchk* to ask before descending each directory.

In addition to reporting errors, the *-c* flag prints shell commands to correct the detected error. The *-l* option can be used with the *-c* option to ask before outputting a command.

It is inadvisable to use the *-x* flag until the description file has been used and debugged. This flag allows *vchk* to execute the *chmod(2)*, *chown(2)*, and *ln(2)* commands internally, saving much time. Re-installation commands (cf. the *REMAKE* macro) are executed via the *system(3)* call.

PREPROCESSING

The *-Psysid* command line option provides a means for simplifying a complex description file. Everything except macro substitution is suppressed and after each line is parsed, it is printed on the standard output instead of being used to check the filesystem.

If a *sysid* is given after the *-P* flag, then it is used to lookup a line from the *(/etc/takelist)* file. (See *take(1m)* for a more complete description of the function of the */etc/takelist* file.)

The lines in */etc/takelist* are composed of any number of fields (called alternates) separated by colons (:s). The first alternate in a line is a list of system names separated by or bars (|s). The *sysid* above is compared with each of the system names in the first alternate of each line until it is found. If not found, then *vchk* exits with an appropriate error message.

When the line from */etc/takelist* for the current *sysid* is found, then each of the additional alternates are considered lists of root directories (separated by colons or bars) to be prepended to filenames in the tree file before looking for them.

If a file is found in more or less than exactly 1 place in the list, then an error is reported and that line is not include in the preprocessed output. If it is found, then the checksum, length, and version number are computed from that file and replaced in the preprocessed output.

EXAMPLE

Following are some excerpts from a typical description file.

```
B = (/usr)/bin          # programs can be in /bin or /usr/bin
/      bin 755          (chmod 755)
$B/ar   Version 1.0
$B/awk  Version 1.3
$B/more  Version 1.0    (link to ./page)
$B/scsdiff C54686 L1253 (shell script)
$B/su    Version 1.0    (chown root; chmod 4755)
```

```
/etc/      root 644
/etc/passwd      [password file]
/etc/group      [group file]
/etc/init      Version 1.0    (chmod 700)
/etc/update Version 1.1    (chmod 700)
/etc/ddate      <dump dates>
```

The first line of the above example defines a macro, *B*, to be the string *(/usr)/bin*. This macro is then invoked on lines 3 through 7 of the example to allow the programs mentioned to be in either */usr/bin* or */bin*.

The second line specifies that the root directory (*/*) should have mode that the default mode and owner for files found in it be 755 and *bin*.

The third line specifies that the *ar* program should be version 1.0, owned by *bin* and have mode 755. The mode and owner are implied in the following way. Each directory inherits its mode and ownership from its parent. Thus */bin* inherits the owner of root (which is unspecified in the example and thus defaults to whatever the owner of the root (*/*) is when the example is run). The mode of the root directory is specified as 755.

FILES

```
/etc/vchk_pw      the file where vchk saves the password file summary.
/etc/passwd      the password file.
/etc/vchk_tree    the default description file.
/dev/tty          where vchk prints questions and gets the responses
                  (when the -l option is used).
<standard error> used to print all diagnostics.
<standard output> used to print shell commands and the newly built
                  description file (when using the -b option).
<standard input> considered the default description file if it is a regular
                  file.
```

SEE ALSO

chmod(1), *ln(1)*, *chown(1M)*.

BUGS

Vchk doesn't know about group names. It expects the group ID of a file to be the one mentioned in the password file. There is no way (except tediously via the *-i* option) to exclude directories from inspection when building a new description file. There is also no way to automatically update an existing description file (i.e., to tell *vchk* to fix the description file instead of the filesystem).

NAME

volcopy, labelit — copy file systems with label checking

SYNOPSIS

```
/etc/volcopy [options] fsname special1 volname1 special2 volname2
/etc/labelit special [ fsname volume [ -n ] ]
```

DESCRIPTION

Volcopy makes a literal copy of the file system using a blocksize matched to the device. *Options* are:

- a invoke a verification sequence requiring a positive operator response instead of the standard 10 second delay before the copy is made,
- s (default) invoke the **DEL if wrong** verification sequence.

Other *options* are used only with tapes:

- bpidensity bits-per-inch (i.e., 800/1600/6250),
- feetsize size of reel in feet (i.e., 1200/2400),
- reelnum beginning reel number for a restarted copy,
- buf use double buffered I/O.

The program requests length and density information if it is not given on the command line or is not recorded on an input tape label. If the file system is too large to fit on one reel, *volcopy* will prompt for additional reels. Labels of all reels are checked. Tapes may be mounted alternately on two or more drives.

The *fsname* argument represents the mounted name (e.g.: **root**, **u1**, etc.) of the filesystem being copied.

The *special* should be the physical disk section or tape (e.g.: **/dev/rdisk15**, **/dev/rmt0**, etc.).

The *volname* is the physical volume name (e.g.: **pk3**, **t0122**, etc.) and should match the external label sticker. Such label names are limited to six or fewer characters. *Volname* may be — to use the existing volume name.

Special1 and *volname1* are the device and volume from which the copy of the file system is being extracted. *Special2* and *volname2* are the target device and volume.

Fsname and *volname* are recorded in the last 12 characters of the superblock (char *fsname*[6], *volname*[6];).

Labelit can be used to provide initial labels for unmounted disk or tape file systems. With the optional arguments omitted, *labelit* prints current label values. The —n option provides for initial labeling of new tapes only (this destroys previous contents).

EXAMPLE

```
volcopy newsys /dev/rrp15 1 /dev/rfd0 1
```

copies volume 1 of the file system labeled *newsys* mounted on **/dev/rrp15** onto volume 1 of **/dev/rfd0**.

```
labelit /dev/rfd0 oldsys save
```

relabels the file system mounted on **/dev/rfd0** with a new *fsname* of *oldsys* and a new *volname* of *save*.

FILES

/etc/log/filesave.log a record of file systems/volumes copied

SEE ALSO

fs(4).

BUGS

Only device names beginning `/dev/rmt` are treated as tapes. Tape record sizes are determined both by density and by drive type. Records are 5,120 bytes long at 800 and 1600 bits-per-inch, and 25,600 bytes long at 6250 bits-per-inch.

NAME

wall — write to all users

SYNOPSIS`/etc/wall`**DESCRIPTION**

Wall reads its standard input until an end-of-file. It then sends this message to all currently logged in users preceded by:

Broadcast Message from ...

It is used to warn all users, typically prior to shutting down the system.

The sender must be super-user to override any protections the users may have invoked (see *mesg*(1)).

EXAMPLE

wall

will broadcast the standard input to all users who are not protected against receiving messages by the *mesg* command.

FILES

`/dev/tty*`

SEE ALSO

mesg(1), *write*(1).

DIAGNOSTICS

“Cannot send to ...” when the open on a user’s tty file fails.

NAME

whodo — who is doing what

SYNOPSIS

/etc/whodo

DESCRIPTION

Whodo produces merged, reformatted, and dated output from the *who(1)* and *ps(1)* commands.

EXAMPLE

/etc/whodo

will return something like the following:

UNIX

```
co root 13:52
co 60 0:01 sh
co 61 0:01 ps
co 62 0:00 sh
```

SEE ALSO

ps(1), *who(1)*.

NAME

intro — introduction to special files

DESCRIPTION

This section describes special files that refer to specific hardware peripherals and UNIX System device drivers. The names of the entries are generally derived from names for the hardware, as opposed to the names of the special files themselves. Characteristics of both the hardware device and the corresponding UNIX System device driver are discussed where applicable.

BUGS

While the names of the entries *generally* refer to vendor hardware names, in certain cases these names are seemingly arbitrary for various historical reasons.

NAME

aliases — aliases file for delivermail

SYNOPSIS

/usr/lib/aliases

DESCRIPTION

This file describes user ID aliases that will be used by /etc/delivermail. It is formatted as a series of lines of the form
name:addr1,addr2,...addrn

The *name* is the name to alias, and the *addri* are the addresses to send the message to. Lines beginning with white space are continuation lines. Lines beginning with '#' are comments.

Aliasing occurs only on local names. Loops cannot occur since no message will be sent to any person more than once.

SEE ALSO

delivermail(8)

NAME

err — error-logging interface

DESCRIPTION

Minor device 0 of the *err* driver is the interface between a process and the system's error-record collection routines. The driver may be opened only for reading by a single process with super-user permissions. Each read causes an entire error record to be retrieved; the record is truncated if the read request is for less than the record's length.

FILES

/dev/error special file

SEE ALSO

errdemon(1M).

NAME

/etc/hosts -- host table for bnet

DESCRIPTION

The BNET host table is organized as follows:

This is a comment line. It must begin with "#"

Other lines are of the form:

<inet-addr> <delim> <host-name> [<delim> <host-nickname>]

where

<inet-addr>

is a 32 bit type-a internet address, composed of one byte of "network number" followed by 3 bytes of local network address. Each byte is delimited by a period. For example,
0x27.0.1.1

refers to local-address 0x11 on network 0x27. Fields can be specified in decimal or hexadecimal notation. Normally, an installation will choose one network number for all hosts on the bnet (ethernet). Official type-a network numbers are assigned by the US DOD. Any network number less than 127 may be actually chosen if a particular installation is not planning to connect to the DCN network in the near future. Future releases of BNET will support type-b (16-bit) and type-c (24-bit) network numbers. See DCN/NIC RFC-790 for discussion of network numbers. Local-addresses are the low-order three bytes of the ethernet board address. The current release assumes a 3com ethernet controller is installed, so the upper three bytes of the ethernet address is determined. This restriction will be removed in the next release of BNET.

<delim>

is a SINGLE SPACE. (!).

<host-name>

is the official name of the host. For the local host, this field should be exactly the same as the contents of /usr/lib/uucp/SYSTEMNAME, though no checks are made anywhere for this equivalence at this time. Since uucp limits the length of hostnames to seven characters, so does BNET, but this restriction will disappear in the next release of BNET.

<host-nickname>

is a nickname or alias for the officially named host. Hosts can have several nicknames.

LOCAL HOST

The local host, i.e., the loopback driver, has a distinguished entry in the host table:

127.0.0.1 myself

That is, network number 127, host number 1.

EXAMPLE

The following is a short host table for a network with two hosts.

```
# Commnet line...
```

```
39.0.1.14 jeff j
```

```
127.0.0.1 bill b
```

The local host is named "bill" or "b". The remote host is named "jeff" or "j", and is on net #39. If the remote host has a 3com ethernet controller, then it would have ethernet number 0x02608C00010D. The 0x02608C is 3com's manufacturer's ethernet number.

NAME

mem, kmem — core memory

DESCRIPTION

Mem is a special file that is an image of the core memory of the computer. It may be used, for example, to examine, and even to patch the system.

Byte addresses in *mem* are interpreted as memory addresses. References to non-existent locations cause errors to be returned.

Examining and patching device registers is likely to lead to unexpected results when read-only or write-only bits are present.

The file *kmem* is the same as *mem* except that kernel virtual memory rather than physical memory is accessed.

FILES

/dev/mem

/dev/kmem

NULL(7)

NULL(7)

NAME

null — the null file

DESCRIPTION

Data written on a null special file is discarded.

Reads from a null special file always return 0 bytes.

FILES

/dev/null

NAME

termio — general terminal interface

DESCRIPTION

This section describes both a particular special file and the general nature of the terminal interface.

The file `/dev/tty` is, in each process, a synonym for the control terminal associated with the process group of that process, if any. It is useful for programs or shell sequences that wish to be sure of writing messages on the terminal no matter how output has been redirected. It can also be used for programs that demand the name of a file for output, when typed output is desired and it is tiresome to find out what terminal is currently in use.

All of the asynchronous communications ports use the same general interface, no matter what hardware is involved. The remainder of this section discusses the common features of this interface.

When a terminal file is opened, it normally causes the process to wait until a connection is established. In practice, users' programs seldom open these files; they are opened by *getty* and become a user's standard input, output, and error files. The very first terminal file opened by the process group leader of a terminal file not already associated with a process group becomes the *control terminal* for that process group. The control terminal plays a special role in handling quit and interrupt signals, as discussed below. The control terminal is inherited by a child process during a *fork(2)*. A process can break this association by changing its process group using *setpgrp(2)*.

A terminal associated with one of these files ordinarily operates in full-duplex mode. Characters may be typed at any time, even while output is occurring, and are only lost when the system's character input buffers become completely full, which is rare, or when the user has accumulated the maximum allowed number of input characters that have not yet been read by some program. Currently, this limit is 256 characters. When the input limit is reached, all the saved characters are thrown away without notice.

Normally, terminal input is processed in units of lines. A line is delimited by a new-line (ASCII LF) character, an end-of-file (ASCII EOT) character, or an end-of-line character. This means that a program attempting to read will be suspended until an entire line has been typed. Also, no matter how many characters are requested in the read call, at most one line will be returned. It is not, however, necessary to read a whole line at once; any number of characters may be requested in a read, even one, without losing information.

During input, erase and kill processing is normally done. By default, the character `#` erases the last character typed, except that it will not erase beyond the beginning of the line. By default, the character `@` kills (deletes) the entire input line, and optionally outputs a new-line character. Both these characters operate on a key-stroke basis, independently of any backspacing or tabbing that may have been done. Both the erase and kill characters may be entered literally by preceding them with the escape character (`\`). In this case the escape character is not read. The erase and kill characters may be changed.

Certain characters have special functions on input. These functions and their default character values are summarized as follows:

| | |
|-------|--|
| INTR | (Rubout or ASCII DEL) generates an <i>interrupt</i> signal which is sent to all processes with the associated control terminal. Normally, each such process is forced to terminate, but arrangements may be made either to ignore the signal or to receive a trap to an agreed-upon location; see <i>signal(2)</i> . |
| QUIT | (Control- or ASCII FS) generates a <i>quit</i> signal. Its treatment is identical to the interrupt signal except that, unless a receiving process has made other arrangements, it will not only be terminated but a core image file (called <i>core</i>) will be created in the current working directory. |
| ERASE | (#) erases the preceding character. It will not erase beyond the start of a line, as delimited by a NL, EOF, or EOL character. |
| KILL | (@) deletes the entire line, as delimited by a NL, EOF, or EOL character. |
| EOF | (Control-d or ASCII EOT) may be used to generate an end-of-file from a terminal. When received, all the characters waiting to be read are immediately passed to the program, without waiting for a new-line, and the EOF is discarded. Thus, if there are no characters waiting, which is to say the EOF occurred at the beginning of a line, zero characters will be passed back, which is the standard end-of-file indication. |
| NL | (ASCII LF) is the normal line delimiter. It can not be changed or escaped. |
| EOL | (ASCII NUL) is an additional line delimiter, like NL. It is not normally used. |
| STOP | (Control-s or ASCII DC3) can be used to temporarily suspend output. It is useful with CRT terminals to prevent output from disappearing before it can be read. While output is suspended, STOP characters are ignored and not read. |
| START | (Control-q or ASCII DC1) is used to resume output which has been suspended by a STOP character. While output is not suspended, START characters are ignored and not read. The start/stop characters can not be changed or escaped. |

The character values for INTR, QUIT, ERASE, KILL, EOF, and EOL may be changed to suit individual tastes. The ERASE, KILL, and EOF characters may be escaped by a preceding \ character, in which case no special function is done.

When the carrier signal from the data-set drops, a *hangup* signal is sent to all processes that have this terminal as the control terminal. Unless other arrangements have been made, this signal causes the processes to terminate. If the hangup signal is ignored, any subsequent read returns with an end-of-file indication. Thus programs that read a terminal and test for end-of-file can terminate appropriately when hung up on.

When one or more characters are written, they are transmitted to the terminal as soon as previously-written characters have finished typing. Input characters are echoed by putting them in the output queue as they arrive.

If a process produces characters more rapidly than they can be typed, it will be suspended when its output queue exceeds some limit. When the queue has drained down to some threshold, the program is resumed.

Several *ioctl(2)* system calls apply to terminal files. The primary calls use the following structure, defined in *<termio.h>*:

```
#define NCC      8
struct termio {
    unsigned short c_iflag; /* input modes */
    unsigned short c_oflag; /* output modes */
    unsigned short c_cflag; /* control modes */
    unsigned short c_lflag; /* local modes */
    char c_line; /* line discipline */
    unsigned char c_cc[NCC]; /* control chars */
};
```

The special control characters are defined by the array *c_cc*. The relative positions and initial values for each function are as follows:

```
0  INTR  DEL
1  QUIT  FS
2  ERASE #
3  KILL  @
4  EOF   EOT
5  EOL   NUL
6  reserved
7  reserved
```

The *c_iflag* field describes the basic terminal input control:

```
IGNBRK  0000001 Ignore break condition.
BRKINT   0000002 Signal interrupt on break.
IGNPAR   0000004 Ignore characters with parity errors.
PARMRK   0000010 Mark parity errors.
INPCK    0000020 Enable input parity check.
ISTRIP   0000040 Strip character.
INLCR    0000100 Map NL to CR on input.
IGNCR    0000200 Ignore CR.
ICRNL    0000400 Map CR to NL on input.
IUCLC    0001000 Map upper-case to lower-case on input.
IXON     0002000 Enable start/stop output control.
IXANY    0004000 Enable any character to restart output.
IXOFF    0010000 Enable start/stop input control.
```

If IGNBRK is set, the break condition (a character framing error with data all zeros) is ignored, that is, not put on the input queue and therefore not read by any process. Otherwise if BRKINT is set, the break condition will generate an interrupt signal and flush both the input and output queues. If IGNPAR is set, characters with other framing and parity errors are ignored.

If PARMRK is set, a character with a framing or parity error which is not ignored is read as the three character sequence: 0377, 0, X, where X is the data of the character received in error. To avoid ambiguity in this case, if ISTRIP is not set, a valid character of 0377 is read as 0377, 0377. If PARMRK is not set, a framing or parity error which is not ignored is read as the character NUL (0).

If INPCK is set, input parity checking is enabled. If INPCK is not set, input parity checking is disabled. This allows output parity generation without input parity errors.

If ISTRIP is set, valid input characters are first stripped to 7-bits, otherwise all 8-bits are processed.

If INLCR is set, a received NL character is translated into a CR character. If IGNCR is set, a received CR character is ignored (not read). Otherwise if ICRNL is set, a received CR character is translated into a NL character.

If IUCLC is set, a received upper-case alphabetic character is translated into the corresponding lower-case character.

If IXON is set, start/stop output control is enabled. A received STOP character will suspend output and a received START character will restart output. All start/stop characters are ignored and not read. If IXANY is set, any input character, will restart output which has been suspended.

If IXOFF is set, the system will transmit START/STOP characters when the input queue is nearly empty/full.

The initial input control value is all bits clear.

The `c_oflag` field specifies the system treatment of output:

| | | |
|--------|---------|------------------------------------|
| OPOST | 0000001 | Postprocess output. |
| OLCUC | 0000002 | Map lower case to upper on output. |
| ONLCR | 0000004 | Map NL to CR-NL on output. |
| OCRNL | 0000010 | Map CR to NL on output. |
| ONOCR | 0000020 | No CR output at column 0. |
| ONLRET | 0000040 | NL performs CR function. |
| OFILL | 0000100 | Use fill characters for delay. |
| OFDEL | 0000200 | Fill is DEL, else NUL. |
| NLDLY | 0000400 | Select new-line delays: |
| NL0 | 0 | |
| NL1 | 0000400 | |
| CRDLY | 0003000 | Select carriage-return delays: |
| CR0 | 0 | |
| CR1 | 0001000 | |
| CR2 | 0002000 | |
| CR3 | 0003000 | |
| TABDLY | 0014000 | Select horizontal-tab delays: |
| TAB0 | 0 | |
| TAB1 | 0004000 | |
| TAB2 | 0010000 | |
| TAB3 | 0014000 | Expand tabs to spaces. |
| BSDLY | 0020000 | Select backspace delays: |
| BS0 | 0 | |
| BS1 | 0020000 | |
| VDLY | 0040000 | Select vertical-tab delays: |
| VT0 | 0 | |
| VT1 | 0040000 | |
| FFDLY | 0100000 | Select form-feed delays: |
| FF0 | 0 | |
| FF1 | 0100000 | |

If OPOST is set, output characters are post-processed as indicated by the remaining flags, otherwise characters are transmitted without change.

If OLCUC is set, a lower-case alphabetic character is transmitted as the corresponding upper-case character. This function is often used in conjunction with IUCLC.

If ONLCR is set, the NL character is transmitted as the CR-NL character pair. If OCRNL is set, the CR character is transmitted as the NL character. If ONOCR is set, no CR character is transmitted when at column 0 (first position). If ONLRET is set, the NL character is assumed to do the carriage-return function; the column pointer will be set to 0 and the delays specified for CR will be used. Otherwise the NL character is assumed to do just the line-feed function; the column pointer will remain unchanged. The column pointer is also set to 0 if the CR character is actually transmitted.

The delay bits specify how long transmission stops to allow for mechanical or other movement when certain characters are sent to the terminal. In all cases a value of 0 indicates no delay. If OFILL is set, fill characters will be transmitted for delay instead of a timed delay. This is useful for high baud rate terminals which need only a minimal delay. If OFDEL is set, the fill character is DEL, otherwise NUL.

If a form-feed or vertical-tab delay is specified, it lasts for about 2 seconds.

New-line delay lasts about 0.10 seconds. If ONLRET is set, the carriage-return delays are used instead of the new-line delays. If OFILL is set, two fill characters will be transmitted.

Carriage-return delay type 1 is dependent on the current column position, type 2 is about 0.10 seconds, and type 3 is about 0.15 seconds. If OFILL is set, delay type 1 transmits two fill characters, and type 2 four fill characters.

Horizontal-tab delay type 1 is dependent on the current column position. Type 2 is about 0.10 seconds. Type 3 specifies that tabs are to be expanded into spaces. If OFILL is set, two fill characters will be transmitted for any delay.

Backspace delay lasts about 0.05 seconds. If OFILL is set, one fill character will be transmitted.

The actual delays depend on line speed and system load.

The initial output control value is all bits clear.

The `c_cflag` field describes the hardware control of the terminal:

| | | |
|-------|---------|------------|
| CBAUD | 0000017 | Baud rate: |
| B0 | 0 | Hang up |
| B50 | 0000001 | 50 baud |
| B75 | 0000002 | 75 baud |
| B110 | 0000003 | 110 baud |
| B134 | 0000004 | 134.5 baud |
| B150 | 0000005 | 150 baud |
| B200 | 0000006 | 200 baud |
| B300 | 0000007 | 300 baud |
| B600 | 0000010 | 600 baud |
| B1200 | 0000011 | 1200 baud |
| B1800 | 0000012 | 1800 baud |
| B2400 | 0000013 | 2400 baud |
| B4800 | 0000014 | 4800 baud |
| B9600 | 0000015 | 9600 baud |
| EXTA | 0000016 | External A |

| | | |
|--------|---------|-------------------------------|
| EXTB | 0000017 | External B |
| CSIZE | 0000060 | Character size: |
| CS5 | 0 | 5 bits |
| CS6 | 0000020 | 6 bits |
| CS7 | 0000040 | 7 bits |
| CS8 | 0000060 | 8 bits |
| CSTOPB | 0000100 | Send two stop bits, else one. |
| CREAD | 0000200 | Enable receiver. |
| PARENB | 0000400 | Parity enable. |
| PARODD | 0001000 | Odd parity, else even. |
| HUPCL | 0002000 | Hang up on last close. |
| CLOCAL | 0004000 | Local line, else dial-up. |

The CBAUD bits specify the baud rate. The zero baud rate, B0, is used to hang up the connection. If B0 is specified, the data-terminal-ready signal will not be asserted. Normally, this will disconnect the line. For any particular hardware, impossible speed changes are ignored.

The CSIZE bits specify the character size in bits for both transmission and reception. This size does not include the parity bit, if any. If CSTOPB is set, two stop bits are used, otherwise one stop bit. For example, at 110 baud, two stops bits are required.

If PARENB is set, parity generation and detection is enabled and a parity bit is added to each character. If parity is enabled, the PARODD flag specifies odd parity if set, otherwise even parity is used.

If CREAD is set, the receiver is enabled. Otherwise no characters will be received.

If HUPCL is set, the line will be disconnected when the last process with the line open closes it or terminates. That is, the data-terminal-ready signal will not be asserted.

If CLOCAL is set, the line is assumed to be a local, direct connection with no modem control. Otherwise modem control is assumed.

The initial hardware control value after open is B300, CS8, CREAD, HUPCL.

The *c_lflag* field of the argument structure is used by the line discipline to control terminal functions. The basic line discipline (0) provides the following:

| | | |
|--------|---------|--|
| ISIG | 0000001 | Enable signals. |
| ICANON | 0000002 | Canonical input (erase and kill processing). |
| XCASE | 0000004 | Canonical upper/lower presentation. |
| ECHO | 0000010 | Enable echo. |
| ECHOE | 0000020 | Echo erase character as BS-SP-BS. |
| ECHOK | 0000040 | Echo NL after kill character. |
| ECHONL | 0000100 | Echo NL. |
| NOFLSH | 0000200 | Disable flush after interrupt or quit. |

If ISIG is set, each input character is checked against the special control characters INTR and QUIT. If an input character matches one of these control characters, the function associated with that character is performed. If ISIG is not set, no checking is done. Thus these special input functions are possible only if ISIG is set. These functions may be disabled individually by changing the value of the control character to an unlikely or impossible

value (e.g. 0377).

If ICANON is set, canonical processing is enabled. This enables the erase and kill edit functions, and the assembly of input characters into lines delimited by NL, EOF, and EOL. If ICANON is not set, read requests are satisfied directly from the input queue. A read will not be satisfied until at least MIN characters have been received or the timeout value TIME has expired. This allows fast bursts of input to be read efficiently while still allowing single character input. The MIN and TIME values are stored in the position for the EOF and EOL characters respectively. The time value represents tenths of seconds.

If XCASE is set, and if ICANON is set, an upper-case letter is accepted on input by preceding it with a \ character, and is output preceded by a \ character. In this mode, the following escape sequences are generated on output and accepted on input:

| | |
|------|------|
| for: | use: |
| \ | \\ |
| [| \[|
| { | \{ |
| } | \} |
| \ | \\ |

For example, A is input as \a, \n as \\n, and \N as \\N.

If ECHO is set, characters are echoed as received.

When ICANON is set, the following echo functions are possible. If ECHO and ECHOE are set, the erase character is echoed as ASCII BS SP BS, which will clear the last character from a CRT screen. If ECHOE is set and ECHO is not set, the erase character is echoed as ASCII SP BS. If ECHOK is set, the NL character will be echoed after the kill character to emphasize that the line will be deleted. Note that an escape character preceding the erase or kill character removes any special function. If ECHONL is set, the NL character will be echoed even if ECHO is not set. This is useful for terminals set to local echo (so-called half duplex). Unless escaped, the EOF character is not echoed. Because EOT is the default EOF character, this prevents terminals that respond to EOT from hanging up.

If NOFLSH is set, the normal flush of the input and output queues associated with the quit and interrupt characters will not be done.

The initial line-discipline control value is all bits clear.

The primary *ioctl*(2) system calls have the form:

```
ioctl (fdes, command, arg)
struct termio *arg;
```

The commands using this form are:

| | |
|---------|--|
| TCGETA | Get the parameters associated with the terminal and store in the <i>termio</i> structure referenced by <i>arg</i> . |
| TCSETA | Set the parameters associated with the terminal from the structure referenced by <i>arg</i> . The change is immediate. |
| TCSETAW | Wait for the output to drain before setting the new parameters. This form should be used when changing parameters that will affect output. |

TERMIO(7)

TCSETAF Wait for the output to drain, then flush the input queue and set the new parameters.

Additional *ioctl*(2) calls have the form:

ioctl (fildes, command, arg)
int arg;

The commands using this form are:

TCSBRK Wait for the output to drain. If *arg* is 0, then send a break (zero bits for 0.25 seconds).

TCXONC Start/stop control. If *arg* is 0, suspend output; if 1, restart suspended output.

TCFLSH If *arg* is 0, flush the input queue; if 1, flush the output queue; if 2, flush both the input and output queues.

FIONREAD Return the number of characters currently in a terminal's input buffer into the integer pointer *rg*. ICANON mode must be set for this option to work.

FILES

/dev/tty
/dev/tty*
/dev/console

SEE ALSO

stty(1), ioctl(2).

TERMIO(7)

TTY(7)

TTY(7)

NAME

tty — controlling terminal interface

DESCRIPTION

The file */dev/tty* is, in each process, a synonym for the control terminal associated with the process group of that process, if any. It is useful for programs or shell sequences that wish to be sure of writing messages on the terminal no matter how output has been redirected. It can also be used for programs that demand the name of a file for output, when typed output is desired and it is tiresome to find out what terminal is currently in use.

FILES

/dev/tty
/dev/tty*

NAME

intro — introduction to system maintenance procedures

DESCRIPTION

This section outlines procedures that will be of interest to those charged with the task of system maintenance. Included are discussions on the topics of boot procedures and recovery from crashes.

BUGS

No manual can take the place of good, solid experience.

NAME

boot — startup procedures

DESCRIPTION

A 68000 UNIX system is typically started by a two-stage process. The first is a primary bootstrap which is used to read in the system itself.

The primary bootstrap, when read into memory and executed, sets up memory management if necessary, and types a prompt message on the console. Then it reads from the console a device specification (see below) followed immediately by a pathname. This program finds the corresponding file on the given device, loads that file into the proper memory location, and then transfers control of the program. Normal line editing characters can be used.

Conventionally, the name of the current version of the system is `‘/unix’`. Then, the recipe is:

- 1) Load the boot program by fiddling with the console keys and crt as appropriate for your hardware.
- 2) When the `“:”` prompt is given, type [for example]
`fpy(0,0)unix`
or
`hd(0,0)unix`

depending on whether you are loading from floppy or hard disk, respectively. The first 0 indicates the physical unit number; the second indicates the block number of the beginning of the logical file system (device) to be searched. (See below).

When asked for the device name, a list of valid device names can be obtained by typing a `“?”` followed by a carriage return. A carriage return by itself boots the UNIX system on the default device.

When the system is running, it types a `“#”` prompt. After doing any file system checks via `fsck(1)` and setting the date (`date(1)`), the system can be brought up for standard operation by typing `init 2` in response to the `“#”` prompt, then an EOT (control-d) when the system requests it.

Device Specifications

A device specification has the following form:

`device(unit,offset)`

where *device* is the type of the device to be searched, *unit* is the unit number of the device, and *offset* is the block offset of the file system on the device. Device specifications vary according to which 68000 UNIX system you are using. Check manufacturer's instructions for the device specifications.

For example, the specification

`hp(1,7000)`

would indicate an HP disk, unit 1, and the file system found starting at block 7000.

ROM Programs

Programs to call the primary bootstrap may be installed in read-only memories or manually keyed into main memory. Each program is position-independent but should be placed well above location 0 so it will

not be overwritten. See manufacturer's instructions for a manually keyed-in ROM boot program, should one become necessary.

FILES

/unix — system code

NAME

crash — what to do when the system crashes

DESCRIPTION

This entry gives at least a few clues about how to proceed if the system crashes. It can't pretend to be complete.

In restarting after a crash, always bring up the system single-user, as specified in *boot(8)* as modified for your particular installation. Then perform an *fsck(1M)* on all file systems which could have been in use at the time of the crash. If any serious file system problems are found, they should be repaired. When you are satisfied with the health of your disks, check and set the date if necessary, then come up multi-user.

To even boot UNIX at all, certain files (and the directories leading to them) must be intact. First, the initialization program */etc/init* must be present and executable. For *init* to work correctly, */dev/console*, */bin/sh* and */bin/env* must be present. If one of these does not exist, the symptom is best described as thrashing. *Init* will go into a *fork/exec* loop trying to create a Shell with proper standard input and output. The file */etc/rc* should also be there and be executable; the system will come up but will not be fully initialized without it.

If you cannot get the system to boot, a runnable system must be obtained from a backup medium. The root file system may then be doctored as a mounted file system as described below. If there are any problems with the root file system, it is probably prudent to go to a backup system to avoid working on a mounted file system.

Repairing disks. The first rule to keep in mind is that an addled disk should be treated gently; it shouldn't be mounted unless necessary, and if it is very valuable yet in quite bad shape, perhaps it should be copied before trying surgery on it. This is an area where experience and informed courage count for much.

Fsck(1M) is adept at diagnosing and repairing file system problems. It first identifies all of the files that contain bad (out of range) blocks or blocks that appear in more than one file. Any such files are then identified by name and *fsck* requests permission to remove them from the file system. Files with bad blocks should be removed. In the case of duplicate blocks, all of the files except the most recently modified should be removed. The contents of the survivor should be checked after the file system is repaired to ensure that it contains the proper data. (Note that running *fsck* with the *-n* option will cause it to report all problems without attempting any repair.)

Fsck will also report on incorrect link counts and will request permission to adjust any that are erroneous. In addition, it will reconnect any files or directories that are allocated but have no file system references to a "lost+found" directory. Finally, if the free list is bad (out of range, missing, or duplicate blocks) *fsck* will, with the operators concurrence, construct a new one.

Why did it crash? UNIX types a message on the console typewriter when it voluntarily crashes. Here is the current list of such messages, with enough information to provide a hope at least of the remedy. The message has the form "panic: ...", possibly accompanied by other information. Left unstated in all cases is the possibility that hardware or software error

produced the message in some unexpected way.

blkdev

The *getblk* routine was called with a nonexistent major device as argument. Definitely hardware or software error.

devtab

Null device table entry for the major device used as argument to *getblk*. Definitely hardware or software error.

dpfrelse

The list of processes currently mapped into the memory management unit has been lost (68451 only).

ilnit

An I/O error reading the super-block for the root file system during initialization.

interrupt stack overflow

The kernel ran out of stack space on an interrupt. Subroutine depth is too great or too many local variables.

kernel memory management error

Bus error or address error in supervisor mode. Can be a software or hardware problem.

no fs

A device has disappeared from the mounted-device table. Definitely hardware or software error.

no imt

Like "no fs", but produced elsewhere.

no clock

During initialization, neither the line nor programmable clock was found to exist.

no procs

Process table has been destroyed.

I/O error in swap

An unrecoverable I/O error during a swap. Really shouldn't be a panic, but it is hard to fix.

oops!!! syscall

The interrupt vector for system calls is missing.

out of swap space

A program needs to be swapped out, and there is no more swap space. It has to be increased. This really shouldn't be a panic, but there is no easy fix.

timeout table overflow

The timeout table overflowed. The timeout table is not large enough or some routine is starting up too many timeouts.

trap

An unexpected trap has occurred within the system. This is accompanied by the following information:

trap type

- 2 bus error
- 3 address error

- 4 illegal instruction
- 5 divide by zero
- 6 CHK instruction
- 7 TRAPV instruction
- 8 privilege violation
- 9 trace
- 10 1010 emulator
- 11 1111 emulator
- 12-255 unexpected interrupt

virtual address (for bus/address errors only)

physical address

instruction register

function code

mmu dump

program counter

status register

program id

registers

In some of these cases it is possible for hex 1000 to be added into the trap type; this indicates that the processor was in user mode when the trap occurred.

SEE ALSO

adb(1), fsck(1M), boot(8).

NAME

delivermail — deliver mail to arbitrary people

SYNOPSIS

```
/etc/delivermail [ -[fr] address ] [ -a ] [ -e[empqw] ] [ -n ] [
-m ] [ -s ] [ -l ] [ -h N ] address ...
```

DESCRIPTION

Delivermail delivers a letter to one or more people, routing the letter over whatever networks are necessary. *Delivermail* will do inter-net forwarding as necessary to deliver the mail to the correct place.

Delivermail is not intended as a user interface routine; it is expected that other programs will provide user-friendly front ends, and *delivermail* will be used only to deliver pre-formatted messages.

Delivermail reads its standard input up to a control-D or a single dot and sends a copy of the letter found there to all of the addresses listed. If the *-i* flag is given, single dots are ignored. It determines the network to use based on the syntax of the addresses. Addresses containing the character "@" or the word "at" are sent to BNET; and addresses containing "!" are sent to the UUCP net. Other addresses are assumed to be local.

Local addresses are looked up in the file */usr/lib/allases* and aliased appropriately. Aliasing can be prevented by preceding the address with a backslash or using the *-n* flag. Normally the sender is not included in any alias expansions, e.g., if "john" sends to "group", and "group" includes "john" in the expansion, then the letter will not be delivered to "john". The *-m* flag disables this suppression.

Delivermail computes the person sending the mail by looking at your login name. The "from" person can be explicitly specified by using the *-f* flag; or, if the *-a* flag is given, *delivermail* looks in the body of the message for a "From:" or "Sender:" field in ARPANET format. The *-f* and *-a* flags can be used only by the special users *root* and *network*, or if the person you are trying to become is the same as the person you are. The *-r* flag is entirely equivalent to the *-f* flag; it is provided for ease of interface only.

The *-ex* flag controls the disposition of error output, as follows:

- e** Print errors on the standard output, and echo a copy of the message when done. It is assumed that a network server will return the message back to the user.
- m** Mail errors back to the user.
- p** Print errors on the standard output.
- q** Throw errors away; only exit status is returned.
- w** Write errors back to the user's terminal, but only if the user is still logged in and write permission is enabled; otherwise errors are mailed back.

If the error is not mailed back, and if the mail originated on the machine where the error occurred, the letter is appended to the file "dead.letter" in the sender's home directory.

If the first character of the user name is a vertical bar, the rest of the user name is used as the name of a program to pipe the mail to. It may be necessary to quote the name of the user to keep *delivermail* from suppressing

the blanks from between arguments.

The message is normally edited to eliminate "From" lines that might confuse other mailers. In particular, "From" lines in the header are deleted, and "From" lines in the body are prepended by ">". The `-s` flag saves "From" lines in the header.

The `-h` flag gives a "hop-count", i.e., a measure of how many times this message has been processed by *delivermail* (presumably on different machines). Each time *delivermail* processes a message, it increases the hop-count by one; if it exceeds 30 *delivermail* assumes that an alias loop has occurred and it aborts the message. The hop-count defaults to zero.

Delivermail returns an exit status describing what it did. The codes are defined in *mailxits.h*:

| | |
|------------------|--|
| 0 EX_OK | Successful completion on all addresses. |
| 2 EX_NOUSER | User name not recognized. |
| 3 EX_UNAVAILABLE | Catchall meaning necessary resources were not available. |
| 4 EX_SYNTAX | Syntax error in address. |
| 5 EX_SOFTWARE | Internal software error, including bad arguments. |
| 6 EX_OSERR | Temporary operating system error, such as "cannot fork". |
| 7 EX_NOHOST | Host name not recognized. |

FILES

| | |
|-------------------------------|---|
| <code>/usr/lib/aliases</code> | to alias names |
| <code>/bin/mail</code> | to deliver local mail |
| <code>/etc/netmailer</code> | to deliver BNET mail |
| <code>/bin/mail</code> | to deliver UUCP mail (<code>/bin/mail</code> knows how...) |
| <code>/tmp/mail*</code> | temp file |
| <code>/tmp/xscript*</code> | saved transcript |
| <code>/dev/log</code> | to log status (optional) |

SEE ALSO

mail(1), aliases(7), netmailer(8).

BUGS

Delivermail sends one copy of the letter to each user; it should send one copy of the letter to each host and distribute to multiple users there whenever possible.

Delivermail assumes the addresses can be represented as one word. This is incorrect according to the ARPANET mail protocol RFC 733 (NIC 41952), but is consistent with the real world.

NAME

netmail — the bnet network mail system

DESCRIPTION

The bnet network mail system consists of the following programs:

`/etc/bnetmaild`

a simple mail daemon run by crontab or by hand. Looks in the *mail spool directory* (`/usr/spool/netmail`) for files to send out onto the network. Uses *remsh* to send mail to remote hosts. Deletes mail if the mail is apparently successfully sent. Deletes mail found lying around which is more than one week old; apparently the destination host in this case is off the net. Accepts no arguments.

`/etc/delivermail`

exec'd by `/bin/mail` to deliver mail to users or networks depending on the contents of the address of the mail. If the address contains an

@ then deliver to the bnet network, else if the address has a
! then deliver to the uucp network,
else deliver locally.

`/etc/netmailer`

exec'd by `/etc/delivermail` to "deliver" netmail. Mail is actually deposited in `/usr/spool/netmail` with appropriate network mail headers prepended. `/etc/bnetmaild` actually sends the mail to the network. See *netmailer*(8) for a description of flag arguments.

`/bin/mail`

has been modified to *exec* `/etc/delivermail` (*delivermail*(8)) which does aliasing and re-routing of mail destined for the b-network.

FILES

| | |
|--|------------------------------------|
| <code>/usr/spool/netmail</code> | directory for network mail |
| <code>/usr/spool/netmail/bnetXXXXXX</code> | actual mail file(s), XXXXXX = pid. |

SEE ALSO

mail(1), remsh(1), delivermail(8), netmailer(8).

BUGS

Many, no doubt; for example, lots of work should be done on `/etc/bnetmaild`, i.e., if a piece of mail is deleted due to its being old or otherwise undeliverable, notification should be sent to the originator. Soon, however, *bnetmaild* will be replaced by *sendmail*.

A front-end is needed for mail, such as *Mail* (ucb).

NAME

netmailer — deliver mail to BNET

SYNOPSIS

/etc/netmailer from-address to-host to-user

DESCRIPTION

Netmailer queues the letter found on its standard input for delivery to the host and user specified. The actual delivery will be performed by the BNET mailer daemon (*/etc/bnetmaild*).

If the letter does not appear to have a full BNET header, *netmailer* will insert "Date:" and "From:" fields in the proper format. The "From:" person is determined by the *from-address* argument, with colons translated to periods and "@<local-host>" appended. The "<local-host>" is obtained from the file */usr/lib/uucp/SYSTEMNAME*.

FILES

*/usr/spool/netmail/**

SEE ALSO

delivermail(8), *netmail(8)*.